

Print date: 13.12.2018
Version: 4

WEBAC 155
Revision date: 13.12.2018
Issue date: 13.12.2018

EN
Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation WEBAC 155
1C PU Injection Foam Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

isocyanate component for polyurethane foam resin

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

WEBAC-Chemie GmbH

Fahrenberg 22
22885 Barsbüttel / Hamburg
GERMANY

Telephone: +49 40 67057-0

Telefax: +49 40 6703227

Dept. responsible for information:

laboratory

E-mail

sdb@webac.de

1.4. Emergency telephone number

Giftinformationszentrum-Nord +49 551 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Resp. Sens. 1 / H334

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Carc. 2 / H351

Carcinogenicity

Suspected of causing cancer.

STOT SE 3 / H335

STOT-single exposure

May cause respiratory irritation.

STOT RE 2 / H373

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317

May cause an allergic skin reaction.

H351

Suspected of causing cancer.

H335

May cause respiratory irritation.

H373

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves and eye/face protection.

P284

In case of inadequate ventilation wear respiratory protection.

P304 + P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342 + P311

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

Hazard components for labelling

diphenylmethanediisocyanate, isomeres and homologues

Print date: 13.12.2018
Version: 4

WEBAC 155
Revision date: 13.12.2018
Issue date: 13.12.2018

EN
Page 2 / 9

Supplemental Hazard information (EU)

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. **Other hazards**

No information available.

SECTION 3: Composition / information on ingredients

3.2. **Mixtures**

Description isocyanate component for polyurethane foam resin

Hazardous ingredients

EC No. CAS No. INDEX No.	REACH No. Designation classification: // Remark	Wt %
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Resp. Sens. 1 H334 / Carc. 2 H351 / STOT RE 2 H373 / STOT SE 3 H335 Specific concentration limit (SCL): Resp. Sens. 1 H334 >= 0,1 / Eye Irrit. 2 H319 >= 5 / Skin Irrit. 2 H315 >= 5 / STOT SE 3 H335 >= 5	25 - 50
229-194-7 6425-39-4	01-2119969278-20-xxxx 2,2'-dimorpholinyl-diethyl ether Eye Irrit. 2 H319	1 - 2,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Use appropriate container to avoid environmental contamination.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke.

Personal protection equipment: refer to section 8.

Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container.

Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

People who spray this preparation should have regular pulmonary function tests.

8.1. Control parameters

Occupational exposure limit values:

diphenylmethanediisocyanate, isomeres and homologues

CAS No. 9016-87-9

EH40 WEL, TWA: 0,02 mg/m³

EH40 WEL, STEL: 0,07 mg/m³

Remark: measured as NCO

Additional information

Print date: 13.12.2018
Version: 4

WEBAC 155
Revision date: 13.12.2018
Issue date: 13.12.2018

EN
Page 4 / 9

TWA : long-term occupational exposure limit value
STEL : short-term occupational exposure limit value
Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. When spraying, wear self-contained breathing apparatus.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.
Suitable respiratory protection apparatus: Combination filtering device (EN 14387)

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: brown

Odour: characteristic

Odour threshold: not determined

pH at 20 °C: not applicable

Melting point/freezing point: not applicable

Initial boiling point and boiling range: not determined

Flash point: > 101 °C
Method: DIN 53213

flammability

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: not determined

Upper explosion limit: not determined

Vapour pressure at 20 °C: 0,2375 mbar
Method: calculated

Relative density:

Density at 20 °C: 1,06 g/cm³
Method: calculated

Solubility(ies):

Water solubility (g/L) at 20 °C: insoluble

Partition coefficient: n-octanol/water: see section 12

Auto-ignition temperature: not applicable

Decomposition temperature: not determined

Print date: 13.12.2018
Version: 4

WEBAC 155
Revision date: 13.12.2018
Issue date: 13.12.2018

EN
Page 5 / 9

Viscosity at 40 °C:	> 20,5 mm²/s
Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
solvent content:	
Organic solvents:	0 Wt %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

2,2'-dimorpholinyl-diethyl ether

oral, LD50, Rat: 2025 mg/kg

dermal, LD50, Rabbit: 3038 mg/kg

diphenylmethanediisocyanate, isomeres and homologues

oral, LD50, Rat: > 10000 mg/kg

dermal, LD50, Rabbit: > 9400 mg/kg

inhalative (dust and mist), LC50, Rat: 1,5 mg/l (4 h)

Method: calculated

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

diphenylmethanediisocyanate, isomeres and homologues

Skin:

May cause sensitization by skin contact.

Respiratory system:

May cause sensitization by inhalation.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of causing cancer.

diphenylmethanediisocyanate, isomeres and homologues

Carcinogenicity

Evidence for possible carcinogenic effects in experimental animals existent.; Determined in aerosol.; No indication of human carcinogenicity.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

diphenylmethanediisocyanate, isomeres and homologues

Specific target organ toxicity (single exposure), Irritation

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Because of the isocyanate components' properties of this and with consideration of similar preparations the following applies: This mixture may cause acute irritation and/or sensitization of airways which lead to tightness in thorax, short-breath and asthmatic complaints. After sensitization even concentrations below the exposure limit values may cause asthma. Repeated inhaling can lead to permanent illness of the respiratory tract.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

diphenylmethanediisocyanate, isomeres and homologues

Fish toxicity, LC50, Brachydanio rerio (zebra-fish): > 1000 mg/l (96 h)

Method: OECD 203

Algae toxicity, ErC50, Scenedesmus subspicatus: > 1640 mg/l (72 h)

Method: OECD 201

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 1000 mg/l (24 h)

Method: OECD 202

Bacteria toxicity, EC50, Activated sludge: > 100 mg/l (3 h)

Method: OECD 209

Long-term Ecotoxicity

diphenylmethanediisocyanate, isomeres and homologues

Daphnia toxicity, NOEC, Daphnia magna: > 10 mg/l (21 D)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

080501* waste isocyanates
070208* other still bottoms and reaction residues

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 0,000

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

MAL-code (1993):

4-3

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Resp. Sens. 1	Respiratory or skin sensitisation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Carc. 2	Carcinogenicity	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT RE 2	STOT-repeated exposure	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

WEBAC®

Print date: 13.12.2018
Version: 4

WEBAC 155
Revision date: 13.12.2018
Issue date: 13.12.2018

EN
Page 9 / 9

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.