

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation WEBAC 4204 Comp. B
Epoxy Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

hardener/amine component for epoxy resin

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

WEBAC-Chemie GmbH

Fahrenberg 22
22885 Barsbüttel / Hamburg
GERMANY

Telephone: +49 40 67057-0

Telefax: +49 40 6703227

Dept. responsible for information:

laboratory

E-mail

sdb@webac.de

1.4. Emergency telephone number

Giftinformationszentrum-Nord +49 551 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 / H302

Acute toxicity (oral)

Harmful if swallowed.

Acute Tox. 4 / H312

Acute toxicity (dermal)

Harmful in contact with skin.

Skin Corr. 1B / H314

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Eye Dam. 1 / H318

Serious eye damage/eye irritation

Causes serious eye damage.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Repr. 2 / H361

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT RE 1 / H372

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H302 + H312

Harmful if swallowed or in contact with skin.

H314

Causes severe skin burns and eye damage.

H317

May cause an allergic skin reaction.

H361

Suspected of damaging fertility or the unborn child.

H372

Causes damage to organs through prolonged or repeated exposure.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves and eye/face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER or doctor/ physician.

Hazard components for labelling

Polymer

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 2 / 10

2-piperazin-1-ylethylamine
Amines, polyethylenepoly, triethylenetetramine fraction
4,4'-Methylenbis(cyclohexylamine)

Supplemental Hazard information (EU)

not applicable

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description hardener/amine component for epoxy resin

Hazardous ingredients

EC No. CAS No. INDEX No.	REACH No. Designation classification: // Remark	Wt %
205-411-0 140-31-8 612-105-00-4	01-2119471486-30-xxxx 2-piperazin-1-ylethylamine Acute Tox. 4 H302 / Acute Tox. 3 H311 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Repr. 2 H361 / STOT RE 1 H372 / Aquatic Chronic 3 H412	25 - 50
292-588-2 90640-67-8 612-065-00-8	01-2119487919-13-xxxx Amines, polyethylenepoly, triethylenetetramine fraction Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	25 - 50
603-894-6 135108-88-2	01-2119983522-33-xxxx Polymer Acute Tox. 4 H302 / Skin Corr. 1C H314 / Skin Sens. 1 H317 / STOT RE 2 H373 / Aquatic Chronic 3 H412	10 - 25
202-859-9 100-51-6 603-057-00-5	01-2119492630-38-xxxx benzyl alcohol Acute Tox. 4 H302 / Acute Tox. 4 H332 / Eye Irrit. 2 H319	2,5 - 10
618-561-0 9046-10-0	01-2119557899-12-xxxx Poly(oxypropylene)diamine Skin Corr. 1C H314 / Aquatic Chronic 3 H412	2,5 - 10
217-168-8 1761-71-3	01-2119541673-38-xxxx 4,4'-Methylenbis(cyclohexylamine) Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / STOT RE 2 H373	1 - 2,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 4 / 10

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

DNEL:

benzyl alcohol

INDEX No. 603-057-00-5 / EC No. 202-859-9 / CAS No. 100-51-6

DNEL acute dermal, short-term (systemic), Workers: 47 mg/kg bw/day

DNEL long-term dermal (systemic), Workers: 9,5 mg/kg bw/day

DNEL acute inhalative (systemic), Workers: 450 mg/m³

DNEL long-term inhalative (systemic), Workers: 90 mg/m³

2-piperazin-1-ylethylamine

INDEX No. 612-105-00-4 / EC No. 205-411-0 / CAS No. 140-31-8

DNEL acute dermal, short-term (local), Workers: 4 mg/dm²

DNEL acute dermal, short-term (systemic), Workers: 20 mg/kg

DNEL long-term dermal (local), Workers: 0,6 mg/dm²

DNEL long-term dermal (systemic), Workers: 3,33 mg/kg bw/day

DNEL acute inhalative (systemic), Workers: 21,4 mg/m³

DNEL long-term inhalative (systemic), Workers: 3,6 mg/m³

4,4'-Methylenbis(cyclohexylamine)

EC No. 217-168-8 / CAS No. 1761-71-3

DNEL long-term dermal (systemic), Workers: 0,1 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 1 mg/m³

Poly(oxypropylene)diamine

EC No. 618-561-0 / CAS No. 9046-10-0

DNEL long-term dermal (local), Workers: 62,3 mg/dm²

DNEL long-term dermal (systemic), Workers: 2,5 mg/kg bw/day

PNEC:

benzyl alcohol

INDEX No. 603-057-00-5 / EC No. 202-859-9 / CAS No. 100-51-6

PNEC aquatic, freshwater: 1 mg/l

PNEC aquatic, marine water: 0,1 mg/l

PNEC aquatic, intermittent release: 2,3 mg/l

PNEC sediment, freshwater: 5,27 mg/kg

PNEC, soil: 0,456 mg/kg

PNEC sewage treatment plant (STP): 39 mg/l

2-piperazin-1-ylethylamine

INDEX No. 612-105-00-4 / EC No. 205-411-0 / CAS No. 140-31-8

PNEC aquatic, freshwater: 0,058 mg/l

PNEC aquatic, marine water: 0,0058 mg/l

PNEC aquatic, intermittent release: 0,58 mg/l

PNEC sediment, freshwater: 215 mg/kg

PNEC sediment, marine water: 21,5 mg/kg

PNEC, soil: 42,9 mg/kg

PNEC sewage treatment plant (STP): 250 mg/l

4,4'-Methylenbis(cyclohexylamine)

EC No. 217-168-8 / CAS No. 1761-71-3

PNEC aquatic, freshwater: 0,008 mg/l

PNEC aquatic, marine water: 0,0008 mg/l

PNEC aquatic, intermittent release: 0,08 mg/l

PNEC sediment, freshwater: 0,39 mg/kg

PNEC sediment, marine water: 0,039 mg/kg

PNEC, soil: 0,072 mg/kg

PNEC sewage treatment plant (STP): 80 mg/l

Poly(oxypropylene)diamine

EC No. 618-561-0 / CAS No. 9046-10-0

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 5 / 10

PNEC aquatic, freshwater: 0,015 mg/l
PNEC aquatic, marine water: 0,0142 mg/l
PNEC aquatic, intermittent release: 0,15 mg/l
PNEC sediment, freshwater: 0,132 mg/kg
PNEC sediment, marine water: 0,125 mg/kg
PNEC, soil: 0,0176 mg/kg
PNEC sewage treatment plant (STP): 7,5 mg/l
PNEC Secondary Poisoning: 6,93 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. In case of inadequate ventilation wear respiratory protection.

Personal protection equipment

Respiratory protection

Suitable respiratory protection apparatus:
Usually no personal respirative protection necessary.

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:	Liquid
Colour:	yellowish
Odour:	like amine
Odour threshold:	not determined
pH at 20 °C:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	not determined
Flash point:	> 101 °C Method: DIN 53213

flammability

Burning time (s):	not applicable
--------------------------	-----------------------

Upper/lower flammability or explosive limits:

Lower explosion limit:	not determined
Upper explosion limit:	not determined

Vapour pressure at 20 °C:

0,0954 mbar Method: calculated

Relative density:

Density at 20 °C:	0,99 g/cm³ Method: calculated
--------------------------	----------------------------------------------------

Solubility(ies):

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 6 / 10

Water solubility (g/L) at 20 °C: insoluble
Partition coefficient: n-octanol/water: see section 12
Auto-ignition temperature: not determined
Decomposition temperature: not applicable
Viscosity at 40 °C: > 20,5 mm²/s

Explosive properties: not applicable
Oxidising properties: not applicable

9.2. **Other information**

Solvent

Organic solvents: 0 Wt %

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

Harmful if swallowed.

Harmful in contact with skin.

benzyl alcohol

oral, LD50, Rat: 1230 mg/kg

dermal, LD50, Rabbit: 2000 mg/kg

inhalative (dust and mist), LC50, Rat: > 4,178 mg/l (4 h)

2-piperazin-1-ylethylamine

oral, LD50, Rat: 2000 mg/kg

dermal, LD50, Rabbit: 866 mg/kg

Method: literature value

4,4'-Methylenbis(cyclohexylamine)

oral, LD50, Rat: 625 mg/kg

dermal, LD50, Rabbit: 2110 mg/kg

Amines, polyethylenepoly, triethylenetetramine fraction

oral, LD50, Rat: 1716 mg/kg

dermal, LD50, Rat

dermal, LD50, Rabbit: 1465 mg/kg

oral, LD50, Mouse: 1600 mg/kg

oral, LD50, Rabbit: 5500 mg/kg

Polymer

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 7 / 10

oral, LD50, Rat: 367 mg/kg
dermal, LD50, Rabbit: > 2000 mg/kg

Poly(oxypropylene)diamine
oral, LD50, Rat: 2885 mg/kg
dermal, LD50, Rabbit: 2090 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of damaging fertility or the unborn child.

STOT-single exposure; STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

No information available.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

benzyl alcohol

Fish toxicity, LC50: 460 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 230 mg/l (48 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 770 mg/l (72 h)

2-piperazin-1-ylethylamine

Fish toxicity, LC50, Poecilia reticulata (Guppy): 368 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 58 mg/l (48 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/l (72 h)

Poly(oxypropylene)diamine

Fish toxicity, LC50, Leuciscus idus (golden orfe): > 15 mg/l (96 h)

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 15 mg/l (72 h)

Bacteria toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): 15 mg/l (96 h)

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

benzyl alcohol

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 310 mg/l (72 h)

12.2. Persistence and degradability

2-piperazin-1-ylethylamine

:

Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 8 / 10

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

070208* other still bottoms and reaction residues

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 2735

14.2. UN proper shipping name

Land transport (ADR/RID):

Amines, liquid, corrosive, n.o.s.
(N-AMINOETHYLPIPERAZINE)

Sea transport (IMDG):

AMINES, LIQUID, CORROSIVE, N.O.S.
(N-AMINOETHYLPIPERAZINE)

Air transport (ICAO-TI / IATA-DGR):

Amines, liquid, corrosive, n.o.s.
(N-AMINOETHYLPIPERAZINE)

14.3. Transport hazard class(es)

8

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

E

Sea transport (IMDG)

EmS-No.

F-A, S-B

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 9 / 10

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 86,000

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/j) ; VOC limit value: 500 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 86,000

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 3 / H311	Acute toxicity (dermal)	Toxic in contact with skin.
Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT RE 1 / H372	STOT-repeated exposure	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Skin Corr. 1C / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4	Acute toxicity (oral)	Calculation method.
Acute Tox. 4	Acute toxicity (dermal)	Calculation method.
Skin Corr. 1B	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Repr. 2	Reproductive toxicity	Calculation method.
STOT RE 1	STOT-repeated exposure	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

WEBAC®

Print date: 01.03.2019
Version: 7

WEBAC 4204 Comp. B
Revision date: 01.03.2019
Issue date: 01.03.2019

EN
Page 10 / 10

EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.