

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**WEBAC®**

Print date: 12.11.2020  
Version: 6

WEBAC 250 Comp. A1  
Revision date: 12.11.2020  
Issue date: 12.11.2020

EN  
Page 1 / 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name/designation WEBAC 250 Comp. A1  
Polyacrylic Gel

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**  
acrylate component for gels

**1.3. Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

WEBAC-Chemie GmbH  
Fahrenberg 22  
22885 Barsbüttel / Hamburg  
GERMANY

Telephone: +49 40 67057-0  
Telefax: +49 40 6703227

**Department responsible for information:**

laboratory  
E-mail

sdb@webac.de

**1.4. Emergency telephone number**

Giftinformationszentrum-Nord +49 551 19240

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Warning**

**Hazard statements**

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H317

May cause an allergic skin reaction.

**Precautionary Statements**

P280

Wear protective gloves and eye/face protection.

**Hazard components for labelling**

2-hydroxyethyl methacrylate

**Supplemental hazard information**

not applicable

**2.3. Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

**3.2. Mixtures**

**Description** acrylate component for gels

**Hazardous ingredients**

**EC No.**

**REACH No.**

**CAS No.**

**Designation**

**INDEX No.**

**classification: // Remark**

**weight-%**

Print date: 12.11.2020  
Version: 6

WEBAC 250 Comp. A1  
Revision date: 12.11.2020  
Issue date: 12.11.2020

EN  
Page 2 / 8

212-782-2	01-2119490169-29-xxxx	
868-77-9	2-hydroxyethyl methacrylate	50 - 100
607-124-00-X	Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317	
203-872-2	01-2119457857-21-xxxx	
111-46-6	2,2' -oxybisethanol	2,5 - 10
603-140-00-6	Acute Tox. 4 H302	

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

not applicable

#### DNEL:

2,2'-oxybisethanol

INDEX No. 603-140-00-6 / EC No. 203-872-2 / CAS No. 111-46-6

DNEL long-term dermal (systemic), Workers: 106 mg/kg

DNEL long-term inhalative (local), Workers: 60 mg/m<sup>3</sup>

2-hydroxyethyl methacrylate

INDEX No. 607-124-00-X / EC No. 212-782-2 / CAS No. 868-77-9

DNEL long-term dermal (systemic), Workers: 1,3 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 4,9 mg/m<sup>3</sup>

#### PNEC:

2,2'-oxybisethanol

INDEX No. 603-140-00-6 / EC No. 203-872-2 / CAS No. 111-46-6

PNEC aquatic, freshwater: 10 mg/L

PNEC aquatic, marine water: 1 mg/L

PNEC aquatic, intermittent release: 10 mg/L

PNEC sediment, freshwater: 20,9 mg/kg

PNEC, soil: 1,53 mg/kg

PNEC sewage treatment plant (STP): 199,5 mg/L

2-hydroxyethyl methacrylate

INDEX No. 607-124-00-X / EC No. 212-782-2 / CAS No. 868-77-9

PNEC aquatic, freshwater: 0,482 mg/L

PNEC aquatic, marine water: 0,482 mg/L

PNEC aquatic, intermittent release: 1 mg/L

PNEC sediment, freshwater: 3,79 mg/kg

PNEC sediment, marine water: 3,79 mg/kg

PNEC, soil: 0,476 mg/kg

PNEC sewage treatment plant (STP): 10 mg/L

### 8.2. Exposure controls

Print date: 12.11.2020  
Version: 6

WEBAC 250 Comp. A1  
Revision date: 12.11.2020  
Issue date: 12.11.2020

EN  
Page 4 / 8

Provide good ventilation. This can be achieved with local or room suction. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. In case of inadequate ventilation wear respiratory protection.

#### **Personal protection equipment**

##### **Respiratory protection**

Suitable respiratory protection apparatus:

Usually no personal respiratory protection necessary.

##### **Hand protection**

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

##### **Eye/face protection**

Wear eye glasses with side protection according to EN 166.

##### **Body protection**

Wear suitable protective clothing.

##### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

##### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

##### **Appearance:**

**Physical state:**

**Liquid**

**Colour:**

**colourless**

**Odour:**

**characteristic**

**Odour threshold:**

**not determined**

**pH at 20 °C:**

**4,5 - 7,5 / 100,0 weight-%**

Method: DIN EN ISO 10523

**Melting point/freezing point:**

**not determined**

**Initial boiling point and boiling range:**

**not determined**

**Flash point:**

**> 110 °C**

Method: DIN 53213

##### **flammability**

**Burning time (s):**

**not applicable**

**Upper/lower flammability or explosive limits:**

**Lower explosion limit:**

**not determined**

**Upper explosion limit:**

**not determined**

**Vapour pressure at 20 °C:**

**8,9846 mbar**

Method: calculated

**Relative density:**

**Density at 20 °C:**

**1,04 g/cm<sup>3</sup>**

Method: calculated

**Solubility(ies):**

**Water solubility (g/L) at 20 °C:**

**mixable with water**

**Partition coefficient: n-octanol/water:**

**see section 12**

**Auto-ignition temperature:**

**not determined**

**Decomposition temperature:**

**not determined**

**Viscosity at °C:**

**5-30 mPas**

**Explosive properties:**

**not applicable**

Print date: 12.11.2020  
Version: 6

WEBAC 250 Comp. A1  
Revision date: 12.11.2020  
Issue date: 12.11.2020

EN  
Page 5 / 8

- Oxidising properties:** not applicable
- 9.2. **Other information**
- Solvent**
- Organic solvents:** 0 weight-%

## SECTION 10: Stability and reactivity

- 10.1. **Reactivity**  
No information available.
- 10.2. **Chemical stability**  
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**  
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**  
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.5. **Incompatible materials**  
not applicable
- 10.6. **Hazardous decomposition products**  
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## SECTION 11: Toxicological information

- Classification according to Regulation (EC) No 1272/2008 [CLP]  
No data on preparation itself available.
- 11.1. **Information on toxicological effects**
- Acute toxicity**
- 2,2'-oxybisethanol  
oral, LD50, Rat: 300 - 2000 mg/kg  
dermal, LD50, Rabbit: 13300 mg/kg  
oral, LD50, human.: 1120 mg/kg  
inhalative (vapours), LC0, Rat: > 4,6 mg/L (4 h)
- 2-hydroxyethyl methacrylate  
oral, LD50, Rat: > 5000 mg/kg  
dermal, LD50, Rabbit: > 5000 mg/kg
- Skin corrosion/irritation; Serious eye damage/eye irritation**  
Causes skin irritation.  
Causes serious eye irritation.
- Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
Based on available data, the classification criteria are not met.
- STOT-single exposure; STOT-repeated exposure**  
Based on available data, the classification criteria are not met.
- Aspiration hazard**  
Based on available data, the classification criteria are not met.
- Practical experience/human evidence**  
No information available.
- Overall Assessment on CMR properties**  
The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## SECTION 12: Ecological information

Print date: 12.11.2020  
Version: 6

WEBAC 250 Comp. A1  
Revision date: 12.11.2020  
Issue date: 12.11.2020

EN  
Page 6 / 8

Classification according to Regulation (EC) No 1272/2008 [CLP]  
There is no information available on the preparation itself .  
Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

##### 2,2' -oxybisethanol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 75200 mg/L (96 h)  
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 10000 mg/L (48 h)

##### 2-hydroxyethyl methacrylate

Fish toxicity, LC50, Oryzias latipes (Ricefish): > 100 mg/L (96 h)  
Method: OECD 203  
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 380 mg/L (48 h)  
Method: OECD 202  
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 836 mg/L (72 h)

#### Long-term Ecotoxicity

##### 2,2' -oxybisethanol

Algae toxicity, NOEC, Scenedesmus quadricauda: 2700 mg/L (8 D)

##### 2-hydroxyethyl methacrylate

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 24,1 mg/L (21 D)

#### 12.2. Persistence and degradability

##### 2,2' -oxybisethanol

Biodegradation: 92 % (28 D)  
Method: OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A  
Readily biodegradable (according to OECD criteria).

##### 2-hydroxyethyl methacrylate

Biodegradation: 84 % (28 D); evaluation Readily biodegradable (according to OECD criteria).  
Method: OECD 301D/ EEC 92/69/V, C.4-E

#### 12.3. Bioaccumulative potential

##### 2,2' -oxybisethanol

Partition coefficient: n-octanol/water: < 1  
No indication of bioaccumulation potential.

#### Bioconcentration factor (BCF)

##### 2,2' -oxybisethanol

Bioconcentration factor (BCF), Leuciscus idus (golden orfe): 100  
No indication of bioaccumulation potential.

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Dispose of waste according to applicable legislation.

##### List of proposed waste codes/waste designations in accordance with EWC

070208\* other still bottoms and reaction residues

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

##### Appropriate disposal / Package Recommendation

##### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

- 14.1. **UN number** not applicable
- 14.2. **UN proper shipping name**
- 14.3. **Transport hazard class(es)** not applicable
- 14.4. **Packing group** not applicable
- 14.5. **Environmental hazards**
- |                          |                |
|--------------------------|----------------|
| Land transport (ADR/RID) | not applicable |
| Marine pollutant         | not applicable |

14.6. **Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code -

**Sea transport (IMDG)**

EmS-No. not applicable

**Air transport (ICAO-TI / IATA-DGR)**

14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

#### SECTION 15: Regulatory information

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions**

VOC-value (in g/L): 31,130

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information

**Full text of classification in section 3:**

Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.

**Abbreviations and acronyms**

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

**WEBAC®**

Print date: 12.11.2020  
Version: 6

WEBAC 250 Comp. A1  
Revision date: 12.11.2020  
Issue date: 12.11.2020

EN  
Page 8 / 8

---

OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.