

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 1 / 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name/designation WEBAC 4520 Comp. B  
Epoxy Putty

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

hardener/amine component for epoxy resin  
Restricted to professional users.

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

WEBAC-Chemie GmbH  
Fahrenberg 22  
22885 Barsbüttel / Hamburg  
GERMANY

Telephone: +49 40 67057-0  
Telefax: +49 40 6703227

#### Department responsible for information:

laboratory

E-mail

sdb@webac.de

### 1.4. Emergency telephone number

Giftinformationszentrum-Nord +49 551 19240  
24 hr. emergency phone number

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 / H302

Acute toxicity (oral)

Harmful if swallowed.

Skin Corr. 1B / H314

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Eye Dam. 1 / H318

Serious eye damage/eye irritation

Causes serious eye damage.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Repr. 2 / H361

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT RE 2 / H373

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 / H411

Hazardous to the aquatic environment

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



Danger

#### Hazard statements

H302

Harmful if swallowed.

H314

Causes severe skin burns and eye damage.

H317

May cause an allergic skin reaction.

H361

Suspected of damaging fertility or the unborn child.

H373

May cause damage to organs through prolonged or repeated exposure.

H411

Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P260

Do not breathe vapour.

P273

Avoid release to the environment.

P280

Wear protective gloves and eye/face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER or doctor/ physician.

P391

Collect spillage.

Print date: 09.11.2022  
 Version: 2

WEBAC 4520 Comp. B  
 Revision date: 09.11.2022  
 Issue date: 09.11.2022

EN  
 Page 2 / 13

**Hazard components for labelling**

Methyleneoxide, polymer with benzenamine, hydrogenated  
 3-aminomethyl-3,5,5-trimethylcyclohexylamine  
 2-piperazin-1-ylethylamine  
 3-aminopropyldimethylamine  
 Phenol, styrenated  
 m-phenylenebis(methylamine)  
 Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine  
 Fatty acids, tall-oil, reaction products with bisphenol A, epichlorhydrin, glycidyl tolyl ether and triethylenetetramine  
 Amines, polyethylenepoly, triethylenetetramine fraction  
 4,4'-methylenebis(cyclohexylamine)

**Supplemental hazard information**

not applicable

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Description** hardener/amine component for epoxy resin

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
202-859-9 100-51-6 603-057-00-5	01-2119492630-38-xxxx benzyl alcohol Acute Tox. 4 H302 / Acute Tox. 4 H332 / Eye Irrit. 2 H319	10 - 25
220-666-8 2855-13-2 612-067-00-9	01-2119514687-32-xxxx 3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412 Specific concentration limit (SCL): Skin Sens. 1A H317 >= 0,001	10 - 25
262-975-0 61788-44-1	01-2119980970-27-xxxx Phenol, styrenated Skin Irrit. 2 H315 / Skin Sens. 1A H317 / Aquatic Chronic 2 H411	10 - 25
205-411-0 140-31-8 612-105-00-4	01-2119471486-30-xxxx 2-piperazin-1-ylethylamine Acute Tox. 4 H302 / Acute Tox. 3 H311 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Repr. 2 H361 / STOT RE 1 H372 / Aquatic Chronic 3 H412	2,5 - 10
603-894-6 135108-88-2	01-2119983522-33-xxxx Methyleneoxide, polymer with benzenamine, hydrogenated Acute Tox. 4 H302 / Skin Corr. 1C H314 / Skin Sens. 1 H317 / STOT RE 2 H373 / Aquatic Chronic 3 H412	2,5 - 10
216-032-5 1477-55-0	01-2119480150-50-xxxx m-phenylenebis(methylamine) Acute Tox. 4 H302 / Acute Tox. 4 H332 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	2,5 - 10
618-561-0 9046-10-0	01-2119557899-12-xxxx Poly(oxypropylene)diamine Skin Corr. 1C H314 / Aquatic Chronic 3 H412	2,5 - 10
500-191-5 68082-29-1	01-2119972320-44-xxxx Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	2,5 - 10

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 3 / 13

606-078-8 186321-96-0	Fatty acids, tall-oil, reaction products with bisphenol A, epichlorhydrin, glycidyl tolyl ether and triethylenetetramine Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	2,5 - 10
614-657-1 68609-08-5	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer Skin Corr. 1B H314 / Eye Dam. 1 H318	2,5 - 10
292-588-2 90640-67-8	01-2119487919-13-xxxx Amines, polyethylenepoly, triethylenetetramine fraction Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	1 - 2,5
217-168-8 1761-71-3	01-2119541673-38-xxxx 4,4'-methylenebis(cyclohexylamine) Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1B H317 / STOT RE 2 H373	1 - 2,5
200-712-3 69-72-7 607-732-00-5	01-2119486984-17-xxxx Salicylic acid Repr. 2 H361 / Acute Tox. 4 H302 / Eye Dam. 1 H318	1 - 2,5
203-680-9 109-55-7 612-061-00-6	01-2119486842-27-xxxx 3-aminopropylidimethylamine Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / STOT SE 3 H335 / Flam. Liq. 3 H226	0,5 - 1
262-977-1 61788-46-3 612-285-00-4	01-2119473798-17-xxxx amines, coco alkyl Acute Tox. 4 H302 / Asp. Tox. 1 H304 / STOT SE 3 H335 / STOT RE 2 H373 / Skin Corr. 1B H314 / Aquatic Acute 1 H400 (M = 10) / Aquatic Chronic 1 H410 (M = 10)	0,1 - 0,5

#### Additional information

Full text of classification: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

##### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

##### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

##### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 4 / 13

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

6.1. **Personal precautions, protective equipment and emergency procedures**

Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

7.1. **Precautions for safe handling**

**Advices on safe handling**

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Follow the legal protection and safety regulations. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel!

7.2. **Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

**Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

8.1. **Control parameters**

**Occupational exposure limit values:**

not applicable

**DNEL:**

Salicylic acid

Index No. 607-732-00-5 / EC No. 200-712-3 / CAS No. 69-72-7

DNEL long-term dermal (systemic), Workers: 2 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 16 mg/m<sup>3</sup>

benzyl alcohol

Index No. 603-057-00-5 / EC No. 202-859-9 / CAS No. 100-51-6

DNEL acute dermal, short-term (systemic), Workers: 47 mg/kg bw/day

DNEL long-term dermal (systemic), Workers: 9,5 mg/kg bw/day

DNEL acute inhalative (systemic), Workers: 450 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 90 mg/m<sup>3</sup>

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 5 / 13

3-aminopropyldimethylamine

Index No. 612-061-00-6 / EC No. 203-680-9 / CAS No. 109-55-7

- DNEL acute inhalative (local), Workers: 9,8 mg/m<sup>3</sup>
- DNEL acute inhalative (systemic), Workers: 9,8 mg/m<sup>3</sup>
- DNEL long-term inhalative (local), Workers: 4,9 mg/m<sup>3</sup>
- DNEL long-term inhalative (systemic), Workers: 4,9 mg/m<sup>3</sup>

2-piperazin-1-ylethylamine

Index No. 612-105-00-4 / EC No. 205-411-0 / CAS No. 140-31-8

- DNEL acute dermal, short-term (local), Workers: 4 mg/dm<sup>2</sup>
- DNEL acute dermal, short-term (systemic), Workers: 20 mg/kg
- DNEL long-term dermal (local), Workers: 0,6 mg/dm<sup>2</sup>
- DNEL long-term dermal (systemic), Workers: 3,33 mg/kg bw/day
- DNEL acute inhalative (systemic), Workers: 21,4 mg/m<sup>3</sup>
- DNEL long-term inhalative (systemic), Workers: 3,6 mg/m<sup>3</sup>

m-phenylenebis(methylamine)

EC No. 216-032-5 / CAS No. 1477-55-0

- DNEL long-term dermal (systemic), Workers: 0,33 mg/kg
- DNEL long-term inhalative (local), Workers: 0,2 mg/m<sup>3</sup>
- DNEL long-term inhalative (systemic), Workers: 1,2 mg/m<sup>3</sup>

4,4'-methylenebis(cyclohexylamine)

EC No. 217-168-8 / CAS No. 1761-71-3

- DNEL long-term dermal (systemic), Workers: 0,1 mg/kg bw/day
- DNEL long-term inhalative (systemic), Workers: 1 mg/m<sup>3</sup>

Phenol, styrenated

EC No. 262-975-0 / CAS No. 61788-44-1

- DNEL long-term dermal (systemic), Workers: 2,92 mg/kg bw/day
- DNEL long-term inhalative (systemic), Workers: 4,11 mg/m<sup>3</sup>

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

EC No. 500-191-5 / CAS No. 68082-29-1

- DNEL long-term dermal (systemic), Workers: 1,1 mg/kg
- DNEL long-term inhalative (systemic), Workers: 3,9 mg/m<sup>3</sup>

Poly(oxypropylene)diamine

EC No. 618-561-0 / CAS No. 9046-10-0

- DNEL long-term dermal (local), Workers: 62,3 mg/dm<sup>2</sup>
- DNEL long-term dermal (systemic), Workers: 2,5 mg/kg bw/day

**PNEC:**

Salicylic acid

Index No. 607-732-00-5 / EC No. 200-712-3 / CAS No. 69-72-7

- PNEC aquatic, freshwater: 0,2 mg/L
- PNEC aquatic, marine water: 0,02 mg/L
- PNEC aquatic, intermittent release: 1 mg/L
- PNEC sediment, freshwater: 1,42 mg/kg
- PNEC sediment, marine water: 0,142 mg/kg
- PNEC, soil: 0,166 mg/kg
- PNEC sewage treatment plant (STP): 162 mg/L

benzyl alcohol

Index No. 603-057-00-5 / EC No. 202-859-9 / CAS No. 100-51-6

- PNEC aquatic, freshwater: 1 mg/L
- PNEC aquatic, marine water: 0,1 mg/L
- PNEC aquatic, intermittent release: 2,3 mg/L
- PNEC sediment, freshwater: 5,27 mg/kg
- PNEC, soil: 0,456 mg/kg
- PNEC sewage treatment plant (STP): 39 mg/L

3-aminopropyldimethylamine

Index No. 612-061-00-6 / EC No. 203-680-9 / CAS No. 109-55-7

- PNEC aquatic, freshwater: 0,0535 mg/L
- PNEC aquatic, marine water: 0,0535 x10<sup>-1</sup> mg/L
- PNEC aquatic, intermittent release: 0,535 mg/L
- PNEC sediment, freshwater: 0,585 mg/kg

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 6 / 13

PNEC sediment, marine water: 0,0585 mg/kg  
PNEC, soil: 0,0854 mg/kg  
PNEC sewage treatment plant (STP): 69,5 mg/L

2-piperazin-1-ylethylamine

Index No. 612-105-00-4 / EC No. 205-411-0 / CAS No. 140-31-8

PNEC aquatic, freshwater: 0,058 mg/L  
PNEC aquatic, marine water: 0,0058 mg/L  
PNEC aquatic, intermittent release: 0,58 mg/L  
PNEC sediment, freshwater: 215 mg/kg  
PNEC sediment, marine water: 21,5 mg/kg  
PNEC, soil: 42,9 mg/kg  
PNEC sewage treatment plant (STP): 250 mg/L

m-phenylenebis(methylamine)

EC No. 216-032-5 / CAS No. 1477-55-0

PNEC aquatic, freshwater: 0,094 mg/L  
PNEC aquatic, marine water: 0,0094 mg/L  
PNEC aquatic, intermittent release: 0,152 mg/L  
PNEC sediment, freshwater: 0,43 mg/kg  
PNEC sediment, marine water: 0,043 mg/kg  
PNEC, soil: 0,045 mg/kg  
PNEC sewage treatment plant (STP): 10 mg/L

4,4'-methylenebis(cyclohexylamine)

EC No. 217-168-8 / CAS No. 1761-71-3

PNEC aquatic, freshwater: 0,008 mg/L  
PNEC aquatic, marine water: 0,0008 mg/L  
PNEC aquatic, intermittent release: 0,08 mg/L  
PNEC sediment, freshwater: 0,39 mg/kg  
PNEC sediment, marine water: 0,039 mg/kg  
PNEC, soil: 0,072 mg/kg  
PNEC sewage treatment plant (STP): 80 mg/L

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Index No. 612-067-00-9 / EC No. 220-666-8 / CAS No. 2855-13-2

PNEC aquatic, freshwater: 0,06 mg/L  
PNEC aquatic, marine water: 0,006 mg/L  
PNEC aquatic, intermittent release: 0,23 mg/L  
PNEC sediment, freshwater: 5,784 mg/kg  
PNEC sediment, marine water: 0,578 mg/kg  
PNEC, soil: 1,121 mg/kg  
PNEC sewage treatment plant (STP): 3,18 mg/L

Phenol, styrenated

EC No. 262-975-0 / CAS No. 61788-44-1

PNEC aquatic, freshwater:  $11,5 \times 10^{-3}$  mg/L  
PNEC aquatic, marine water:  $1,15 \times 10^{-3}$  mg/L  
PNEC aquatic, intermittent release:  $13,5 \times 10^{-3}$  mg/L  
PNEC sediment, freshwater: 1,564 mg/kg  
PNEC sediment, marine water: 0,1564 mg/kg  
PNEC, soil: 0,3052 mg/kg  
PNEC sewage treatment plant (STP): 10 mg/L

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

EC No. 500-191-5 / CAS No. 68082-29-1

PNEC aquatic, freshwater: 0,0043 mg/L  
PNEC aquatic, marine water: 0,0004 mg/L  
PNEC aquatic, intermittent release: 0,0434 mg/L  
PNEC sediment, freshwater: 434,02 mg/kg  
PNEC sediment, marine water: 43,4 mg/kg  
PNEC sewage treatment plant (STP): 3,84 mg/L

Poly(oxypropylene)diamine

EC No. 618-561-0 / CAS No. 9046-10-0

PNEC aquatic, freshwater: 0,015 mg/L  
PNEC aquatic, marine water: 0,0142 mg/L



Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 7 / 13

PNEC aquatic, intermittent release: 0,15 mg/L  
PNEC sediment, freshwater: 0,132 mg/kg  
PNEC sediment, marine water: 0,125 mg/kg  
PNEC, soil: 0,0176 mg/kg  
PNEC sewage treatment plant (STP): 7,5 mg/L  
PNEC Secondary Poisoning: 6,93 mg/kg

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Personal protection equipment

##### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number.

Suitable respiratory protection apparatus: Usually no personal respirative protection necessary.

##### **Hand protection**

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

##### **Eye/face protection**

Wear eye glasses with side protection according to EN 166. Wear closely fitting protective glasses in case of splashes.

##### **Body protection**

Wear suitable protective clothing. Wear work clothes with long sleeves. Remove contaminated, saturated clothing immediately.

##### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>yellow</b>
<b>Odour:</b>	<b>characteristic</b>
<b>Odour threshold:</b>	<b>not applicable</b>
<b>Melting point/freezing point:</b>	<b>not determined</b>
<b>Initial boiling point and boiling range:</b>	<b>not determined</b>
<b>Flammability</b>	<b>not applicable</b>
<b>Lower and upper explosion limit:</b>	
<b>Lower explosion limit:</b>	<b>not determined</b>
<b>Upper explosion limit:</b>	<b>not applicable</b>
<b>Flash point:</b>	<b>&gt; 101 °C</b> Method: DIN 53213
<b>Auto-ignition temperature:</b>	<b>not determined</b>
<b>Decomposition temperature:</b>	<b>not applicable</b>
<b>pH at 20 °C:</b>	<b>not applicable</b>
<b>Viscosity: at 20 °C:</b>	<b>pasty</b>
<b>Solubility(ies):</b>	
<b>Water solubility at 20 °C:</b>	<b>insoluble</b>
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 8 / 13

**Vapour pressure at 20 °C:** **0,0818 mbar**  
Method: calculated

**Density and/or relative density:**  
**Density at 20 °C:** **1,14 g/cm<sup>3</sup>**  
Method: calculated

**Relative vapour density:** **not applicable**  
**particle characteristics:** **not applicable**

9.2. **Other information**

**solvent content:**  
**Organic solvents:** **0 weight-%**

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No further relevant information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

10.4. **Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

No further relevant information available.

10.6. **Hazardous decomposition products**

No further relevant information available.

**SECTION 11: Toxicological information**

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Harmful if swallowed.

Salicylic acid

oral, LD50, Rat: 891 mg/kg

dermal, LD50, Rat: > 2000 mg/kg

benzyl alcohol

oral, LD50, Rat: 1230 mg/kg

dermal, LD50, Rabbit: 2000 mg/kg

inhalative (dust and mist), LC50, Rat: > 4,178 mg/L (4 h)

3-aminopropyldimethylamine

oral, LD50, Rat: 1600 mg/kg

dermal, LD50, Rabbit: 2139 mg/kg

2-piperazin-1-ylethylamine

oral, LD50, Rat: 2000 mg/kg

dermal, LD50, Rabbit: 866 mg/kg

Method: literature value

m-phenylenebis(methylamine)

oral, LD50, Rat: 930 mg/kg

dermal, LD50, Rabbit: > 3100 mg/kg

4,4'-methylenebis(cyclohexylamine)

oral, LD50, Rat: 625 mg/kg

dermal, LD50, Rabbit: 2110 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine

oral, LD50, Rat: 1030 mg/kg

dermal, LD50, Rabbit: 1840 mg/kg



Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 9 / 13

Phenol, styrenated

oral, LD50, Rat: > 2000 mg/kg  
dermal, LD50, Rat: > 2000 mg/kg

amines, coco alkyl

oral, LD50, Rat: 1300 mg/kg

Amines, polyethylenepoly, triethylenetetramine fraction

oral, LD50, Rat: 1716 mg/kg  
dermal, LD50, Rabbit: 1465 mg/kg  
oral, LD50, Mouse: 1600 mg/kg  
oral, LD50, Rabbit: 5500 mg/kg

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

oral, LD50, Rat: > 2000 mg/kg  
dermal, LD50, Rat: > 2000 mg/kg

Methyleneoxide, polymer with benzenamine, hydrogenated

oral, LD50, Rat: 367 mg/kg  
dermal, LD50, Rabbit: > 2000 mg/kg

Poly(oxypropylene)diamine

oral, LD50, Rat: 2885 mg/kg  
dermal, LD50, Rabbit: 2980 mg/kg

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Causes severe skin burns and eye damage.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Suspected of damaging fertility or the unborn child.

**STOT-single exposure; STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

No further relevant information available.

**Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. **Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. **Toxicity**

Salicylic acid

Daphnia toxicity, EC50: 870 mg/L (48 h)  
literature value

benzyl alcohol

Fish toxicity, LC50: 460 mg/L (96 h)  
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 230 mg/L (48 h)  
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 770 mg/L (72 h)

3-aminopropyldimethylamine

Fish toxicity, LC50, Leuciscus idus (golden orfe): 122 mg/L (96 h)  
Daphnia toxicity, EC50: 59,5 mg/L (48 h)  
Algae toxicity, EC50, Algae: 56,2 mg/L (72 h)  
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44,5 mg/L (24 h)

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 10 / 13

Bacteria toxicity, EC50, *Pseudomonas putida*: 95 mg/L (17 h)  
Bacteria toxicity, EC50: > 1000 mg/L

**2-piperazin-1-ylethylamine**

Fish toxicity, LC50, *Poecilia reticulata* (Guppy): 368 mg/L (96 h)  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 58 mg/L (48 h)  
Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: > 1000 mg/L (72 h)

**m-phenylenebis(methylamine)**

Fish toxicity, LC50, *Oncorhynchus mykiss* (Rainbow trout): > 100 mg/L (96 h)  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 15,2 mg/L (48 h)  
Algae toxicity, ErC50, *Scenedesmus subspicatus*: 12 mg/L (72 h)  
Fish toxicity, LC50, *Danio rerio* (zebrafish): > 100 mg/L (96 h)

**3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Fish toxicity, LC50, *Danio rerio* (zebrafish): 110 mg/L (96 h)  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 23 mg/L (48 h)  
Method: OECD 202  
Algae toxicity, ErC50, *Scenedesmus subspicatus*: > 50 mg/L (72 h)  
Method: 88/302/EWG, annex V; C.8  
Bacteria toxicity, EC10, *Pseudomonas putida*: 1120 mg/L (18 h)  
Method: literature value

**amines, coco alkyl**

Fish toxicity, LC50, *Leuciscus idus* (golden orfe) 0,16 - 0,3 mg/L (96 h)  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 0,045 mg/L (48 h)  
Algae toxicity, ErC50, *Selenastrum capricornutum*: 0,17 mg/L (72 h)

**Poly(oxypropylene)diamine**

Fish toxicity, LC50, *Leuciscus idus* (golden orfe): > 15 mg/L (96 h)  
Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: 15 mg/L (72 h)  
Bacteria toxicity, NOEC, *Oncorhynchus mykiss* (Rainbow trout): 15 mg/L (96 h)

**Long-term Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**benzyl alcohol**

Algae toxicity, NOEC, *Pseudokirchneriella subcapitata*: 310 mg/L (72 h)

**m-phenylenebis(methylamine)**

Algae toxicity, ErC50, *Scenedesmus subspicatus*: 12 mg/L (72 h)

**12.2. Persistence and degradability**

**2-piperazin-1-ylethylamine**

:

Not readily biodegradable (according to OECD criteria)

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**Bioconcentration factor (BCF)**

Toxicological data are not available.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Liquid product may not be disposed of with household waste or landfilled. Do not allow to enter into drains/waters or in the

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 11 / 13

soil. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080409\* waste adhesives and sealants containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number or ID number**

UN 2735

**14.2. UN proper shipping name**

Land transport (ADR/RID):

Amines, liquid, corrosive, n.o.s.  
(ISOPHORONEDIAMINE)

Sea transport (IMDG):

AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONEDIAMINE, Phenol, styrolisiert)

Air transport (ICAO-TI / IATA-DGR):

Amines, liquid, corrosive, n.o.s.  
(ISOPHORONEDIAMINE)

**14.3. Transport hazard class(es)**

8

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID)

UMWELTGEFÄHRDEND

Marine pollutant

p / Phenol, styrolisiert

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

Tunnel restriction code

E

**Sea transport (IMDG)**

EmS-No.

F-A, S-B

**14.7. Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

VOC-value (in g/L): 193,290

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Full text of classification in section 3:**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

**WEBAC®**

Print date: 09.11.2022  
 Version: 2

WEBAC 4520 Comp. B  
 Revision date: 09.11.2022  
 Issue date: 09.11.2022

EN  
 Page 12 / 13

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Skin Sens. 1A / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Acute Tox. 3 / H311	Acute toxicity (dermal)	Toxic in contact with skin.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT RE 1 / H372	STOT-repeated exposure	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Skin Corr. 1C / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Skin Sens. 1B / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4	Acute toxicity (oral)	Calculation method.
Skin Corr. 1B	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Repr. 2	Reproductive toxicity	Calculation method.
STOT RE 2	STOT-repeated exposure	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 09.11.2022  
Version: 2

WEBAC 4520 Comp. B  
Revision date: 09.11.2022  
Issue date: 09.11.2022

EN  
Page 13 / 13

---

IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.