

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC HIS Comp. B  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 1 / 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name/designation WEBAC HIS Comp. B  
HIS Combi grouting

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

isocyanate component for polyurethane resin  
Restricted to professional users.

**1.3. Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

WEBAC-Chemie GmbH

Fahrenberg 22  
22885 Barsbüttel / Hamburg  
GERMANY

Telephone: +49 40 67057-0

Telefax: +49 40 6703227

**Department responsible for information:**

laboratory

E-mail

sdb@webac.de

**1.4. Emergency telephone number**

Giftinformationszentrum-Nord +49 551 19240

24 hr. emergency phone number

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 / H332

Acute toxicity (inhalative)

Harmful if inhaled.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Resp. Sens. 1 / H334

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Carc. 2 / H351

Carcinogenicity

Suspected of causing cancer.

STOT SE 3 / H335

STOT-single exposure

May cause respiratory irritation.

STOT RE 2 / H373

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H332

Harmful if inhaled.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H317

May cause an allergic skin reaction.

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351

Suspected of causing cancer.

H373

May cause damage to organs through prolonged or repeated exposure.

H335

May cause respiratory irritation.

**Precautionary statements**

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves and eye/face protection.

P284

In case of inadequate ventilation wear respiratory protection.

P304 + P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342 + P311

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Print date: 02.12.2022  
Version: 5

WEBAC HIS Comp. B  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 2 / 8

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

**Hazard components for labelling**

diphenylmethanediisocyanate, isomeres and homologues

**Supplemental hazard information**

EUH204 Contains isocyanates. May produce an allergic reaction.

**Use restriction according to REACH annex XVII, no.:**

Restrictions on use

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. **Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

3.2. **Mixtures**

**Description** isocyanate component for polyurethane resin

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification: // Remark	
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Resp. Sens. 1 H334 / Carc. 2 H351 / STOT RE 2 H373 / STOT SE 3 H335 Specific concentration limit (SCL): Resp. Sens. 1 H334 >= 0,1 / Eye Irrit. 2 H319 >= 5 / Skin Irrit. 2 H315 >= 5 / STOT SE 3 H335 >= 5	50 - 100

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

4.1. **Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In all cases of doubt, or when symptoms persist, seek medical advice.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

5.1. **Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

Print date: 02.12.2022  
Version: 5

WEBAC HIS Comp. B  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 3 / 8

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Use appropriate container to avoid environmental contamination.

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid contact with skin, eyes and clothes. Avoid breathing spray. When using do not eat, drink or smoke. Follow the legal protection and safety regulations. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel!

**Further information**

Vapours are heavier than air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers. Keep away from amines, alcohols and water. Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

**8.1. Control parameters**

**Occupational exposure limit values:**

not applicable

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. When spraying, wear self-contained breathing apparatus.

**Personal protection equipment**

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol

including four digit test number.

Suitable respiratory protection apparatus: Combination filtering device

**Hand protection**

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear eye glasses with side protection according to EN 166. Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear suitable protective clothing. Wear work clothes with long sleeves. Remove contaminated, saturated clothing.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
Odour:	earthy
Odour threshold:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not determined
Flammability	not applicable
Lower and upper explosion limit	
Lower explosion limit:	not determined
Upper explosion limit:	not determined
Flash point:	> 101 °C Method: DIN 53213
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	> 20,5 mm <sup>2</sup> /s
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	< 0,01 mbar
Density and/or relative density:	
Density at 20 °C:	1,23 g/cm <sup>3</sup> Method: calculated
Relative vapour density:	not determined
particle characteristics:	not applicable

9.2. Other information

solvent content:	
Organic solvents:	0 weight-%

**SECTION 10: Stability and reactivity**

Print date: 02.12.2022  
Version: 5

WEBAC HIS Comp. B  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 5 / 8

**10.1. Reactivity**

Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

**10.3. Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

**10.4. Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Harmful if inhaled.

diphenylmethanediisocyanate, isomeres and homologues

oral, LD50, Rat: > 10000 mg/kg

dermal, LD50, Rabbit: > 9400 mg/kg

inhalative (dust and mist), LC50, Rat: 1,5 mg/L (4 h)

Method: calculated

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Causes skin irritation.

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

diphenylmethanediisocyanate, isomeres and homologues

Skin:

May cause sensitization by skin contact.

Respiratory system:

May cause sensitization by inhalation.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Suspected of causing cancer.

diphenylmethanediisocyanate, isomeres and homologues

Carcinogenicity

Evidence for possible carcinogenic effects in experimental animals existent.; Determined in aerosol.; No indication of human carcinogenicity.

**STOT-single exposure; STOT-repeated exposure**

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

diphenylmethanediisocyanate, isomeres and homologues

Specific target organ toxicity (single exposure), Irritation

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Because of the isocyanate components' properties of this and with consideration of similar preparations the following applies: This mixture may cause acute irritation and/or sensitization of airways which lead to tightness in thorax, short-breath and asthmatic complaints. After sensitization even concentrations below the exposure limit values may cause asthma. Repeated inhaling can lead to permanent illness of the respiratory tract.

**Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. **Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]  
Do not allow to enter into surface water or drains.

12.1. **Toxicity**

diphenylmethanediisocyanate, isomeres and homologues

Fish toxicity, LC50, Danio rerio (zebrafish): > 1000 mg/L (96 h)

Method: OECD 203

Algae toxicity, ErC50, Scenedesmus subspicatus: > 1640 mg/L (72 h)

Method: OECD 201

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 1000 mg/L (24 h)

Method: OECD 202

Bacteria toxicity, EC50, Activated sludge: > 100 mg/L (3 h)

Method: OECD 209

**Long-term Ecotoxicity**

diphenylmethanediisocyanate, isomeres and homologues

Daphnia toxicity, NOEC, Daphnia magna: > 10 mg/L (21 D)

12.2. **Persistence and degradability**

Toxicological data are not available.

12.3. **Bioaccumulative potential**

Toxicological data are not available.

**Bioconcentration factor (BCF)**

Toxicological data are not available.

12.4. **Mobility in soil**

Toxicological data are not available.

12.5. **Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. **Endocrine disrupting properties**

No information available.

12.7. **Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

13.1. **Waste treatment methods**

**Appropriate disposal / Product**

**Recommendation**

Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080501\* waste isocyanates

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC HIS Comp. B  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 7 / 8

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**No dangerous good in sense of this transport regulation.**

14.1. **UN number or ID number**

not applicable

14.2. **UN proper shipping name**

14.3. **Transport hazard class(es)**

not applicable

14.4. **Packing group**

not applicable

14.5. **Environmental hazards**

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. **Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

Tunnel restriction code

-

**Sea transport (IMDG)**

EmS-No.

not applicable

14.7. **Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

VOC-value (in g/L): 0,000

**Use restriction according to REACH annex XVII, no.:**

Restrictions on use

As from 24 August 2023 adequate training is required before industrial or professional use.

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Full text of classification in section 3:**

Acute Tox. 4 / H332

Acute toxicity (inhalative)

Harmful if inhaled.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Resp. Sens. 1 / H334

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 / H351

Carcinogenicity

Suspected of causing cancer (state route of exposure if it is conclusively proven that no



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC HIS Comp. B  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 8 / 8

STOT RE 2 / H373

STOT-repeated exposure

other routes of exposure cause the hazard).  
May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

STOT SE 3 / H335

STOT-single exposure

May cause respiratory irritation.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.