

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 1 / 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name/designation WEBAC PURseal M SL5 Comp. A  
PU Injection Resin

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

polyhydroxy alcohol component for polyurethane resin  
Restricted to professional users.

**1.3. Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

WEBAC-Chemie GmbH

Fahrenberg 22  
22885 Barsbüttel / Hamburg  
GERMANY

Telephone: +49 40 67057-0

Telefax: +49 40 6703227

**Department responsible for information:**

laboratory

E-mail

sdb@webac.de

**1.4. Emergency telephone number**

Giftinformationszentrum-Nord +49 551 19240

24 hr. emergency phone number

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**

**Hazard statements**

not applicable

**Precautionary statements**

not applicable

**Hazard components for labelling**

not applicable

**Supplemental hazard information**

EUH210 Safety data sheet available on request.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Description** polyhydroxy alcohol component for polyurethane resin

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification: // Remark	
500-039-8	01-2119457556-29-xxxx	
25322-69-4	Propane-1,2-diol, propoxylated Acute Tox. 4 H302	10 - 25
203-872-2	01-2119457857-21-xxxx	
111-46-6	2,2' -oxybisethanol	2,5 - 10
603-140-00-6	Acute Tox. 4 H302	

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 2 / 8

286-272-3	01-2119979093-30-xxxx	
85203-81-2	Hexanoic acid, 2-ethyl-, zinc salt, basic	0,1 - 0,5
	Eye Irrit. 2 H319 / Repr. 2 H361	

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 3 / 8

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Follow the legal protection and safety regulations. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel!

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

##### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

##### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit values:

not applicable

##### DNEL:

2,2' -oxybisethanol

Index No. 603-140-00-6 / EC No. 203-872-2 / CAS No. 111-46-6

DNEL long-term dermal (systemic), Workers: 106 mg/kg

DNEL long-term inhalative (local), Workers: 60 mg/m<sup>3</sup>

Propane-1,2-diol, propoxylated

EC No. 500-039-8 / CAS No. 25322-69-4

DNEL long-term dermal (systemic), Workers: 13,9 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 98 mg/m<sup>3</sup>

##### PNEC:

2,2' -oxybisethanol

Index No. 603-140-00-6 / EC No. 203-872-2 / CAS No. 111-46-6

PNEC aquatic, freshwater: 10 mg/L

PNEC aquatic, marine water: 1 mg/L

PNEC aquatic, intermittent release: 10 mg/L

PNEC sediment, freshwater: 20,9 mg/kg

PNEC, soil: 1,53 mg/kg

PNEC sewage treatment plant (STP): 199,5 mg/L

Propane-1,2-diol, propoxylated

EC No. 500-039-8 / CAS No. 25322-69-4

PNEC aquatic, freshwater: 0,2 mg/L

PNEC aquatic, marine water: 0,02 mg/L

PNEC aquatic, intermittent release: 1,06 mg/L

PNEC sediment, freshwater: 0,419 mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

##### Personal protection equipment

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number.

Suitable respiratory protection apparatus: Usually no personal respirative protection necessary.

##### Hand protection

For prolonged or repeated handling the following glove material must be used: impermeable material

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 4 / 8

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### **Eye/face protection**

Wear eye glasses with side protection according to EN 166. Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear suitable protective clothing. Wear work clothes with long sleeves. Remove contaminated, saturated clothing immediately.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### **SECTION 9: Physical and chemical properties**

#### **9.1. Information on basic physical and chemical properties**

<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>refer to label</b>
<b>Odour:</b>	<b>poor</b>
<b>Odour threshold:</b>	<b>not determined</b>
<b>Melting point/freezing point:</b>	<b>not determined</b>
<b>Initial boiling point and boiling range:</b>	<b>not determined</b>
<b>Flammability</b>	<b>not applicable</b>
<b>Lower and upper explosion limit:</b>	
Lower explosion limit:	<b>not determined</b>
Upper explosion limit:	<b>not determined</b>
<b>Flash point:</b>	<b>&gt; 101 °C</b> Method: DIN 53213
<b>Auto-ignition temperature:</b>	<b>not determined</b>
<b>Decomposition temperature:</b>	<b>not applicable</b>
<b>pH at 20 °C:</b>	<b>not applicable</b>
<b>Cinematic viscosity (40°C):</b>	<b>&gt; 20,5 mm<sup>2</sup>/s</b>
<b>Solubility(ies):</b>	
<b>Water solubility at 20 °C:</b>	<b>insoluble</b>
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>
<b>Vapour pressure at 20 °C:</b>	<b>1,2049 mbar</b>
<b>Density and/or relative density:</b>	
<b>Density at 20 °C:</b>	<b>1,02 g/cm<sup>3</sup></b> Method: calculated
<b>Relative vapour density:</b>	<b>not applicable</b>
<b>particle characteristics:</b>	<b>not applicable</b>

#### **9.2. Other information**

<b>solvent content:</b>	
<b>Organic solvents:</b>	<b>0 weight-%</b>

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No further relevant information available.

#### **10.2. Chemical stability**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 5 / 8

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

**10.3. Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**10.4. Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

No further relevant information available.

**10.6. Hazardous decomposition products**

No further relevant information available.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

2,2'-oxybisethanol

oral, LD50, Rat 300 - 2000 mg/kg

dermal, LD50, Rabbit: 13300 mg/kg

oral, LD50, human.: 1120 mg/kg

inhalative (vapours), LC0, Rat: > 4,6 mg/L (4 h)

Propane-1,2-diol, propoxylated

oral, LD50, Rat 1000 - 2000 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

No further relevant information available.

**Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

2,2'-oxybisethanol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 75200 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 10000 mg/L (48 h)

Propane-1,2-diol, propoxylated

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h)

Fish toxicity, LC50, Danio rerio (zebrafish): > 100 mg/L (48 h)

Aquatic plants, Desmodemus subspicatus: > 100 mg/L (72 h)

**Long-term Ecotoxicity**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 6 / 8

2,2' -oxybisethanol  
Algae toxicity, NOEC, Scenedesmus quadricauda: 2700 mg/L (8 D)

**12.2. Persistence and degradability**

2,2' -oxybisethanol  
Biodegradation: 92 % (28 D)  
Method: OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A  
Readily biodegradable (according to OECD criteria).

**12.3. Bioaccumulative potential**

2,2' -oxybisethanol  
Partition coefficient: n-octanol/water: < 1  
No indication of bioaccumulation potential.

**Bioconcentration factor (BCF)**

2,2' -oxybisethanol  
Bioconcentration factor (BCF), Leuciscus idus (golden orfe): 100  
No indication of bioaccumulation potential.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Liquid product may not be disposed of with household waste or landfilled. Do not allow to enter into drains/waters or in the soil. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080410 waste adhesives and sealants other than those mentioned in  
080409

**Appropriate disposal / Package Recommendation**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**No dangerous good in sense of this transport regulation.**

**14.1. UN number or ID number**

not applicable

**14.2. UN proper shipping name**

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

**14.6. Special precautions for user**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 7 / 8

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

Tunnel restriction code -

**Sea transport (IMDG)**

EmS-No. not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

VOC-value (in g/L): 30,639

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Full text of classification in section 3:**

Acute Tox. 4 / H302

Acute toxicity (oral)

Harmful if swallowed.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Repr. 2 / H361

Reproductive toxicity

Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

**WEBAC®**

Print date: 02.12.2022  
Version: 5

WEBAC PURseal M SL5 Comp. A  
Revision date: 02.12.2022  
Issue date: 02.12.2022

EN  
Page 8 / 8

---

REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.