

Cleaner

WEBAC® Degreasing Agent

- ▶ WEBAC® Degreasing Agent is universally applicable against hydrophobic (oils/greases) and hydrophilic (salinization/acidification) impurities.


Range of application

- Cleaning of concrete or masonry surfaces by removing:
 - Major or stubborn impurities caused by:
 - Mold release oil and other (industrial) oils
 - Greases and oils, e.g. used in gastronomy or the food sector
 - Salinization, e.g. occurring in building structures used in farming operations
 - Acidified substrates

Properties

- Extremely good penetration
- Deep down cleaning action
- Easy to rinse with water

Example



Cleaning of oilcontaminated substrates

Technical data

	Values
Density, 20 °C / 68 °F (ISO 2811)	≈ 1.0 g/cm ³
Viscosity (ISO 3219)	≈ 30 mPas
Application temperature	> 5 °C / 41 °F
Exposure scenarios according to REACH	Assessment of industry standard application

The specified data are values determined under laboratory conditions and are subject to a certain fluctuation. Deviations are possible in practice depending on the respective object situation.

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

▶ Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 12/18

Cleaner

WEBAC® Degreasing Agent



Mixing

- Ready to use



Application

- Brush material into the surface, allow to work in, then rinse with water and suck off
- In case of stubborn soiling, apply several times, if necessary
- The surface can then be primed with **WEBAC® 4270/4270T**

Product data

Application	Brush in/rinse/suck off
Packing	Unit 1 kg
Storage	<ul style="list-style-type: none"> • Between 5 °C / 41 °F and 30 °C / 86 °F • Protect from moisture • In original, sealed containers

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de



Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac-grouts.com.



Waste disposal

In Germany, empty containers can be disposed of via "Interseroh Dienstleistungs GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Information on the disposal and return of WEBAC packaging" in our product catalog or www.webac-grouts.com and the safety data sheets.

► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 12/18