

WEBAC® Plug/Ring/Flange



► Form work anchors are unavoidable when forming and concreting walls. For sealing intersections these items are used.


Range of application

- Sealing of intersections/tie points (with swellable sealing rings and plugs) in concrete and reinforced concrete construction
- Suitable for:
 - Fiber reinforced concrete pipes
 - Plastic pipe spacers
 - Foundation earth electrodes

Properties

- Easy and economical solution
- Sealing with a simple hammer blow
- No gluing
- Temperature- and weather-independent
- Active swelling sealant
- Suitable also in case of negative pressing water

Example



Installation of WEBAC® Flange, Ring and Plug

Technical data

Water pressure

Values

tested with 5 bar

The specified data are values determined under laboratory conditions and are subject to a certain fluctuation. Deviations are possible in practice depending on the respective object situation.

WEBAC-Chemie GmbH
 Fahrenberg 22
 22885 Barsbüttel
 Germany
 Tel. +49 40 67057-0
 Fax +49 40 6703227
 info@webac.de

www.webac.de




► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
 © WEBAC-Chemie GmbH. Version 03/2020

Special Construction Products

WEBAC® Plug/Ring/Flange

Products

		Dimensions
WEBAC. Plug		Ø 22, 24, 26 mm
WEBAC. Ring		Ø 24 mm
WEBAC. Flange		Ø 10, 12, 17, 24, 31, 39 mm

WEBAC-Chemie GmbH
 Fahrenberg 22
 22885 Barsbüttel
 Germany
 Tel. +49 40 67057-0
 Fax +49 40 6703227
 info@webac.de

www.webac.de

Product data

Installation	<ul style="list-style-type: none"> Mount WEBAC. Flange or WEBAC. Ring for exterior sealing purposes to the plastic pipe or the fiber-reinforced cement pipe during the formwork operations The interior sealing process takes place following the formwork by simply knocking the WEBAC. Plugs into the pipe
Storage	<ul style="list-style-type: none"> Protect from mechanical damage and moisture

Test certificate

- Test Report of watertightness of tie points

Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac-grouts.com.

Waste disposal

In Germany, empty containers can be disposed of via "Interseroh Dienstleistungs GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Information on the disposal and return of WEBAC packaging" in our product catalog or www.webac-grouts.com and the safety data sheets.

► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
 © WEBAC-Chemie GmbH. Version 03/2020