

PU Injection Resins

WEBAC® PURseal M ACC3

Range of Application

- Accelerates foam formation of PU resins
WEBAC® PURseal, **WEBAC® PURseal M**, **WEBAC® PURseal M S**,
WEBAC® PURseal M SL5 and **WEBAC® PURseal M SL10**

Application Instruction

- Add accelerator amount referring to total volume according to table
- Shake well before use
- Mix homogeneously with component A immediately before use


Reaction Time

WEBAC® PURseal M depending on amount of **WEBAC® PURseal M ACC3** added

— Start of reaction

— End of reaction

II Tolerance



WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 01/2025


PU Injection Resins

WEBAC® PURseal M ACC3

Reaction Time

WEBAC® PURseal M S depending on amount of WEBAC® PURseal M ACC3 added

— Start of reaction — End of reaction II Tolerance



Further reaction times on request.

Product Data

Unit	
Delivery form	1 kg 4 kg
Storage	<ul style="list-style-type: none"> Between 5 °C and 30 °C Protected from moisture In original, sealed containers

Occupational Safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac-grouts.com.

Waste Disposal

In Germany, empty containers can be disposed of via "Interzero Circular Solutions Germany GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Disposal Notes" in our product catalog or www.webac-grouts.com and the safety data sheets.

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 01/2025