

Print c Versio		02.12.2022 7	WEBAC PURstop 1K Revision date: 02.12.2 Issue date: 02.12.202	2022	EN Page 1 / 8
SEC	TION 1: Ide	entification of the	e substance/mixture	and of the company/	/undertaking
1.1.	Product id	entifier			
	Trade name	e/designation	V	VEBAC PURstop 1K	
1.2.	Relevant ic	lentified uses of th	e substance or mixtu	re and uses advised aga	ainst
	isocyanate	lentified uses component for poly o professional users	urethane foam resin s.		
1.3.	Details of t	he supplier of the	safety data sheet		
	WEBAC-Ch Fahrenberg	nemie GmbH		distributor) elephone: +49 40 67057 elefax: +49 40 6703227	-0
	GERMANY	battor, Harnburg	·		
	Departmen laboratory	t responsible for i	nformation:		
	E-mail		S	db@webac.de	
1.4.	Giftinformat	y telephone numbe tionszentrum-Nord rgency phone numb	+	49 551 19240	
SEC	TION 2: Ha	zards identificati	ion		

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs through
		prolonged or repeated exposure.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard state	nents		
H332	Harmful if inhaled.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H317	May cause an allergic skin reaction.		
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
H351	Suspected of causing cancer.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H335	May cause respiratory irritation.		
Precautionary statements			
P260	Do not breathe aerosol.		

- P280 Wear protective gloves and eye/face protection.
- P284 In case of inadequate ventilation wear respiratory protection.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.



Print o Versio		2.12.2022	WEBAC PURstop 1K Revision date: 02.12.2022 Issue date: 02.12.2022	EN Page 2 / 8		
	Hazard comp		belling nylmethanediisocyanate, isomeres and	homologues		
	Supplementa EUH204		rmation ains isocyanates. May produce an allerg	c reaction.		
	Restrictions o	n use	to REACH annex XVII, no.: equate training is required before industr	ial or professional use.		
2.3.	Other hazard	S				
	No information	n available.				
SEC	TION 3: Com	position/inf	ormation on ingredients			
3.2.	Mixtures					
	Description	isocy	anate component for polyurethane foam	resin		
	Classification according to Regulation (EC) No 1272/2008 [CLP]					
	EC No. CAS No.		CH No. gnation		weight-%	
	Index No.		sification: // Remark		noight /c	
	9016-87-9	Acute H317 SE 3	enylmethanediisocyanate, isomeres and e Tox. 4 H332 / Skin Irrit. 2 H315 / I / Resp. Sens. 1 H334 / Carc. 2 H35 H335	Eye Irrit. 2 H319 / Skin Sens. 1 51 / STOT RE 2 H373 / STOT	50 - 100	
		Spec	ific concentration limit (SCL): Resp. Ser	s. 1 H334 >= 0,1 / Eye Irrit.		

2 H319 >= 5 / Skin Irrit. 2 H315 >= 5 / STOT SE 3 H335 >= 5 Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media alcohol resistant foam, carbon dioxide, Powder, spray mist, (water) Unsuitable extinguishing media



		WEBAC PURstop 1K	
Print date:	02.12.2022	Revision date: 02.12.2022	EN
Version:	7	Issue date: 02.12.2022	Page 3 / 8
			- 3

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Use appropriate container to avoid environmental contamination.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. When using do not eat, drink or smoke. Follow the legal protection and safety regulations. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel!

Further information

Vapours are heavier than air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers. Keep away from amines, alcohols and water. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. When spraying, wear self-contained breathing apparatus.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol



		WEBAC PURstop 1K
Print date:	02.12.2022	Revision date: 02.12.2022
Version:	7	Issue date: 02.12.2022

ΕN Page 4/8

including four digit test number.

Suitable respiratory protection apparatus: Combination filtering device

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166. Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing. Wear work clothes with long sleeves. Remove contaminated, saturated clothing.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state: Colour:	Liquid brown
	Odour:	earthy
	Odour threshold:	not determined
	Melting point/freezing point:	not determined
	Initial boiling point and boiling range:	not determined
	Flammability	not applicable
	Lower and upper explosion limit Lower explosion limit: Upper explosion limit:	not determined not determined
	Flash point:	> 101 °C Method: DIN 53213
	Auto-ignition temperature:	not determined
	Decomposition temperature:	not determined
	pH at 20 °C:	not applicable
	Cinematic viscosity (40°C):	> 20,5 mm²/s
	Solubility(ies):	
	Water solubility at 20 °C:	insoluble
	Partition coefficient: n-octanol/water:	see section 12
	Vapour pressure at 20 °C:	< 0,01 mbar
	Density and/or relative density: Density at 20 °C:	1,23 g/cm³ Method: calculated
	Relative vapour density:	not determined
	particle characteristics:	not applicable
9.2.	Other information	
	solvent content: Organic solvents:	0 weight-%
SEC	TION 10: Stability and reactivity	



		WEBAC PURstop 1K	
Print date:	02.12.2022	Revision date: 02.12.2022	EN
Version:	7	Issue date: 02.12.2022	Page 5 / 8

10.1. Reactivity

Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

diphenylmethanediisocyanate, isomeres and homologues oral, LD50, Rat: > 10000 mg/kg dermal, LD50, Rabbit: > 9400 mg/kg inhalative (dust and mist), LC50, Rat: 1,5 mg/L (4 h) Method: calculated

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

diphenylmethanediisocyanate, isomeres and homologues

Skin:

May cause sensitization by skin contact. Respiratory system: May cause sensitization by inhalation.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of causing cancer.

diphenylmethanediisocyanate, isomeres and homologues

Carcinogenicity Evidence for possible carcinogenic effects in experimental animals existent.; Determined in aerosol.; No indication of human carcinogenicity.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

diphenylmethanediisocyanate, isomeres and homologues Specific target organ toxicity (single exposure), Irritation May cause respiratory irritation. Specific target organ toxicity (repeated exposure) May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard



Drint data	00 40 0000	WEBAC PURstop 1K		
Print date:	02.12.2022	Revision date: 02.12.2022	EN	
Version:	7	Issue date: 02.12.2022	Page 6 / 8	

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Because of the isocyanate components' properties of this and with consideration of similar preparations the following applies: This mixture may cause acute irrtation and/or sensitization of airways which lead to tightness in thorax, short-breath and asthmatic complaints. After sensitization even concentrations below the exposure limit values may cause asthma. Repeated inhaling can lead to permanent illness of the respiratory tract.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

diphenylmethanediisocyanate, isomeres and homologues Fish toxicity, LC50, Danio rerio (zebrafish): > 1000 mg/L (96 h) Method: OECD 203 Algae toxicity, ErC50, Scenedesmus subspicatus: > 1640 mg/L (72 h) Method: OECD 201 Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 1000 mg/L (24 h) Method: OECD 202 Bacteria toxicity, EC50, Activated sludge: > 100 mg/L (3 h) Method: OECD 209

Long-term Ecotoxicity

diphenylmethanediisocyanate, isomeres and homologues Daphnia toxicity, NOEC, Daphnia magna: > 10 mg/L (21 D)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080501* waste isocyanates

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package



according	g to Regulation (EU) 2	WEBAC				
Print date: Version:	02.12.2022 7	WEBAC PURstop 1K Revision date: 02.12.2022 Issue date: 02.12.2022	EN Page 7 / 8			
	commendation	s may be recycled. Vessels not properly	emptied are special waste.			
SECTION	N 14: Transport inforr	nation				
No	dangerous good in sen	se of this transport regulation.				
14.1. UN	number or ID number					
		not applicable				
14.2. UN	proper shipping name					
14.3. Tra	nsport hazard class(es)					
		not applicable				
14.4. Pac	king group	not applicable				
14.5 Env	vironmental hazards	not applicable				
-	d transport (ADR/RID)	not applicable				
	ine pollutant	not applicable				
	ecial precautions for us					
Trai	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8					
Fur	ther information					
Lan	d transport (ADR/RID)					
	nel restriction code	-				
Sea	transport (IMDG)					
Em	S-No.	not applicable				
14.7. Ma i	ritime transport in bulk	according to IMO instruments				
No	transport as bulk accordi	ng IBC - Code.				
SECTION	N 15: Regulatory info	rmation				
15.1. Saf	ety, health and environ	mental regulations/legislation specific	ofor the substance or mixture			
EU	Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation					
	Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC-value (in g/L): 0,000					
Use Res	Use restriction according to REACH annex XVII, no.: Restrictions on use As from 24 August 2023 adequate training is required before industrial or professional use.					
Nat	National regulations					
Obs		tions under the Maternity Protection Dire	ective (92/85/EEC) for expectant or nursing mothers. venile work protection guideline' (94/33/EC).			
	emical Safety Assessme emical safety assessmen	ent ts for substances in this mixture were no	t carried out.			
SECTION	N 16: Other information	on				
Full	I text of classification ir	section 3:				
Acu	te Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.			
	1 1001 27 836					

Full text of classification in section 3:				
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.		
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.		
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.		
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.		
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of		

exposure if it is conclusively proven that no



Print date: Version:	02.12.2022 7	WEBAC PURstop 1K Revision date: 02.12.2022 Issue date: 02.12.2022	EN Page 8 / 8
STOT R	E 2 / H373	STOT-repeated exposure	other routes of exposure cause the hazard). May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT S	E 3 / H335	STOT-single exposure	May cause respiratory irritation.
Abbrevi	ations and acrony	ms	
ADR OEL BLV CAS CLP CMR DIN DNEL EAKV EC EC EN IATA-DC IBC Cod ICAO-TI IMDG C ISO LC	Euro Occu Biolo Chen Class Carci Germ Deriv Euro Euro Euro Euro SR Interr Interr Interr Good ode Interr Letha	bean Agreement concerning the Interna pational Exposure Limit Value gical Limit Value nical Abstracts Service bification, Labelling and Packaging nogenic, Mutagenic and Reprotoxic an Institute for Standardization / Germa ed No-Effect Level bean Waste Catalogue Directive tive Concentration bean Community bean Standard national Air Transport Association – Dar national Code for the Construction and F national Civil Aviation Organization Teo is by Air national Maritime Code for Dangerous C national Organization for Standardization of Concentration	ngerous Goods Regulations Equipment of Ships carrying Dangerous Chemicals in Bulk chnical Instructions for the Safe Transport of Dangerous Goods
LD MARPO OECD PBT PNEC REACH RID UN VOC vPvB	L Marit Orga persi Predi Regu Regu Unite Volat	Il Dose ime Pollution: The International Conven nisation for Economic Cooperation and stent, bioaccumulative, toxic cted No Effect Concentration stration, Evaluation, Authorisation and F lations concerning the International Car d Nations ile Organic Compounds persistent and very bioaccumulative	Restriction of Chemicals

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.