

WEBAC SILform Comp. A Version 1.0

Revision date 16-May-2023

Print date 16-May-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

WEBAC SILform Comp. A Silicate Injection Foam Resin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

silicate injection resin

1.3 Details of the supplier of the safety data sheet

supplier

WEBAC-Chemie GmbHFahrenberg 22Telephone: +49 40 67057022885 BarsbüttelTelefax: +49 40 6703227DeutschlandTelefax: +49 40 6703227

Department responsible for information

E-mail (competent person)

1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40 available 24h/365days; Information will be provided in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation. Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.

msds@webac.de

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS07	
Signal word	
Warning	
Hazard statements	
H319	Causes serious eye irritation.
H315	Causes skin irritation.
Precautionary statement	nts
P280	Wear protective gloves and eye/face protection.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
Hazard components for	r labelling
not applicable	

Supplemental hazard information

not applicable

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



WEBAC SILform Comp. A Version 1.0

Revision date 16-May-2023

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

silicate injection resin

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
1344-09-8 215-687-4 -	Silicic acid, sodium salt 01-2119448725-31-xxxx Skin Irrit. 2 H315 / Eye Irrit. 2 H319	25,0 < 50,0
1704-62-7 216-940-1 -	2-[2-(dimethylamino)ethoxy]ethanol 01-2119976346-26-xxxx Acute Tox. 4 H312 / Skin Corr. 1C H314 ATE (dermal): = 1.663 mg/kg	1,00 < 2,50

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water) **Unsuitable extinguishing media**

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.



WEBAC SILform Comp. A Version 1.0

Revision date 16-May-2023

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8 Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers. Do not store together with: Food and feedingstuffs

Storage class LGK12 - non-co

LGK12 - non-combustible liquids that cannot be assigned to any of the above storage classes

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term dermal (systemic)	2,33 mg/kg bw/day
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term inhalative (local)	1,07 mg/m ³



WEBAC SILform Comp. A

	Outestance news		
PNEC			
1344-09-8	Silicic acid, sodium salt	DNEL long-term inhalative (systemic)	5,61 mg/m ³
1344-09-8	Silicic acid, sodium salt	DNEL long-term dermal (systemic)	1,59 mg/kg bw/day
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term inhalative (systemic)	0,48 mg/m ³
ion 1.0	Revision date 16-May-2023	Pr	int date 16-May-20

CAS No.	Substance name	PNEC type	PNEC Value
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, intermittent release	1 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, marine water	0,01 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, freshwater	0,1 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sewage treatment plant (STP)	100 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sediment, marine water	0,87 mg/kg
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sediment, freshwater	8,696 mg/kg
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC soil, freshwater	2,817 mg/kg
1344-09-8	Silicic acid, sodium salt	PNEC aquatic, intermittent release	7,5 mg/L
1344-09-8	Silicic acid, sodium salt	PNEC aquatic, freshwater	7,5 mg/L
1344-09-8	Silicic acid, sodium salt	PNEC aquatic, marine water	1 mg/L
1344-09-8	Silicic acid, sodium salt	PNEC sewage treatment plant (STP)	348 mg/L

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0,4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166 Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing. Change contaminated, saturated clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	colourless
Odour	characteristic
рН	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	not applicable
flammability	not applicable
Lower explosion limit at 20°C	not determined



WEBAC SILform Comp. A Version 1.0

ersion 1.0	Revision date 16-May-2023	Print date 16-May-2023
Upper explosion limit at 20°C	not determined	
Vapour pressure at 20°C	21,81 mbar	
Relative vapour density	not applicable	
Density at 20 °C	1,403 kg/l	
Water solubility at 20°C	practically insoluble	
Partition coefficient: n-octanol/	vater see section 12	
Ignition temperature in °C	not determined	
Decomposition temperature	not determined	
Viscosity at 20 °C:	> 20,5 mm²/s	
particle characteristics	not applicable	

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2 Chemical stability

Stable under recommended storage and handling conditions. Please note the expiry date.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

2-[2-(dimethylamino)ethoxy]ethanol

LD50: dermal (Rabbit): = 1.663 mg/kg; (OECD 402)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Indications for this are:

Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural



WEBAC SILform Comp. A

Version 1.0

Revision date 16-May-2023

Print date 16-May-2023

fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Based on available data, the classification criteria are not met.

Algae toxicity 2-[2-(dimethylamino)ethoxy]ethanol

ErC50: (Selenastrum capricornutum): = 160 mg/L (72 h) Method: OECD 201

Daphnia toxicity EC50 > 100 mg/L (48 h) Method: OECD 202

Silicic acid, sodium salt EC50 > 100 mg/L (48 h)

Fish toxicity

2-[2-(dimethylamino)ethoxy]ethanol LC50: (Leuciscus idus (golden orfe)): = 320 mg/L (96 h)

Silicic acid, sodium salt EC50 > 100 mg/L

LC50: > 100 mg/L (96 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information



Print date 16-May-2023

WEBAC SILform Comp. A Version 1.0 Revision

Revision date 16-May-2023

	-		
14.1	UN number or ID number		
	not applicable		
14.2	UN proper shipping name		
	Land transport (ADR/RID)		
	No dangerous good in sense of these transport regulations.		
	Sea transport (IMDG)		
	No dangerous good in sense of these transport regulations.		
	Air transport (ICAO-TI / IATA-DGR)		
	No dangerous good in sense of these transpor	t regulations.	
14.3	Transport hazard class(es)		
	not applicable		
14.4	Packing group		
	not applicable		
14.5	Environmental hazards		
		not applicable	
44.0		not applicable	
14.6	Special precautions for user		
	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8		
14.7	Maritime transport in bulk according to IMO	instruments	
	No transport as bulk according to IBC Code.		
14.8	Additional information		
	Land transport (ADR/RID)		
	not applicable		
	Sea transport (IMDG)		
	not applicable		
	Air transport (ICAO-TI / IATA-DGR)		

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 0 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15 H312 Harmful in contact with skin.

Page 7/8



AC SILform Comp ion 1.0	Revision date 16-May-2023	Print date 16-May-2023
H314 H315 H319	Causes severe skin burns and eye damage. Causes skin irritation. Causes serious eye irritation.	
Classification for	or mixtures and used evaluation method according to regula	tion (EC) No 1272/2008 [CLP]
Eye Irrit. 2 Skin Irrit. 2	Calculation method. Calculation method.	
Abbreviations a	nd acronyms	
OEL: Occupationa BLV: Biological Iir CAS: Chemical A CLP: Classificatio CMR: Carcinoger DIN: German Inst DNEL: Derived N EAKV: European EC: Effective Con EC: European Co EN: European Sta IATA-DGR: Interna IBC Code: Interna ICAO-TI: International ICAO-TI: International LC: Lethal Conce LD: Lethal Dose :	ostracts Service n, Labelling and Packaging ic, Mutagenic and Reprotoxic itute for Standardization / German industrial standard o-Effect Level Waste Catalogue Directive centration mmunity andard ational Air Transport Association – Dangerous Goods Regulations tional Code for the Construction and Equipment of Ships carrying Da onal Civil Aviation Organization Technical Instructions for the Safe Tr national Maritime Code for Dangerous Goods Organization for Standardization ntration	angerous Chemicals in Bulk ransport of Dangerous Goods by Air
OECD: Organisat PBT: persistent, b PNEC: Predicted RID: Regulations UN: United Nation VOC: Volatile Org		tion from Ships

Indication of changes

* Data changed compared with the previous version.