Special Construction Products

WEBAC_® Fastening Grid



Range of application	• Fastening of WEBAC. Bentonite Swelling Tape
Properties	U-shaped expanded metal made of galvanized steel
Test certificate	 National Test Certificate for WEBAC. Bentonite Swelling Tape in combination with WEBAC. Fastening Grid

Example

WEBAC-Chemie GmbH Fahrenberg 22 22885 Barsbüttel Germany Tel. +49 40 67057-0 Fax +49 40 6703227 info@webac.de

www.webac.de

Technical data	Values
Shape	U-shape
Length	1 m

Special Construction Products

WEBAC® Fastening Grid

Installation

- · Installation by nailing, doweling or tacking
- The installed swelling tape must lie firmly to the entire joint
- · Secure swelling tape against shifting or floating
- · Recommended fastening space: 25 cm

Product data	
Delivery form	Unit 30 x 1 m
Storage	Protected from mechanical damage

Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac.com.

Waste disposal

It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Disposal Notes" in our product catalog or www.webac.com and the safety data sheets.



WEBAC-Chemie Gmb Fahrenberg 22 22885 Barsbüttel Germany Tel. +49 40 67057-0 Fax +49 40 6703227 info@webac.de

www.webac.de