

Special Construction Products

WEBAC® Hammer-in Profiles EPDM


Range of application

- Sealing of structural elements and movement joints
- Suitable as end profile for joints

Properties

- 100% closed-cell EPDM foam
- Very good heat resistance
- Good workability also at low temperatures
- High resistance to weathering, chemicals, UV and ozone

Example



WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Technical data

	Values	
	Round profile	
Profile shape		Ø 30 mm, Ø 40 mm other sizes on demand
Density		≈ 0.55 g/cm ³
Tensile strength		≥ 3 MPa (N/mm ²)
Elongation at break		≥ 150%
Shore hardness A		≈ 20 +/- 5
Surface texture		even
Color		greyish black

The specified data are values determined under laboratory conditions and are subject to a certain fluctuation. Deviations are possible in practice depending on the respective object situation.

Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products. © WEBAC-Chemie GmbH. Version 03/2024

Special Construction Products

WEBAC® Hammer-in Profiles EPDM

Installation

- Manually or mechanically with a special chisel hammer
- The profile size should exceed the joint width by $\approx 30\%$

Product data

Product data		
	Sizes	Unit
Delivery form	Ø 30 mm	20 m
	Ø 40 mm	20 m
Storage	• Dry and protected from mechanical damage	

Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac.com.

Waste disposal

It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Disposal Notes" in our product catalog or www.webac.com and the safety data sheets.

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Technical Information