

## Injection Pumps

# WEBAC® Piston Pumps

### Hand pumps

**WEBAC® HP 100 CE**



- For injecting PU injection foam resins, PU combi injection resins, PU injection resins and epoxy injection resins
- Delivery rate approx. 35 cm<sup>3</sup>/stroke
- Up to 100 bar injection pressure
- Low weight and easy handling on site

**WEBAC® HP 250 CE**



- For injecting PU injection foam resins, PU combi injection resins, PU injection resins and epoxy injection resins
- Delivery rate approx. 10 cm<sup>3</sup>/stroke
- Up to 250 bar injection pressure
- Low weight and easy handling on site

WEBAC-Chemie GmbH  
Fahnenberg 22  
22885 Barsbüttel  
Germany  
Tel. +49 40 67057-0  
Fax +49 40 6703227  
info@webac.de

[www.webac.de](http://www.webac.de)

### High-pressure electrical pump

**WEBAC® HEP 1001 CE**



- Entry-level model
- For injecting PU injection foam resins, PU combi injection resins, PU injection resins and epoxy injection resins
- Delivery rate approx. 30 l/h
- Up to 400 bar injection pressure
- Low weight and easy handling on site

### Hand pump

**WEBAC® Hand Lever Injection Press CE**



- For one-time use only
- For injecting epoxy and PU resins in small cracks and cavities
- Up to 400 bar injection pressure
- Delivery rate approx. 2 cm<sup>3</sup>/stroke

## ► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.

## Injection Pumps

# WEBAC® Piston Pumps

### Operation

For the operation of the injection pump, see the pump manual.

### Cleaning

- Clean the injection pump with **WEBAC® Cleaner A**
- Observe the technical data sheets of the cleaner used
- Refer to the operating manual of the injection pump for detailed information

### Storage

- Always store the injection pump in an upright position
- Fill the cleaned pump system with (water-free) hydraulic oil in case of long non-operating periods

### Occupational safety/waste disposal



[webac-grouts.com/  
downloads](http://webac-grouts.com/downloads)

WEBAC-Chemie GmbH  
Fahrenberg 22  
22885 Barsbüttel  
Germany  
Tel. +49 40 67057-0  
Fax +49 40 6703227  
[info@webac.de](mailto:info@webac.de)

[www.webac.de](http://www.webac.de)

### Overview: Range of application

	Sealing of Masonry	Gel Injection (Curtain Injection)	Stabilization of Structures	Crack Repair	Sealing of Joints	Monument Conservation	Sealing of Foundation Pits	Sewer Repair	Soil Solidification
<b>1C pumps</b>	✓		✓	✓	✓	✓	✓	✓	✓
	✓		✓	✓	✓	✓		✓	✓
	✓		✓	✓	✓	✓		✓	✓
	✓		✓	✓		✓			
	✓		✓	✓		✓			
	✓		✓	✓		✓			
<b>2C pumps</b>	✓	✓			✓		✓	✓	✓
	✓		✓			✓	✓	✓	✓
	✓	✓			✓		✓	✓	✓
	✓	✓			✓		✓	✓	✓
	✓	✓			✓		✓	✓	✓

## ► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.  
 © WEBAC-Chemie GmbH, Version 03/2020