

WEBAC 150 Comp. A Version 1.0

Revision date 11-May-2023

Print date 11-May-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

WEBAC 150 Comp. A PU Injection Foam Resin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

polyhydroxy alcohol - amine component for polyurethane foam resin

1.3 Details of the supplier of the safety data sheet

supplier

WEBAC-Chemie GmbHFahrenberg 22Telephone: +49 40 67057022885 BarsbüttelTelefax: +49 40 6703227DeutschlandTelefax: +49 40 6703227

Department responsible for information

E-mail (competent person)

1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40 available 24h/365days; Information will be provided in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation. Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.

msds@webac.de

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS07			
Signal word			
Warning			
Hazard statements			
H319	Causes serious eye irritation.		
H315	Causes skin irritation.		
Precautionary statements			
P280	Wear protective gloves and eye/face protection.		
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P337 + P313	If eye irritation persists: Get medical advice/attention.		
Hazard components f	or labelling		
not applicable			

Supplemental hazard information

not applicable

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



WEBAC 150 Comp. A Version 1.0

Revision date 11-May-2023

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

polyhydroxy alcohol - amine component for polyurethane foam resin

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	1,00 < 2,50
216-940-1	01-2119976346-26-xxxx	
-	Acute Tox. 4 H312 / Skin Corr. 1C H314	
	ATE (dermal): = 1.663 mg/kg	

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.



WEBAC 150 Comp. A Version 1.0 Revision c

Revision date 11-May-2023

Print date 11-May-2023

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8 Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Do not store together with: Food and feedingstuffs

Storage class

LGK10 - Combustible liquids that cannot be assigned to any of the above storage classes

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	hylamino)ethoxy]ethanol DNEL long-term dermal (systemic) 2	
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term inhalative (local)	1,07 mg/m³
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term inhalative (systemic)	0,48 mg/m³
PNEC			
CAS No.	Substance name	PNEC type	PNEC Value



WEBAC 150 Comp. A Version 1.0

Revision date 11-May-2023

Print date 11-May-2023

1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, intermittent release	1 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, marine water	0,01 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, freshwater	0,1 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sewage treatment plant (STP)	100 mg/L
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sediment, marine water	0,87 mg/kg
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sediment, freshwater	8,696 mg/kg
1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC soil, freshwater	2,817 mg/kg

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0,4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166 Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing. Change contaminated, saturated clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	yellow
Odour	characteristic
рН	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	> 101 °C
flammability	not applicable
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	0,1 mbar
Relative vapour density	not applicable
Density at 20 °C	0,979 kg/l
Water solubility at 20°C	practically insoluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined



	AC 150 Comp. A on 1.0	Revision date 11-May-2023	Print date 11-May-202
	Viscosity at 20 °C:	> 20.5 mm²/s	
	particle characteristics	not applicable	
	Other information		
	not applicable		
SEC	TION 10: Stability and	I reactivity	
0.1	Reactivity		
No hazardous reaction when handled and stored according to provisions.			
0.2	Chemical stability		
	Stable under recommended storage and handling conditions. Please note the expiry date.		
	Possibility of hazardous		
		ids, strong bases and strong oxidizing agents to avoid exothermine	c reactions.
	Conditions to avoid		
		bid high temperatures or direct sunlight.	
	Incompatible materials	a ngh temperatares of an eet sa night.	
	No further relevant informa	ation available	
	D.6 Hazardous decomposition products Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.		
	TION 11: Toxicologica	al information asses as defined in Regulation (EC) No 1272/2008	
	Acute toxicity		
		he classification criteria are not met.	
	2-[2-(dimethylamino)etho LD50: dermal (Rabbit): = 1		
	Skin corrosion/irritation		
	Causes skin irritation.		
	Serious eye damage/eye	irritation	
	Causes serious eye irritatio	on.	
	Respiratory or skin sensi	itisation	
	Based on available data, th	he classification criteria are not met.	
	Overall assessment on C	MR properties	
Based on available data, the classification criteria are not met. STOT-single exposure			
	Based on available data, th	he classification criteria are not met.	
STOT-repeated exposure		•	
	Based on available data, th	he classification criteria are not met.	
	Indications for this are:	gue, amyosthenia, Dizziness, in serious cases: unconsciousness.	Solvents may cause some of the
	Headache, Dizziness, fatig aforementioned effects thr	ough skin resorption. Repeated or prolonged contact with the pre in non-allergic contact dermatitis and/or absorption through skin.	eparation may cause removal of natural
	Headache, Dizziness, fatig aforementioned effects thr fat from the skin resulting i	ough skin resorption. Repeated or prolonged contact with the pre	eparation may cause removal of natural
	Headache, Dizziness, fatig aforementioned effects thr fat from the skin resulting i reversible damage. Aspiration hazard	ough skin resorption. Repeated or prolonged contact with the pre	eparation may cause removal of natural
	Headache, Dizziness, fatig aforementioned effects thr fat from the skin resulting i reversible damage. Aspiration hazard	ough skin resorption. Repeated or prolonged contact with the pre in non-allergic contact dermatitis and/or absorption through skin. he classification criteria are not met.	eparation may cause removal of natural
1.2	Headache, Dizziness, fatig aforementioned effects thr fat from the skin resulting i reversible damage. Aspiration hazard Based on available data, th	ough skin resorption. Repeated or prolonged contact with the pre in non-allergic contact dermatitis and/or absorption through skin. he classification criteria are not met.	eparation may cause removal of natura



WEBAC 150 Comp. A

Version 1.0

Revision date 11-May-2023

Print date 11-May-2023

SECTION 12: Ecological information

12.1 Toxicity

Based on available data, the classification criteria are not met.

Algae toxicity

2-[2-(dimethylamino)ethoxy]ethanol ErC50: (Selenastrum capricornutum): = 160 mg/L (72 h) Method: OECD 201

Daphnia toxicity

EC50 > 100 mg/L (48 h) Method: OECD 202

Fish toxicity

LC50: (Leuciscus idus (golden orfe)): = 320 mg/L (96 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080410 - waste adhesives and sealants other than those mentioned in 08 04 09

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

- not applicable
- 14.4 Packing group
 - not applicable

14.5 Environmental hazards

Land transport (ADR/RID)

not applicable



	AC 150 Comp. A	Revision date 11-May-2023	Print date 11-May-2023
	Sea transport (IMDG)	not applicable	· ···· a a a a a a a a a a a a a a a a
14.6	Special precautions for us	ser	
	Transport always in closed, of an accident or leakage. Advices on safe handling: s	upright and safe containers. Make sure that persons transp see parts 6 - 8	orting the product know what to do in case
14.7	Maritime transport in bulk	caccording to IMO instruments	
	No transport as bulk accord	ling to IBC Code.	
14.8	Additional information		
	Land transport (ADR/RII	0)	
	not applicable		
	Sea transport (IMDG)		
	not applicable		
	Air transport (ICAO-TI / I	ATA-DGR)	
	not applicable		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 0 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

H314

H312 Harmful in contact with skin.

Causes severe skin burns and eye damage.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 Calculation method.

Skin Irrit. 2 Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road OEL: Occupational Exposure Limit Value BLV: Biological limit values CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic DIN: German Institute for Standardization / German industrial standard DNEL: Derived No-Effect Level EAKV: European Waste Catalogue Directive EC: Effective Concentration EC: European Community EN: European Standard IATA-DGR: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk



WEBAC 150 Comp. A Version 1.0 Revision date 11-May-2023 Print date 11-May-2023 ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization LC: Lethal Concentration LD: Lethal Dose MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OECD: Organisation for Economic Cooperation and Development PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RID: Regulations concerning the International Carriage of Dangerous Goods by Rail **UN: United Nations** VOC: Volatile Organic Compounds vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.