

WEBAC 2100 Version 2.0

Revision date 20-Dec-2024

Print date 20-Dec-2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name/designation

WEBAC 2100 Alkali Silicate

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

waterproofing agent

### 1.3 Details of the supplier of the safety data sheet

#### supplier

WEBAC-Chemie GmbHFahrenberg 22Telephone: +49 40 67057022885 BarsbüttelTelefax: +49 40 6703227GermanyGermany

# Department responsible for information

E-mail (competent person)

# 1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40 available 24h/365days; Information will be provided in German and English

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage. Skin Corr. 1; Skin corrosion/irritation; H314 Causes severe skin burns and eye damage.

msds@webac.de

#### 2.2 Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

# Hazard pictograms



GHS05		
Signal word		
Danger		
Hazard statements		
H314	Causes severe skin burns and eye damage.	
Precautionary stateme	ents	
P260	Do not breathe vapours.	
P280	Wear protective gloves and eye protection/face protection.	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER.	
Hazard components for labelling not applicable		

# Supplemental hazard information

not applicable



WEBAC 2100 Version 2.0

Revision date 20-Dec-2024

### 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# SECTION 3: Composition/information on ingredients.

### 3.2 Mixtures

#### Description

waterproofing agent

### Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
1344-09-8 215-687-4 -	Silicic acid, sodium salt 01-2119448725-31-xxxx Skin Irrit. 2 H315 / Eye Irrit. 2 H319	10,0 <= 25,0
31795-24-1 250-807-9 -	potassium methylsilanetriolate 01-2119517439-34-xxxx Skin Corr. 1A H314 / Eye Dam. 1 H318 ATE (oral): > 2,000 mg/kg	1,00 <= 2,50

#### Remark

Full text of H- and EUH-statements: see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### **Following inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

#### Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

# 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

# Unsuitable extinguishing media

Strong water jet



WEBAC 2100 Version 2.0

Revision date 20-Dec-2024

# 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

Clean using cleansing agents. Do not use solvents.

#### 6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

### **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8 Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Do not store together with: Food and feedingstuffs

Storage class LGK8A - Combustible corrosive substances

# Further information on storage conditions

\* Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C.

# 7.3 Specific end use(s)

Observe technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Occupational exposure limit values No data available Biological limit values No data available



**WEBAC 2100** Version 2.0

Revision date 20-Dec-2024

**DNEL** worker CAS No. **DNEL** type **DNEL** value Substance name Silicic acid, sodium salt 1.59 mg/kg bw/day 1344-09-8 DNEL long-term dermal (systemic) 1344-09-8 Silicic acid, sodium salt DNEL long-term inhalative (systemic) 5.61 mg/m<sup>3</sup> 31795-24-1 potassium methylsilanetriolate DNEL long-term dermal (systemic) 6.6 mg/kg bw/day 31795-24-1 DNEL acute dermal, short-term potassium methylsilanetriolate 6.6 mg/kg bw/day (systemic) 31795-24-1 potassium methylsilanetriolate DNEL long-term inhalative (systemic) 47 mg/m<sup>3</sup> 31795-24-1 potassium methylsilanetriolate DNEL acute inhalative (systemic) 47 mg/m<sup>3</sup>

# PNEC

	CAS No.	Substance name	PNEC type	PNEC Value
*	1344-09-8	Silicic acid, sodium salt	PNEC aquatic, intermittent release	7.5 mg/L
*	1344-09-8	Silicic acid, sodium salt	PNEC aquatic, freshwater	7.5 mg/L
	1344-09-8	Silicic acid, sodium salt	PNEC aquatic, marine water	1 mg/L
	1344-09-8	Silicic acid, sodium salt	PNEC sewage treatment plant (STP)	348 mg/L

# 8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

### Personal protection equipment

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

# Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0.4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

# Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

# Eye/face protection

Eye glasses with side protection: EN 166

Wear closely fitting protective glasses in case of splashes.

# **Body protection**

Wear suitable protective clothing. Change contaminated, saturated clothing.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

# **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties 9.1

Liquid
colourless
characteristic
12 - 13
not determined
not determined
> 101 °C
not applicable
not determined
not determined



Vers	ion 2.0 Revision of	late 20-Dec-2024	Print date 20-Dec-2024
	Vapour pressure at 20°C	23.085 mbar	
	Relative vapour density	not applicable	
	Density at 20 °C	1.1 kg/l	
	Water solubility at 20°C	completely miscible	
	Partition coefficient: n-octanol/water	see section 12	
	Ignition temperature in °C	not determined	
	Decomposition temperature	not determined	
	Viscosity at 20 °C:	> 20.5 mm²/s	
	particle characteristics	not applicable	
9.2	Other information		
	not applicable		

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

**WEBAC 2100** 

No hazardous reaction when handled and stored according to provisions.

# 10.2 Chemical stability

Stable under recommended storage and handling conditions. Please note the expiry date.

# 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

# 10.5 Incompatible materials

No further relevant information available.

# 10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

- potassium methylsilanetriolate
- LD50: oral (Rat): > 2,000 mg/kg; (OECD 423)

# Skin corrosion/irritation

Causes severe skin burns and eye damage.

# Serious eye damage/eye irritation

Causes serious eye damage.

# Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

# Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met. **Aspiration hazard** 

Based on available data, the classification criteria are not met.

# 11.2 Information on other hazards

# Endocrine disrupting properties



WEBAC 2100 Version 2.0

Revision date 20-Dec-2024

Print date 20-Dec-2024

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Based on available data, the classification criteria are not met.

#### Daphnia toxicity Silicic acid, sodium salt EC50 > 100 mg/L (48 h)

#### Fish toxicity EC50 > 100 mg/L

LC50: > 100 mg/L (96 h)

### 12.2 Persistence and degradability

No information available.

#### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7 Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.

### Waste codes/waste designations according to EWC/AVV

080409\* - Waste adhesives and sealants containing organic solvents or other dangerous substances Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

not applicable

# 14.2 UN proper shipping name

#### Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

#### Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

# Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

# 14.3 Transport hazard class(es)

not applicable

#### 14.4 Packing group

not applicable



Print date 20-Dec-2024

WEBAC 2100 Version 2.0

Revision date 20-Dec-2024

14.5 Environmental hazards

Land transport (ADR/RID) Sea transport (IMDG)

not applicable not applicable

# 14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

# No transport as bulk according to IBC Code.

# 14.8 Additional information

Land transport (ADR/RID)

not applicable

### Sea transport (IMDG)

not applicable

# Air transport (ICAO-TI / IATA-DGR)

not applicable

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU legislation

# **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

# Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 2 g/l

# Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

# Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

#### National regulations

Observe in addition any national regulations!

# 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

List of relevant hazard statements and/or precautionary	statements from sections 2 to 15
---	----------------------------------

H314 Causes severe skin burns and eye damage.

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

# Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Eye Dam. 1 On basis of test data.

Skin Corr. 1 On basis of test data.

# Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive



WEBAC 2100 Version 2.0

Revision date 20-Dec-2024

EC: Effective Concentration EC: European Community EN: European Standard IATA-DGR: International Air Transport Association - Dangerous Goods Regulations IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization LC: Lethal Concentration LD: Lethal Dose MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OECD: Organisation for Economic Cooperation and Development PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RID: Regulations concerning the International Carriage of Dangerous Goods by Rail **UN: United Nations** VOC: Volatile Organic Compounds vPvB: very persistent and very bioaccumulative

# Indication of changes

\* Data changed compared with the previous version.