

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

#### Trade name/designation

WEBAC 4120P Comp. B  
Epoxy Injection Resin

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

#### Relevant identified uses

hardener/amine component for epoxy resin

### 1.3 Details of the supplier of the safety data sheet

#### supplier

WEBAC-Chemie GmbH

Fahrenberg 22  
22885 Barsbüttel  
Deutschland

Telephone: +49 40 670570  
Telefax: +49 40 6703227

#### Department responsible for information

E-mail (competent person) msds@webac.de

### 1.4 Emergency telephone number

#### Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40  
available 24h/365days; Information will be provided in German and English

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage.

Repr. 2; Reproductive toxicity; H361 Suspected of damaging fertility or the unborn child.

STOT RE 2; STOT-repeated exposure; H373 May cause damage to organs through prolonged or repeated exposure.

Skin Corr. 1B; Skin corrosion/irritation; H314 Causes severe skin burns and eye damage.

Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

Aquatic Chronic 3; Hazardous to the aquatic environment; H412 Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



GHS05 GHS07 GHS08

#### Signal word

Danger

#### Hazard statements

H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P260	Do not breathe vapours.
P280	Wear protective gloves and eye/face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER.

#### Hazard components for labelling

2-piperazin-1-ylethylamine  
4,4'-methylenebis(cyclohexylamine)  
Amines, polyethylenepoly-, triethylenetetramine fraction  
Hydrocarbons, C9-unsaturated, polymerized  
Methyleneoxide, polymer with benzenamine, hydrogenated  
Poly(oxypropylene)diamine

#### Supplemental hazard information

not applicable

### 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients.

### 3.2 Mixtures

#### Description

hardener/amine component for epoxy resin

#### Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
9046-10-0 618-561-0 -	<b>Poly(oxypropylene)diamine</b> 01-2119557899-12-xxxx Skin Corr. 1C H314 / Aquatic Chronic 3 H412 ATE (dermal): = 2.980 mg/kg ATE (oral): = 2.885 mg/kg	25,0 < 50,0
90640-67-8 292-588-2 -	<b>Amines, polyethylenepoly-, triethylenetetramine fraction</b> 01-2119487919-13-xxxx Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412 ATE (oral): = 5.500 mg/kg ATE (dermal): = 1.465 mg/kg ATE (oral): = 1.600 mg/kg ATE (oral): = 1.716 mg/kg	10,0 < 25,0
100-51-6 202-859-9 603-057-00-5	<b>benzyl alcohol</b> 01-2119492630-38-xxxx Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 ATE (dermal): = 2.000 mg/kg ATE (oral): = 1.230 mg/kg ATE (inhalative): > 4,178 mg/L (4 h)	10,0 < 25,0
140-31-8 205-411-0 612-105-00-4	<b>2-piperazin-1-ylethylamine</b> 01-2119471486-30-xxxx Acute Tox. 4 H302 / Acute Tox. 3 H311 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Repr. 2 H361 / STOT RE 1 H372 / Aquatic Chronic 3 H412 ATE (dermal): = 866 mg/kg ATE (oral): = 2.000 mg/kg	2,50 < 10,0
135108-88-2 603-894-6 -	<b>Methyleneoxide, polymer with benzenamine, hydrogenated</b> 01-2119983522-33-xxxx Acute Tox. 4 H302 / Skin Corr. 1C H314 / Skin Sens. 1 H317 / STOT RE 2 H373 / Aquatic Chronic 3 H412 ATE (dermal): > 2.000 mg/kg ATE (oral): = 367 mg/kg	2,50 < 10,0
71302-83-5 701-299-7 -	<b>Hydrocarbons, C9-unsaturated, polymerized</b> 01-2119555292-40-xxxx Asp. Tox. 1 H304 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412	2,50 < 10,0
2579-20-6 219-941-5 -	<b>1,3-Cyclohexanedimethanamine</b> 01-2119543741-41-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1C H314 / Aquatic Chronic 3 H412 ATE (dermal): = 1.700 mg/kg ATE (oral): = 700 mg/kg	2,50 < 10,0
1761-71-3 217-168-8 -	<b>4,4'-methylenebis(cyclohexylamine)</b> 01-2119541673-38-xxxx Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1B H317 / STOT RE 2 H373 ATE (dermal): = 2.110 mg/kg ATE (oral): = 625 mg/kg	1,00 < 2,50

#### Remark

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

#### Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Powder, spray mist, (water)

#### Unsuitable extinguishing media

Strong water jet

### 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

Clean using cleansing agents. Do not use solvents.

### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8  
Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons.  
Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.  
Do not store together with: Food and feedingstuffs

**Storage class** LGK8A - Combustible corrosive substances

### 7.3 Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No data available

#### Biological limit values

No data available

#### DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL long-term dermal (systemic)	0,2 mg/kg bw/day
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL long-term inhalative (systemic)	0,71 mg/m <sup>3</sup>
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL acute inhalative (systemic)	21,2 mg/m <sup>3</sup>
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL acute dermal, short-term (systemic)	6 mg/kg
140-31-8	2-piperazin-1-ylethylamine	DNEL long-term dermal (local)	0,6 mg/dm <sup>2</sup>
140-31-8	2-piperazin-1-ylethylamine	DNEL acute dermal, short-term (local)	4 mg/dm <sup>2</sup>
140-31-8	2-piperazin-1-ylethylamine	DNEL long-term dermal (systemic)	3,33 mg/kg bw/day
140-31-8	2-piperazin-1-ylethylamine	DNEL acute inhalative (systemic)	21,4 mg/m <sup>3</sup>
140-31-8	2-piperazin-1-ylethylamine	DNEL long-term inhalative (systemic)	3,6 mg/m <sup>3</sup>
140-31-8	2-piperazin-1-ylethylamine	DNEL acute dermal, short-term (systemic)	20 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	DNEL long-term dermal (systemic)	0,1 mg/kg bw/day
1761-71-3	4,4'-methylenebis(cyclohexylamine)	DNEL long-term inhalative (systemic)	1 mg/m <sup>3</sup>
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term inhalative (systemic)	3,3 mg/m <sup>3</sup>
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term dermal (systemic)	4,7 mg/kg
9046-10-0	Poly(oxypropylene)diamine	DNEL long-term dermal (local)	62,3 mg/dm <sup>2</sup>
9046-10-0	Poly(oxypropylene)diamine	DNEL long-term dermal (systemic)	2,5 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL acute dermal, short-term (systemic)	47 mg/kg bw/day

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



WEBAC 4120P Comp. B  
Version 1.0

Revision date 15-May-2023

Print date 15-May-2023

100-51-6	benzyl alcohol	DNEL long-term dermal (systemic)	9,5 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL acute inhalative (systemic)	450 mg/m <sup>3</sup>
100-51-6	benzyl alcohol	DNEL long-term inhalative (systemic)	90 mg/m <sup>3</sup>

**PNEC**

CAS No.	Substance name	PNEC type	PNEC Value
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, intermittent release	0,331 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC sewage treatment plant (STP)	10 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, marine water	0,033 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, freshwater	0,033 mg/L
140-31-8	2-piperazin-1-ylethylamine	PNEC aquatic, intermittent release	0,58 mg/L
140-31-8	2-piperazin-1-ylethylamine	PNEC sewage treatment plant (STP)	250 mg/L
140-31-8	2-piperazin-1-ylethylamine	PNEC aquatic, marine water	0,006 mg/L
140-31-8	2-piperazin-1-ylethylamine	PNEC aquatic, freshwater	0,058 mg/L
140-31-8	2-piperazin-1-ylethylamine	PNEC sediment, marine water	21,5 mg/kg
140-31-8	2-piperazin-1-ylethylamine	PNEC sediment, freshwater	215 mg/kg
140-31-8	2-piperazin-1-ylethylamine	PNEC soil, freshwater	42,9 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, intermittent release	0,08 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, marine water	0,001 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, freshwater	0,008 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sewage treatment plant (STP)	80 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sediment, marine water	0,039 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sediment, freshwater	0,39 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC soil, freshwater	0,072 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, freshwater	0,026 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, intermittent release	0,54 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, marine water	0,003 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sewage treatment plant (STP)	0,26 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sediment, marine water	196 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sediment, freshwater	1.960 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC soil, freshwater	391 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC aquatic, marine water	0,014 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC aquatic, freshwater	0,015 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC aquatic, intermittent release	0,15 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC Secondary Poisoning	6,93 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC sewage treatment plant (STP)	7,5 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC sediment, marine water	0,125 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC sediment, freshwater	0,132 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC soil, freshwater	0,018 mg/kg
100-51-6	benzyl alcohol	PNEC aquatic, intermittent release	2,3 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, marine water	0,1 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, freshwater	1 mg/L
100-51-6	benzyl alcohol	PNEC sewage treatment plant (STP)	39 mg/L
100-51-6	benzyl alcohol	PNEC sediment, marine water	0,527 mg/kg
100-51-6	benzyl alcohol	PNEC sediment, freshwater	5,27 mg/kg
100-51-6	benzyl alcohol	PNEC soil, freshwater	0,456 mg/kg

**8.2 Exposure controls**

Provide good ventilation. This can be achieved with local or room suction.

**Personal protection equipment**

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### **Hand protection**

Suitable material: NBR (Nitrile rubber)  
Thickness of the glove material  $\geq 0,4$  mm  
Breakthrough time  $\geq 480$  min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.  
Recommended glove articles: EN ISO 374

#### **Skin protection**

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### **Eye/face protection**

Eye glasses with side protection: EN 166  
Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear suitable protective clothing. Change contaminated, saturated clothing.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

Physical state	Liquid
Colour	yellow
Odour	characteristic
pH	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	$> 101$ °C
flammability	not applicable
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	0,651 mbar
Relative vapour density	not applicable
Density at 20 °C	0,971 kg/l
Water solubility at 20°C	practically insoluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined
Viscosity at 20 °C:	$> 20,5$ mm <sup>2</sup> /s
particle characteristics	not applicable

### **9.2 Other information**

not applicable

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

No hazardous reaction when handled and stored according to provisions.

### **10.2 Chemical stability**

Stable under recommended storage and handling conditions.  
Please note the expiry date.



### 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

### 10.5 Incompatible materials

No further relevant information available.

### 10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, smoke.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### 1,3-Cyclohexanedimethanamine

LD50: dermal (Rabbit): = 1.700 mg/kg

LD50: oral (Rat): = 700 mg/kg

#### 2-piperazin-1-ylethylamine

LD50: dermal (Rabbit): = 866 mg/kg; (literature value)

LD50: oral (Rat): = 2.000 mg/kg

#### 4,4'-methylenebis(cyclohexylamine)

LD50: dermal (Rabbit): = 2.110 mg/kg

LD50: oral (Rat): = 625 mg/kg

#### Amines, polyethylenepoly-, triethylenetetramine fraction

LD50: oral (Rabbit): = 5.500 mg/kg

LD50: dermal (Rabbit): = 1.465 mg/kg

LD50: oral (Mouse): = 1.600 mg/kg

LD50: oral (Rat): = 1.716 mg/kg

#### Methyleneoxide, polymer with benzenamine, hydrogenated

LD50: dermal (Rabbit): > 2.000 mg/kg

LD50: oral (Rat): = 367 mg/kg

#### Poly(oxypropylene)diamine

LD50: dermal (Rabbit): = 2.980 mg/kg

LD50: oral (Rat): = 2.885 mg/kg

#### benzyl alcohol

LD50: dermal (Rabbit): = 2.000 mg/kg

LD50: oral (Rat): = 1.230 mg/kg

LC50: inhalative (Rat): > 4,178 mg/L (4 h)

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

May cause an allergic skin reaction.

#### Overall assessment on CMR properties

Suspected of damaging fertility or the unborn child.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Indications for this are:

Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Harmful to aquatic life with long lasting effects.

**Algae toxicity**

**1,3-Cyclohexanedimethanamine**

ErC50: (Pseudokirchneriella subcapitata): > 100 mg/L (72 h)

Method: OECD 201

**2-piperazin-1-ylethylamine**

ErC50: (Pseudokirchneriella subcapitata): > 1.000 mg/L (72 h)

**Amines, polyethylenepoly-, triethylenetetramine fraction**

EC50 (Scenedesmus subspicatus): = 2,5 (16 h)

ErC50: (Selenastrum capricornutum): = 20 mg/L (72 h)

**Poly(oxypropylene)diamine**

ErC50: (Pseudokirchneriella subcapitata): = 15 mg/L (72 h)

**benzyl alcohol**

ErC50: (Pseudokirchneriella subcapitata): = 770 mg/L (72 h)

NOEC (Pseudokirchneriella subcapitata): = 310 mg/L (72 h)

**Daphnia toxicity**

**1,3-Cyclohexanedimethanamine**

EC50 (Daphnia magna (Big water flea)): = 65,4 mg/L (48 h)

Method: OECD 202

**2-piperazin-1-ylethylamine**

EC50 (Daphnia magna (Big water flea)): = 58 mg/L (48 h)

**Amines, polyethylenepoly-, triethylenetetramine fraction**

EC50 (Daphnia magna (Big water flea)): = 31 mg/L (48 h)

**Poly(oxypropylene)diamine**

EC50 (Daphnia magna (Big water flea)): = 80 mg/L (48 h)

**benzyl alcohol**

EC50 (Daphnia magna (Big water flea)): = 230 mg/L (48 h)

**Fish toxicity**

**1,3-Cyclohexanedimethanamine**

LC50: (Leuciscus idus (golden orfe)): = 130 mg/L (96 h)

Method: OECD 203

**2-piperazin-1-ylethylamine**

LC50: (Poecilia reticulata (Guppy)): = 368 mg/L (96 h)

**Amines, polyethylenepoly-, triethylenetetramine fraction**

= 0,003 mg/L

= 0,135 mg/L

= 800 mg/L

EC50 (Pseudomonas putida): = 137 mg/L

LC50: = 330 mg/L (96 h)



LC50: (Poecilia reticulata (Guppy)): = 570 (96 h)

**Poly(oxypropylene)diamine**

NOEC (Oncorhynchus mykiss (Rainbow trout)): = 15 mg/L (96 h)

LC50: (Leuciscus idus (golden orfe)): > 15 mg/L (96 h)

**benzyl alcohol**

LC50: = 460 mg/L (96 h)

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

**1,3-Cyclohexanedimethanamine**

Partition coefficient: n-octanol/water = 0,73

Method: OECD 107

**12.4 Mobility in soil**

**Hydrocarbons, C9-unsaturated, polymerized**

= 5,5

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6 Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Product/Packaging disposal**

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Waste codes/waste designations according to EWC/AVV**

080409\* - Waste adhesives and sealants containing organic solvents or other dangerous substances

Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Other disposal recommendations**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1 UN number or ID number**

UN 2735

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**

AMINE, FLÜSSIG, ÄTZEND, N.A.G (enthält TRIETHYLENTETRAMIN, METHYLENOXID, POLYMER MIT BENZENAMIN, HYDRIERT)

**Sea transport (IMDG)**

Amines, liquid, corrosive, n.o.s. (contain TRIETHYLENETETRAMINE, METHYLENEOXIDE, POLYMER WITH BENZENAMINE, HYDROGENATED)

**Air transport (ICAO-TI / IATA-DGR)**

Amines, liquid, corrosive, n.o.s. (contain TRIETHYLENETETRAMINE, METHYLENEOXIDE, POLYMER WITH BENZENAMINE, HYDROGENATED)

**14.3 Transport hazard class(es)**

Land transport (ADR/RID) 8

Sea transport (IMDG) 8

Air transport (ICAO-TI / IATA-DGR) 8

**14.4 Packing group**

Land transport (ADR/RID)	II
Sea transport (IMDG)	II
Air transport (ICAO-TI / IATA-DGR)	II

#### 14.5 Environmental hazards

Land transport (ADR/RID)	not applicable
Sea transport (IMDG)	not applicable

#### 14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

#### 14.8 Additional information

##### Land transport (ADR/RID)

Tunnel restriction code: E

Limited quantity (LQ): 1 ltr

Hazard identification number (Kemler No.): 80

##### Sea transport (IMDG)

Segregation group: IMDG-Code segregation group 18 - Alkalies

EmS-No.: F-A, S-B

Limited quantity (LQ): 1 ltr

##### Air transport (ICAO-TI / IATA-DGR)

not applicable

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

##### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 98 g/l

##### Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

##### Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

##### National regulations

Observe in addition any national regulations!

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

H372	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H412	Harmful to aquatic life with long lasting effects.

**Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

Eye Dam. 1	Calculation method.
Repr. 2	Calculation method.
STOT RE 2	Calculation method.
Skin Corr. 1B	Calculation method.
Skin Sens. 1	Calculation method.
Aquatic Chronic 3	Calculation method.

**Abbreviations and acronyms**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
OEL: Occupational Exposure Limit Value  
BLV: Biological limit values  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging  
CMR: Carcinogenic, Mutagenic and Reprotoxic  
DIN: German Institute for Standardization / German industrial standard  
DNEL: Derived No-Effect Level  
EAKV: European Waste Catalogue Directive  
EC: Effective Concentration  
EC: European Community  
EN: European Standard  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG Code: International Maritime Code for Dangerous Goods  
ISO: International Organization for Standardization  
LC: Lethal Concentration  
LD: Lethal Dose  
:  
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
OECD: Organisation for Economic Cooperation and Development  
PBT: persistent, bioaccumulative, toxic  
PNEC: Predicted No Effect Concentration  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
UN: United Nations  
VOC: Volatile Organic Compounds  
vPvB: very persistent and very bioaccumulative

**Indication of changes**

\* Data changed compared with the previous version.