according to Regulation (EC) No. 1907/2006 (REACH)





WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

WEBAC 4130 Comp. A **Epoxy Injection Resin**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

epoxy resin component

1.3 Details of the supplier of the safety data sheet

supplier

WEBAC-Chemie GmbH

Fahrenberg 22 Telephone: +49 40 670570 Telefax: +49 40 6703227 22885 Barsbüttel Deutschland

Department responsible for information

msds@webac.de E-mail (competent person)

1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40

available 24h/365days; Information will be provided in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation.

Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.

Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

Aquatic Chronic 2; Hazardous to the aquatic environment; H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





GHS09 GHS07

Signal word

Warning

Hazard statements

H319 Causes serious eve irritation. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects. H411

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P391 Collect spillage.

Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane

Hydrocarbons, C9-unsaturated, polymerized

Page 1/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023

Print date 16-May-2023

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Supplemental hazard information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

epoxy resin component

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
1675-54-3 216-823-5 -	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 01-2119456619-26-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Aquatic Chronic 2 H411 Specific concentration limit (SCL) Eye Irrit. 2 H319: >= 5,00 / Skin Irrit. 2 H315: >= 5,00 ATE (dermal): = 23.000 mg/kg ATE (oral): = 15.000 mg/kg	50,0 < 100,0
701-263-0 -	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane 01-2119454392-40-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411 ATE (oral): > 5.000 mg/kg ATE (dermal): > 2.000 mg/kg	10,0 < 25,0
933999-84-9 618-939-5 -	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) 01-2119463471-41-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Aquatic Chronic 3 H412 ATE (oral): = 2.190 mg/kg	2,50 < 10,0
- 701-328-3 -	Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane 01-2119962192-39-xxxx Skin Sens. 1 H317 / Aquatic Chronic 2 H411 ATE (dermal): > 2.000 mg/kg ATE (oral): = 26.800 mg/kg	2,50 < 10,0
71302-83-5 701-299-7	Hydrocarbons, C9-unsaturated, polymerized 01-2119555292-40-xxxx Asp. Tox. 1 H304 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412	2,50 < 10,0

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Page 2/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023

Print date 16-May-2023

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8 Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Page 3/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023

Print date 16-May-2023

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Do not store together with: Food and feedingstuffs

Storage class LGK10 - Combustiti

LGK10 - Combustible liquids that cannot be assigned to any of the above storage classes

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	DNEL long-term dermal (systemic)	0,75 mg/kg bw/day
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	DNEL long-term inhalative (systemic)	4,93 mg/m³
-	Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane	DNEL long-term dermal (systemic)	4 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term inhalative (systemic)	3,3 mg/m ³
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term dermal (systemic)	4,7 mg/kg
-	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane	DNEL long-term dermal (systemic)	104,15 mg/kg bw/ day
-	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane	DNEL long-term inhalative (systemic)	29,39 mg/m³
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	DNEL long-term dermal (systemic)	2,8 mg/kg bw/day
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	DNEL long-term inhalative (systemic)	4,9 mg/m³
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	DNEL acute inhalative (systemic)	4,9 mg/m³

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	PNEC Secondary Poisoning	11 mg/kg
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	PNEC sewage treatment plant (STP)	10 mg/L
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	PNEC aquatic, freshwater	0,006 mg/L
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	PNEC aquatic, marine water	0,001 mg/L
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	PNEC sediment, marine water	0,034 mg/kg
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	PNEC sediment, freshwater	0,341 mg/kg

Page 4/11 IE (en_GB)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-PNEC soil, freshwater 0,065 mg/kg phenyleneoxymethylene)]bisoxirane Alcohols C13-15 (branched and linear, odd numbered). 0,001 mg/L PNEC aquatic, marine water reaction product with 1-chloro-2,3-epoxypropane Alcohols C13-15 (branched and linear, odd numbered), PNEC aquatic, freshwater 0,007 mg/L reaction product with 1-chloro-2,3-epoxypropane Alcohols C13-15 (branched and linear, odd numbered), PNEC aquatic, intermittent release 0,072 mg/L reaction product with 1-chloro-2,3-epoxypropane Alcohols C13-15 (branched and linear, odd numbered), PNEC sewage treatment plant (STP) 1 mg/L reaction product with 1-chloro-2,3-epoxypropane Alcohols C13-15 (branched and linear, odd numbered), PNEC sediment, marine water 0,677 mg/kg reaction product with 1-chloro-2,3-epoxypropane Alcohols C13-15 (branched and linear, odd numbered). PNEC sediment freshwater 6,677 mg/kg reaction product with 1-chloro-2,3-epoxypropane Alcohols C13-15 (branched and linear, odd numbered), PNEC soil, freshwater 8,012 mg/kg reaction product with 1-chloro-2,3-epoxypropane 0,026 mg/L 71302-83-5 Hydrocarbons, C9-unsaturated, polymerized PNEC aquatic, freshwater Hydrocarbons, C9-unsaturated, polymerized 0,54 mg/L 71302-83-5 PNEC aquatic, intermittent release 71302-83-5 Hydrocarbons, C9-unsaturated, polymerized PNEC aquatic, marine water 0,003 mg/L 71302-83-5 Hydrocarbons, C9-unsaturated, polymerized PNEC sewage treatment plant (STP) 0,26 mg/L 71302-83-5 Hydrocarbons, C9-unsaturated, polymerized PNEC sediment, marine water 196 mg/kg 71302-83-5 Hydrocarbons, C9-unsaturated, polymerized PNEC sediment, freshwater 1.960 mg/kg 71302-83-5 Hydrocarbons, C9-unsaturated, polymerized PNEC soil, freshwater 391 mg/kg Reaction mass of 2,2'-[methylenebis(2,1-0 mg/L PNEC aquatic, marine water phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane Reaction mass of 2,2'-[methylenebis(2,1-0,003 mg/L PNEC aquatic, freshwater phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane Reaction mass of 2,2'-[methylenebis(2,1-PNEC aquatic, intermittent release 0,025 mg/L phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane Reaction mass of 2,2'-[methylenebis(2,1-PNEC sewage treatment plant (STP) 10 ma/L phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane Reaction mass of 2,2'-[methylenebis(2,1-PNEC sediment, marine water 0,029 mg/kg phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane Reaction mass of 2,2'-[methylenebis(2,1-PNEC sediment, freshwater 0,294 mg/kg phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane Reaction mass of 2,2'-[methylenebis(2,1-PNEC soil, freshwater 0,237 mg/kg phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy)methyl)oxirane reaction products of hexane-1,6-diol with 2-0,011 mg/L 933999-84-9 PNEC aquatic, marine water (chloromethyl)oxirane (1:2)

Page 5/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

ion 1.0	Revision date 15-May-2023	Pr	int date 16-May-2023
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC aquatic, freshwater	0,011 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC aquatic, intermittent release	0,115 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	PNEC sewage treatment plant (STP)	1 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	PNEC sediment, marine water	0,028 mg/kg
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC sediment, freshwater	0,283 mg/kg
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC soil, freshwater	0,223 mg/kg

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0,4 mm

Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing. Change contaminated, saturated clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid Colour colourless Odour characteristic рΗ not applicable Melting point/freezing point not determined Initial boiling point and boiling range not determined > 101 °C Flash point flammability not applicable Lower explosion limit at 20°C not determined not determined Upper explosion limit at 20°C Vapour pressure at 20°C 0,619 mbar Relative vapour density not applicable Density at 20 °C 1,135 kg/l Water solubility at 20°C not determined

Page 6/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

Partition coefficient: n-octanol/water see section 12
Ignition temperature in °C not determined
Decomposition temperature not determined
Viscosity at 20 °C: > 20,5 mm²/s
particle characteristics not applicable

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2 Chemical stability

Stable under recommended storage and handling conditions.

Please note the expiry date.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

LD50: dermal (Rabbit): = 23.000 mg/kg

LD50: oral (Rat): = 15.000 mg/kg

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane

LD50: dermal (Rat): > 2.000 mg/kg LD50: oral (Rat): = 26.800 mg/kg

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

LD50: oral (Rat): > 5.000 mg/kg

LD50: dermal (Rat): > 2.000 mg/kg

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

LD50: oral (Rat): = 2.190 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Page 7/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023

Print date 16-May-2023

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Indications for this are:

Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Algae toxicity

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

ErC50: = 11 mg/L (72 h)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane ErC50: = 1,8 mg/L (72 h)

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

ErC50: = 23,1 mg/L (48 h)

Daphnia toxicity

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC50 = 1.8 mg/L (48 h)

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane EC50 = 7.2 mg/L (48 h)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane EC50 = 2,55 mg/L (48 h)

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

EC50 = 47 mg/L (48 h)

Fish toxicity

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 2 mg/L (96 h)

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane LC50: = 7 mg/L (96 h)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane LC50: = 2,54 mg/L (96 h)

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

LC50: (Leuciscus idus (golden orfe)): = 30 mg/L (96 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Partition coefficient: n-octanol/water = 0,822

Method: OECD 107

12.4 Mobility in soil

Page 8/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

Hydrocarbons, C9-unsaturated, polymerized

=5,5

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

UN 3082

14.2 UN proper shipping name

Land transport (ADR/RID)

UMWELTGEFÄHRDENDER STOFF, FLÜSSIG, N.A.G. (enthält BISPHENOL-A-EPICHLORHYDRINHARZE, BISPHENOL-F-EPICHLORHYDRINHARZE)

Sea transport (IMDG)

Environmentally hazardous substance, liquid, n.o.s. (contain BISPHENOL-A-EPICHLORHYDRIN RESINS, BISPHENOL-F-EPICHLORHYDRIN RESINS)

Air transport (ICAO-TI / IATA-DGR)

Environmentally hazardous substance, liquid, n.o.s. (contain BISPHENOL-A-EPICHLORHYDRIN RESINS, BISPHENOL-F-EPICHLORHYDRIN RESINS)

14.3 Transport hazard class(es)

Land transport (ADR/RID) 9
Sea transport (IMDG) 9
Air transport (ICAO-TI / IATA-DGR) 9

14.4 Packing group

Land transport (ADR/RID) III
Sea transport (IMDG) III
Air transport (ICAO-TI / IATA-DGR) III

14.5 Environmental hazards

Land transport (ADR/RID) ENVIRONMENTALLY HAZARDOUS

Sea transport (IMDG) Marine pollutant / BISPHENOL-A-EPICHLORHYDRINHARZE

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Page 9/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

Tunnel restriction code: -Limited quantity (LQ): 5 ltr

Hazard identification number (Kemler No.): 90

Sea transport (IMDG)

EmS-No.: F-A S-F Limited quantity (LQ): 5 ltr

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 1 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value: 2004/42/IIA(j): 500 g/l (2010)

Maximum VOC content of the product in a ready to use condition: 1135

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200t; Quantity 2: 500t

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 Calculation method.
Skin Irrit. 2 Calculation method.
Skin Sens. 1 Calculation method.
Aquatic Chronic 2 Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

Page 10/11 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4130 Comp. A

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

EC: European Community EN: European Standard

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.

Page 11/11 IE (en_GB)