# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Trade name/designation

WEBAC 4170 Komp. B EP Injektionsharz

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

#### Relevant identified uses

#### 1.3 Details of the supplier of the safety data sheet

#### supplier

WEBAC-Chemie GmbH

Fahrenberg 22 Telephone: +49 40 670570 22885 Barsbüttel Telefax: +49 40 6703227

Germany

#### Department responsible for information

E-mail (competent person) msds@webac.de

#### 1.4 Emergency telephone number

#### Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40

available 24h/365days; Information will be provided in German and English

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 oral; Acute toxicity; H302 Harmful if swallowed.

Skin Corr. 1A; Skin corrosion/irritation; H314 Causes severe skin burns and eye damage.

Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage.

Aquatic Chronic 1; Hazardous to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### **Hazard pictograms**



GHS05 GHS07 GHS09

#### Signal word

Danger

#### **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Page 1/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

P310 Immediately call a POISON CENTER.

P391 Collect spillage.

#### Hazard components for labelling

1,3-Cyclohexanedimethanamine

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

3,6-dioxaoctamethylenediamine

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Amines, polyethylenepoly-, triethylenetetramine fraction

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

3-aminopropyldimethylamine

Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols

[Fatty acids, C18-unsaturated, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine] reaction

products with glycidyl tolyl ether m-phenylenebis(methylamine)

#### Supplemental hazard information

EUH071 Corrosive to the respiratory tract.

#### 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### **SECTION 3: Composition/information on ingredients.**

#### 3.2 Mixtures

#### Description

#### Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
90640-67-8 292-588-2 -	Amines, polyethylenepoly-, triethylenetetramine fraction 01-2119487919-13-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Aquatic Chronic 3 H412 / EUH071 ATE (dermal): 1,465 mg/kg ATE (oral): 1,716 mg/kg	10,0 <= 25,0
38640-62-9 254-052-6 -	Bis(isopropyl)naphthalene 01-2119565150-48-xxxx Asp. Tox. 1 H304 / Aquatic Chronic 1 H410 (M = 1,00)	10,0 <= 25,0
929-59-9 213-203-6 -	3,6-dioxaoctamethylenediamine 01-2120734009-59 Acute Tox. 4 H302 / Skin Corr. 1C H314 / Skin Sens. 1 H317 / Eye Dam. 1 H318 ATE (dermal): > 8,000 mg/kg ATE (oral): 1,600 mg/kg	10,0 <= 25,0
1477-55-0 216-032-5 -	m-phenylenebis(methylamine) 01-2119480150-50-xxxx Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Acute Tox. 4 H332 / Aquatic Chronic 3 H412 / EUH071 ATE (dermal): > 3,100 mg/kg ATE (oral): 930 mg/kg	10,0 <= 25,0
2579-20-6 219-941-5 -	1,3-Cyclohexanedimethanamine 01-2119543741-41-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Aquatic Chronic 3 H412 ATE (dermal): 1,700 mg/kg ATE (oral): 700 mg/kg	2,50 <= 10,0
- 701-443-9 -	Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols 01-2119980970-27-xxxx Skin Irrit. 2 H315 / Skin Sens. 1A H317 / Aquatic Chronic 2 H411 ATE (oral): > 2,000 mg/kg ATE (dermal): > 2,000 mg/kg	2,50 <= 10,0
25513-64-8 247-063-2 -	<b>2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine</b> 01-2119560598-25-xxxx Acute Tox. 4 H302 / Skin Corr. 1A H314 / Skin Sens. 1A H317	2,50 <= 10,0

Page 2/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

on 1.0	Revision date 1 Jul 2025	Print date 2 Jul
	ATE (oral): 910 mg/kg	
100-51-6 202-859-9 603-057-00-5	benzyl alcohol 01-2119492630-38-xxxx Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 ATE (dermal): > 2,000 mg/kg ATE (oral): 1,620 mg/kg ATE (inhalative): 1.5 mg/L (4 h)	2,50 <= 10,0
2855-13-2 220-666-8 612-067-00-9	3-aminomethyl-3,5,5-trimethylcyclohexylamine 01-2119514687-32-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412 Specific concentration limit (SCL) Skin Sens. 1A H317: >= 0,001 ATE (dermal): 1,840 mg/kg ATE (oral): 1,030 mg/kg	2,50 <= 10,0
68082-29-1 500-191-5 -	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 01-2119972320-44-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Aquatic Chronic 2 H411 ATE (dermal): > 2,000 mg/kg ATE (oral): > 2,000 mg/kg	1,00 <= 2,50
2919722-63-5 968-660-0 -	[Fatty acids, C18-unsaturated, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine] reaction products with glycidyl tolyl ether Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Aquatic Chronic 2 H411	1,00 <= 2,50
61788-46-3 262-977-1 612-285-00-4	amines, coco alkyl 01-2119473798-17-xxxx Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Skin Corr. 1B H314 / STOT SE 3 H335 / STOT RE 2 H373 / Aquatic Acute 1 H400 (M = 10,00) / Aquatic Chronic 1 H410 (M = 10,00) ATE (oral): 1,300 mg/kg	0,100 <= 0,50
109-55-7 203-680-9 612-061-00-6	3-aminopropyldimethylamine 01-2119486842-27-xxxx Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 ATE (dermal): 2,139 mg/kg ATE (oral): 1,600 mg/kg	0,100 <= 0,50
69-72-7 200-712-3 607-732-00-5	salicylic acid 01-2119486984-17-xxxx Acute Tox. 4 H302 / Eye Dam. 1 H318 / Repr. 2 H361d ATE (oral): 891 mg/kg ATE (dermal): > 2,000 mg/kg	0,100 <= 0,50

#### Remark

Full text of H- and EUH-statements: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Self-protection of the first aider

Page 3/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

First aider: Pay attention to self-protection!

#### 4.2 Most important symptoms and effects, both acute and delayed

#### **Symptoms**

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

#### Unsuitable extinguishing media

Strong water jet

#### 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

Clean using cleansing agents. Do not use solvents.

#### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray.

Personal protection equipment: see section 8

Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

#### Hints on joint storage

Page 4/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH)





WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Do not store together with: Food and feedingstuffs

LGK8A - Combustible corrosive substances Storage class

#### Further information on storage conditions

Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C.

#### Specific end use(s)

Observe technical data sheet.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
1477-55-0	m-phenylenebis(methylamine)	-	0.1 / - ( - ) mg/m <sup>3</sup>

#### **Additional information**

Long-term: Long-term occupational exposure limit value short-term: short-term occupational exposure limit value

#### **Biological limit values**

No data available

#### **DNEL** worker

CAS No.	Substance name	DNEL type	DNEL value
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL long-term inhalative (local)	0.009 mg/m³
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL long-term dermal (systemic)	0.1 mg/kg bw/day
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL acute dermal, short-term (systemic)	25.2 mg/kg bw/day
109-55-7	3-aminopropyldimethylamine	DNEL acute inhalative (systemic)	9.8 mg/m³
109-55-7	3-aminopropyldimethylamine	DNEL long-term inhalative (local)	4.9 mg/m³
109-55-7	3-aminopropyldimethylamine	DNEL long-term inhalative (systemic)	4.9 mg/m³
109-55-7	3-aminopropyldimethylamine	DNEL acute inhalative (local)	9.8 mg/m³
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	DNEL acute inhalative (systemic)	0.54 mg/m³
38640-62-9	Bis(isopropyl)naphthalene	DNEL long-term dermal (systemic)	4.3 mg/kg bw/day
38640-62-9	Bis(isopropyl)naphthalene	DNEL long-term inhalative (systemic)	30 mg/m³
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	DNEL long-term inhalative (systemic)	3.9 mg/m³
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	DNEL long-term dermal (systemic)	1.1 mg/kg
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	DNEL long-term dermal (systemic)	2.87 mg/kg bw/day
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	DNEL long-term inhalative (systemic)	1.21 mg/m³
100-51-6	benzyl alcohol	DNEL acute dermal, short-term (systemic)	47 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL long-term dermal (systemic)	9.5 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL acute inhalative	450 mg/m³

Page 5/14 IE (en\_GB)

# Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

		(systemic)	
100-51-6	benzyl alcohol	DNEL long-term inhalative (systemic)	90 mg/m³
1477-55-0	m-phenylenebis(methylamine)	DNEL long-term inhalative (local)	0.2 mg/m³
1477-55-0	m-phenylenebis(methylamine)	DNEL long-term inhalative (systemic)	1.2 mg/m³
1477-55-0	m-phenylenebis(methylamine)	DNEL long-term dermal (systemic)	0.33 mg/kg
69-72-7	salicylic acid	DNEL long-term dermal (systemic)	2.3 mg/kg bw/day
69-72-7	salicylic acid	DNEL long-term inhalative (local)	5 mg/m³

#### **DNEL Consumer**

CAS No.	Substance name	DNEL type	DNEL value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL long-term oral (repeated)	0.526 mg/kg

#### **PNEC**

CAS No.	Substance name	PNEC type	PNEC Value
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, intermittent release	0.331 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC sewage treatment plant (STP)	10 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, marine water	0.033 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, freshwater	0.033 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC aquatic, intermittent release	0.295 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC aquatic, marine water	0.003 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC aquatic, freshwater	0.029 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC sewage treatment plant (STP)	72 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC sediment, marine water	0.018 mg/kg
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC sediment, freshwater	0.18 mg/kg
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC soil, freshwater	0.019 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, intermittent release	0.23 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sewage treatment plant (STP)	3.18 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, marine water	0.006 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, freshwater	0.06 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sediment, marine water	0.578 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sediment, freshwater	5.784 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC soil, freshwater	1.121 mg/kg
109-55-7	3-aminopropyldimethylamine	PNEC aquatic, intermittent release	0.535 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC sewage treatment plant (STP)	69.5 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC aquatic, marine water	0.053 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC aquatic, freshwater	0.053 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC sediment, marine water	0.059 mg/kg
109-55-7	3-aminopropyldimethylamine	PNEC sediment, freshwater	0.585 mg/kg
109-55-7	3-aminopropyldimethylamine	PNEC soil, freshwater	0.085 mg/kg
38640-62-9	Bis(isopropyl)naphthalene	PNEC Secondary Poisoning	25 mg/kg dw
38640-62-9	Bis(isopropyl)naphthalene	PNEC aquatic, marine water	0.024 μg/L

Page 6/14 IE (en\_GB)

# Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

on 1.0	Revision date 1 Jul 2025		Print date 2 Jul 2
38640-62-9	Bis(isopropyl)naphthalene	PNEC aquatic, freshwater	0.236 μg/L
38640-62-9	Bis(isopropyl)naphthalene	PNEC sewage treatment plant (STP)	0.15 mg/L
38640-62-9	Bis(isopropyl)naphthalene	PNEC sediment, marine water	0.085 mg/kg
38640-62-9	Bis(isopropyl)naphthalene	PNEC sediment, freshwater	0.853 mg/kg dw
38640-62-9	Bis(isopropyl)naphthalene	PNEC soil, freshwater	0.171 mg/kg dw
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC aquatic, marine water	0 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC aquatic, freshwater	0.004 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC aquatic, intermittent release	0.043 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC sewage treatment plant (STP)	3.84 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC sediment, marine water	43.4 mg/kg
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC sediment, freshwater	434.02 mg/kg
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC aquatic, freshwater	0.011 mg/L
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC aquatic, intermittent release	0.013 mg/L
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC aquatic, marine water	0.001 mg/L
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC sewage treatment plant (STP)	10 mg/L
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC sediment, freshwater	1.564 mg/kg sediment dw
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC sediment, marine water	0.156 mg/kg sediment dw
-	Reaction mass of (1-phenylethyl)phenols and bis- (1-phenylethyl)phenols	PNEC soil	0.305 mg/kg soil dw
100-51-6	benzyl alcohol	PNEC aquatic, intermittent release	2.3 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, marine water	0.1 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, freshwater	1 mg/L
100-51-6	benzyl alcohol	PNEC sewage treatment plant (STP)	39 mg/L
100-51-6	benzyl alcohol	PNEC sediment, marine water	0.527 mg/kg
100-51-6	benzyl alcohol	PNEC sediment, freshwater	5.27 mg/kg
100-51-6	benzyl alcohol	PNEC soil, freshwater	0.456 mg/kg
1477-55-0	m-phenylenebis(methylamine)	PNEC aquatic, intermittent release	0.152 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC aquatic, marine water	0.009 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC aquatic, freshwater	0.094 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC sewage treatment plant (STP)	10 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC sediment, marine water	0.043 mg/kg
1477-55-0	m-phenylenebis(methylamine)	PNEC sediment, freshwater	0.43 mg/kg
1477-55-0	m-phenylenebis(methylamine)	PNEC soil, freshwater	0.045 mg/kg

Page 7/14 IE (en\_GB)

#### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



0.142 mg/kg

1.42 mg/kg

0.166 mg/kg

Print date 2 Jul 2025

WEBAC 4170 Komp. B

Version 1.0 69-72-7 salicylic acid PNEC aquatic, marine water 0.02 mg/L 69-72-7 salicylic acid PNEC aquatic, freshwater 0.2 mg/L 69-72-7 salicylic acid PNEC aquatic, intermittent 1 mg/L release 69-72-7 salicylic acid PNEC sewage treatment plant 162 ma/L (STP)

PNEC sediment, marine water

PNEC sediment, freshwater

PNEC soil, freshwater

#### 8.2 Exposure controls

69-72-7

69-72-7

69-72-7

Provide good ventilation. This can be achieved with local or room suction.

Revision date 1 Jul 2025

#### Personal protection equipment

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

salicylic acid

salicylic acid

salicylic acid

#### Hand protection

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

#### Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Liquid

vellow

#### Eye/face protection

Eve glasses with side protection: EN 166

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Physical state

Colour

Wear suitable protective clothing. Change contaminated, saturated clothing.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Odour characteristic pН not applicable Melting point/freezing point not determined Initial boiling point and boiling range not determined Flash point > 101 °C flammability not applicable Lower explosion limit at 20°C not determined Upper explosion limit at 20°C not determined 2,429 mbar Vapour pressure at 20°C Relative vapour density not applicable Density at 20 °C 1.0 kg/l

partially soluble Water solubility at 20°C Partition coefficient: n-octanol/water see section 12 Ignition temperature in °C not determined Decomposition temperature not determined Viscosity at 40 °C: 22 mm<sup>2</sup>/s

Page 8/14 IE (en\_GB)

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

particle characteristics

not applicable

#### 9.2 Other information

not applicable

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions.

Please note the expiry date.

#### 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

#### 10.5 Incompatible materials

No further relevant information available.

#### 10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Harmful if swallowed.

ATEmix: (oral) 1,735.802 mg/kg

#### 1,3-Cyclohexanedimethanamine

LD50: dermal (Rabbit): 1,700 mg/kg

LD50: oral (Rat): 700 mg/kg

#### 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

LD50: oral (Rat): 910 mg/kg

#### 3,6-dioxaoctamethylenediamine

LD50: dermal (Rabbit): > 8,000 mg/kg

LD50: oral (Rat): 1,600 mg/kg

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine

LD50: dermal (Rabbit): 1,840 mg/kg

LD50: oral (Rat): 1,030 mg/kg

#### 3-aminopropyldimethylamine

LD50: dermal (Rabbit): 2,139 mg/kg

LD50: oral (Rat): 1,600 mg/kg

#### Amines, polyethylenepoly-, triethylenetetramine fraction

LD50: dermal (Rabbit): 1,465 mg/kg

LD50: oral (Rat): 1,716 mg/kg

#### Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

LD50: dermal (Rat): > 2,000 mg/kg

LD50: oral (Rat): > 2,000 mg/kg

#### Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols

LD50: oral (Rat): > 2,000 mg/kg

LD50: dermal (Rat): > 2,000 mg/kg

amines, coco alkyl

LD50: oral (Rat): 1,300 mg/kg

Page 9/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

#### benzyl alcohol

LD50: dermal (Rabbit): > 2,000 mg/kg

LD50: oral (Rat): 1,620 mg/kg

LC50: inhalative (Rat): 1.5 mg/L (4 h)

#### m-phenylenebis(methylamine)

LD50: dermal (Rabbit): > 3,100 mg/kg

LD50: oral (Rat): 930 mg/kg

salicylic acid

LD50: oral (Rat): 891 mg/kg

LD50: dermal (Rat): > 2,000 mg/kg

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

May cause an allergic skin reaction.

#### Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

#### Acute (short-term) fish toxicity Bis(isopropyl)naphthalene

LC0: 0.5 mg/L (96 h)

#### Acute (short-term) toxicity to algae and cyanobacteria

EC0 0.15 mg/L (72 h)

#### Acute (short-term) toxicity to crustacea

EC0 0.16 mg/L (48 h)

#### Algae toxicity

#### 1,3-Cyclohexanedimethanamine

ErC50: (Pseudokirchneriella subcapitata): > 100 mg/L (72 h)

Method: OECD 201

#### 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

ErC50: (Scenedesmus subspicatus): = 43.5 mg/L (72 h)

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine

ErC50: (Scenedesmus subspicatus): > 50 mg/L (72 h)

#### 3-aminopropyldimethylamine

EC50 = 56.2 mg/L (72 h)

#### Amines, polyethylenepoly-, triethylenetetramine fraction

EC50 (Scenedesmus subspicatus): 3.7 mg/L (48 h)

ErC50: (Pseudokirchneriella subcapitata): 20 mg/L (72 h)

Page 10/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

#### Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols

EL50: (Scenedesmus subspicatus): 3.14 mg/L (72 h)

#### amines, coco alkyl

ErC50: (Selenastrum capricornutum): = 0.17 mg/L (72 h)

#### benzyl alcohol

ErC50: (Pseudokirchneriella subcapitata): 770 mg/L (72 h) NOEC (Pseudokirchneriella subcapitata): 310 mg/L (72 h)

#### m-phenylenebis(methylamine)

ErC50: (Scenedesmus subspicatus): 12 mg/L (72 h) ErC50: (Scenedesmus subspicatus): 12 mg/L (72 h)

#### Daphnia toxicity

#### 1,3-Cyclohexanedimethanamine

EC50 (Daphnia magna (Big water flea)): 65.4 mg/L (48 h)

Method: OECD 202

#### 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

EC50 = 31.5 (24 h)

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC50 (Daphnia magna (Big water flea)): 23 mg/L (48 h)

Method: OECD 202 EC50 3 mg/L (504 h) Method: OECD 202

#### 3-aminopropyldimethylamine

EC50 = 59.5 mg/L (48 h)

EC50 (Daphnia magna (Big water flea)): = 44.5 mg/L (24 h)

#### Amines, polyethylenepoly-, triethylenetetramine fraction

EC50 (Daphnia magna (Big water flea)): 31.1 mg/L (48 h)

#### Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols

EC50 (Daphnia magna (Big water flea)): 4.6 mg/L (48 h)

#### amines, coco alkyl

EC50 (Daphnia magna (Big water flea)): = 0.045 mg/L (48 h)

#### benzyl alcohol

EC50 (Daphnia magna (Big water flea)): 230 mg/L (48 h)

#### m-phenylenebis(methylamine)

EC50 (Daphnia magna (Big water flea)): 15.2 mg/L (48 h)

#### salicylic acid

EC50 870 mg/L (48 h)

#### Fish toxicity

#### 1,3-Cyclohexanedimethanamine

LC50: (Leuciscus idus (golden orfe)): 130 mg/L (96 h)

Method: OECD 203

#### 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

EC50 (Pseudomonas putida): = 89 (17 h)

LC50: (Leuciscus idus (golden orfe)): = 174 (48 h)

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC10: (Pseudomonas putida): 1,120 mg/L (18 h)

Method: literature value

LC50: (Danio rerio (zebrafish)): 110 mg/L (96 h)

#### 3-aminopropyldimethylamine

EC50 > 1,000 mg/L

EC50 (Pseudomonas putida): = 95 mg/L (17 h)

LC50: (Leuciscus idus (golden orfe)): = 122 mg/L (96 h)

#### Amines, polyethylenepoly-, triethylenetetramine fraction

LC50: (Pimephales promelas (fathead minnow)): 330 mg/L (96 h)

Page 11/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine LC50: = 7.07 mg/L (96 h)

Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols

LL50: 14.8 mg/L (96 h)

benzyl alcohol

LC50: 460 mg/L (96 h)

m-phenylenebis(methylamine)

LC50: (Oncorhynchus mykiss (Rainbow trout)): > 100 mg/L (96 h)

LC50: (Danio rerio (zebrafish)): > 100 mg/L (96 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

1,3-Cyclohexanedimethanamine

Partition coefficient: n-octanol/water = 0.73

Method: OECD 107

Bis(isopropyl)naphthalene

Bioconcentration factor (BCF) = 500

Partition coefficient: n-octanol/water = -2.08 (Amines, polyethylenepoly-, triethylenetetramine fraction)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### Waste codes/waste designations according to EWC/AVV

080409\* - Waste adhesives and sealants containing organic solvents or other dangerous substances Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

UN 2735

#### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

AMINE, FLÜSSIG, ÄTZEND, N.A.G (enthält TRIETHYLENTETRAMIN, TRIETHYLENEGLYCOL DIAMINE)

#### Sea transport (IMDG)

Amines, liquid, corrosive, n.o.s. (contains TRIETHYLENETETRAMINE, TRIETHYLENEGLYCOL DIAMINE, BIS(ISOPROPYL)NAPHTHALENE)

#### Air transport (ICAO-TI / IATA-DGR)

Amines, liquid, corrosive, n.o.s. (contains TRIETHYLENETETRAMINE, TRIETHYLENEGLYCOL DIAMINE)

#### 14.3 Transport hazard class(es)

Page 12/14 IE (en\_GB)

### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0 Revision date 1 Jul 2025 Print date 2 Jul 2025

Land transport (ADR/RID) 8
Sea transport (IMDG) 8
Air transport (ICAO-TI / IATA-DGR) 8

14.4 Packing group

Land transport (ADR/RID) II
Sea transport (IMDG) II
Air transport (ICAO-TI / IATA-DGR) II

14.5 Environmental hazards

Land transport (ADR/RID) ENVIRONMENTALLY HAZARDOUS
Sea transport (IMDG) Marine pollutant / Bis(isopropyl)naphthalene

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

#### 14.8 Additional information

#### Land transport (ADR/RID)

Tunnel restriction code: E Limited quantity (LQ): 1 ltr

Hazard identification number (Kemler No.): 80

#### Sea transport (IMDG)

Segregation group: IMDG-Code segregation group 18 - Alkalis

EmS-No.: F-A, S-B Limited quantity (LQ): 1 ltr

#### Air transport (ICAO-TI / IATA-DGR)

not applicable

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

#### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 31 g/l

### Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

#### Hazard categories / Named dangerous substances

E1 Hazardous to the aquatic environment in Category Acute 1 or Chronic 1

Quantity 1: 100t; Quantity 2: 200t

#### National regulations

Observe in addition any national regulations!

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226 Flammable liquid and vapour. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

Page 13/14 IE (en\_GB)

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4170 Komp. B

Version 1.0	Revision date 1 Jul 2025 Print date 2 Jul	ul 2025
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H361d	Suspected of damaging the unborn child.	
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause t hazard).	:he
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH071	Corrosive to the respiratory tract.	

#### Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 oral
Skin Corr. 1A
Skin Sens. 1
Eye Dam. 1
Aquatic Chronic 1
Calculation method.
Calculation method.
Calculation method.
Calculation method.

#### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

**DNEL: Derived No-Effect Level** 

EAKV: European Waste Catalogue Directive

EC: Effective Concentration EC: European Community EN: European Standard

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

MAK:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

**UN: United Nations** 

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

#### Indication of changes

\* Data changed compared with the previous version.

Page 14/14 IE (en\_GB)