

WEBAC 4170T Comp. A Version 1.0

Revision date 15-May-2023

Print date 16-May-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

WEBAC 4170T Comp. A Epoxy Injection Resin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

epoxy resin component

1.3 Details of the supplier of the safety data sheet

supplier

WEBAC-Chemie GmbHFahrenberg 22Telephone: +49 40 67057022885 BarsbüttelTelefax: +49 40 6703227DeutschlandTelefax: +49 40 6703227

Department responsible for information

E-mail (competent person)

msds@webac.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40 available 24h/365days; Information will be provided in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation. Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation. Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction. Aquatic Chronic 2; Hazardous to the aquatic environment; H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS07 GHS09

Signal word

Warning

Hazard statements

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

•	
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P391	Collect spillage.

Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane Hydrocarbons, C9-unsaturated, polymerized



WEBAC 4170T Comp. A Version 1.0

Revision date 15-May-2023

Print date 16-May-2023

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Supplemental hazard information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

epoxy resin component

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
933999-84-9 618-939-5 -	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) 01-2119463471-41-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Aquatic Chronic 3 H412 ATE (oral): = 2.190 mg/kg	25,0 < 50,0
1675-54-3 216-823-5 -	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 01-2119456619-26-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Aquatic Chronic 2 H411 Specific concentration limit (SCL) Eye Irrit. 2 H319: >= 5,00 / Skin Irrit. 2 H315: >= 5,00 ATE (dermal): = 23.000 mg/kg ATE (oral): = 15.000 mg/kg	25,0 < 50,0
- 701-263-0 -	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane 01-2119454392-40-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411 ATE (oral): > 5.000 mg/kg ATE (dermal): > 2.000 mg/kg	10,0 < 25,0
71302-83-5 701-299-7 -	Hydrocarbons, C9-unsaturated, polymerized 01-2119555292-40-xxxx Asp. Tox. 1 H304 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412	2,50 < 10,0

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider



	3AC 4170T Comp. A ion 1.0 Revisio	n date 15-May-2023	Print date 16-May-202
	First aider: Pay attention to self-protection	on!	
4.2	Most important symptoms and effects	s, both acute and delayed	
	Symptoms		
	In all cases of doubt, or when symptoms	s persist, seek medical advice.	
4.3	Indication of any immediate medical a	attention and special treatment needed	
	First Aid, decontamination, treatment of	symptoms.	
SE	CTION 5: Firefighting measures		
5.1	Extinguishing media		
	Suitable extinguishing media		
	alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)	
	Unsuitable extinguishing media		
	Strong water jet		
5.2			
	•	nhaling hazardous decomposing products can ca	use serious health damage.
5.3	Advice for firefighters		
	Provide a conveniently located respirato allow water used to extinguish fire to ent	ry protective device. Cool closed containers that a ter drains, ground or waterways.	are near the source of the fire. Do not
6.1 6.2 6.3	Personal precautions, protective equi Ventilate affected area. Do not breather Environmental precautions Do not allow to enter into surface water authorities in accordance with local regu Methods and material for containment	vapours. or drains. If the product contaminates lakes, rivers ilations.	s or sewages, inform competent
	For containment		
	disposal in appropriate containers in acc	able absorption agent (e.g. sand, earth, vermiculi cordance with the local regulations (see section 1	
	For cleaning up		
_	Clean using cleansing agents. Do not us	se solvents.	
6.4	Reference to other sections		
	Safe handling: see section 7 Personal protection equipment: refer to Disposal: see section 13	section 8	
SE	CTION 7: Handling and storage		
7.1	Precautions for safe handling		
	Advices on safe handling		
	Avoid contact with skin, eyes and clothe Follow the legal protection and safety re	 Avoid breathing spray. Personal protection equ gulations. 	lipment: see section 8
	Advices on general occupational hy	/giene	
	When using do not eat, drink or smoke.		
7.2	Conditions for safe storage, including	any incompatibilities	
	Requirements for storage rooms ar	nd vessels	
		ce on Industrial Safety and Health (BetrSiVO). Ac	cess only for authorised persons

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers. Do not store together with: Food and feedingstuffs



WEBAC 4170T Comp. A Version 1.0

Revision date 15-May-2023

Print date 16-May-2023

Storage class

LGK10 - Combustible liquids that cannot be assigned to any of the above storage classes

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values No data available Biological limit values No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	DNEL long-term dermal (systemic)	0,75 mg/kg bw/day
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	DNEL long-term inhalative (systemic)	4,93 mg/m³
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term inhalative (systemic)	3,3 mg/m ³
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term dermal (systemic)	4,7 mg/kg
-	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	DNEL long-term dermal (systemic)	104,15 mg/kg bw/ day
-	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	DNEL long-term inhalative (systemic)	29,39 mg/m³
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	DNEL long-term dermal (systemic)	2,8 mg/kg bw/day
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	DNEL long-term inhalative (systemic)	4,9 mg/m³
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	DNEL acute inhalative (systemic)	4,9 mg/m³

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC Secondary Poisoning	11 mg/kg
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC sewage treatment plant (STP)	10 mg/L
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC aquatic, freshwater	0,006 mg/L
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC aquatic, marine water	0,001 mg/L
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC sediment, marine water	0,034 mg/kg
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC sediment, freshwater	0,341 mg/kg
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	PNEC soil, freshwater	0,065 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, freshwater	0,026 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, intermittent release	0,54 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, marine water	0,003 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sewage treatment plant (STP)	0,26 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sediment, marine water	196 mg/kg



WEBAC 4170T Comp. A Version 1.0

71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sediment, freshwater	1.960 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC soil, freshwater	391 mg/kg
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC aquatic, marine water	0 mg/L
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC aquatic, freshwater	0,003 mg/L
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC aquatic, intermittent release	0,025 mg/L
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC sewage treatment plant (STP)	10 mg/L
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC sediment, marine water	0,029 mg/kg
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC sediment, freshwater	0,294 mg/kg
	Reaction mass of 2,2'-[methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy)methyl)oxirane	PNEC soil, freshwater	0,237 mg/kg
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC aquatic, marine water	0,011 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC aquatic, freshwater	0,011 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC aquatic, intermittent release	0,115 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC sewage treatment plant (STP)	1 mg/L
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC sediment, marine water	0,028 mg/kg
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC sediment, freshwater	0,283 mg/kg
933999-84-9	reaction products of hexane-1,6-diol with 2- (chloromethyl)oxirane (1:2)	PNEC soil, freshwater	0,223 mg/kg

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0,4 mm Breakthrough time >= 480 min



WEBAC 4170T Comp. A Version 1.0

Revision date 15-May-2023

Print date 16-May-2023

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing. Change contaminated, saturated clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	colourless
Odour	characteristic
рН	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	> 101 °C
flammability	not applicable
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	0,354 mbar
Relative vapour density	not applicable
Density at 20 °C	1,115 kg/l
Water solubility at 20°C	not determined
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined
Viscosity at 20 °C:	> 20,5 mm²/s
particle characteristics	not applicable

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2 Chemical stability

Stable under recommended storage and handling conditions. Please note the expiry date.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

10.5 Incompatible materials



WEBAC 4170T Comp. A Version 1.0

Revision date 15-May-2023

Print date 16-May-2023

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

LD50: dermal (Rabbit): = 23.000 mg/kg

LD50: oral (Rat): = 15.000 mg/kg

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane LD50: oral (Rat): > 5.000 mg/kg

LD50: dermal (Rat): > 2.000 mg/kg

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

LD50: oral (Rat): = 2.190 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Indications for this are:

Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Algae toxicity 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ErC50: = 11 mg/L (72 h)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane ErC50: = 1,8 mg/L (72 h)



/ers	ion 1.0 Revision date 15-May-2023 Print date 16-May-2023
	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) ErC50: = 23,1 mg/L (48 h)
	Daphnia toxicity 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane EC50 = 1,8 mg/L (48 h)
	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane EC50 = 2,55 mg/L (48 h)
	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) EC50 = 47 mg/L (48 h)
	<i>Fish toxicity</i> 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane LC50: (Oncorhynchus mykiss (Rainbow trout)): = 2 mg/L (96 h)
	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane LC50: = 2,54 mg/L (96 h)
	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) LC50: (Leuciscus idus (golden orfe)): = 30 mg/L (96 h)
2.2	Persistence and degradability
	No information available.
2.3	Bioaccumulative potential
	reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Partition coefficient: n-octanol/water = 0,822 Method: OECD 107
2.4	Mobility in soil
	Hydrocarbons, C9-unsaturated, polymerized = 5,5
2.5	Results of PBT and vPvB assessment
	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
2.6	Endocrine disrupting properties
	This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.
2.7	Other adverse effects
	No information available.
SE	CTION 13: Disposal considerations
3.1	Waste treatment methods
	Product/Packaging disposal
	Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98 EC, covering waste and dangerous waste.
	Waste codes/waste designations according to EWC/AVV
	080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances Hazardous waste according to Directive 2008/98/EC (waste framework directive).
	Other disposal recommendations
	other disposal recommendations

SECTION 14: Transport information

14.1 UN number or ID number

UN 3082

14.2 UN proper shipping name

Land transport (ADR/RID)

UMWELTGEFÄHRDENDER STOFF, FLÜSSIG, N.A.G. (enthält BISPHENOL-A-EPICHLORHYDRINHARZE, BISPHENOL-F-EPICHLORHYDRINHARZE)



WEBAC 4170T Comp. A Version 1.0	Revision date 15-May-2023	Print date 16-May-2023
Sea transport (IMDG)		
Environmentally hazardo EPICHLORHYDRIN RES	us substance, liquid, n.o.s. (contain BISPHENOL-A-EPICH SINS)	LORHYDRIN RESINS, BISPHENOL-F-
Air transport (ICAO-T	/ IATA-DGR)	
— · · · · · ·		

Environmentally hazardous substance, liquid, n.o.s. (contain BISPHENOL-A-EPICHLORHYDRIN RESINS, BISPHENOL-F-EPICHLORHYDRIN RESINS)

14.3 Transport hazard class(es)

Land transport (ADR/RID)	9
Sea transport (IMDG)	9
Air transport (ICAO-TI / IATA-DGR)	9
-	

14.4 Packing group

r doning group	
Land transport (ADR/RID)	
Sea transport (IMDG)	
Air transport (ICAO-TI / IATA-DGR)	

14.5 Environmental hazards

Land transport (ADR/RID) Sea transport (IMDG)

ENVIRONMENTALLY HAZARDOUS Marine pollutant / BISPHENOL-A-EPICHLORHYDRINHARZE

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Tunnel restriction code: -Limited quantity (LQ): 5 ltr Hazard identification number (Kemler No.): 90

Sea transport (IMDG)

EmS-No.: F-A S-F Limited quantity (LQ): 5 ltr

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 0 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200t; Quantity 2: 500t

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Print date 16-May-2023

WEBAC 4170T Comp. A	
Version 1.0	Revision date 15-May-2023

SECTION 16: Other information

List of relevant hazard statements and/or p	recautionary statements from sections 2 to 15

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2	Calculation method.
Skin Irrit. 2	Calculation method.
Skin Sens. 1	Calculation method.
Aquatic Chronic 2	Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road **OEL: Occupational Exposure Limit Value BLV: Biological limit values** CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic DIN: German Institute for Standardization / German industrial standard **DNEL: Derived No-Effect Level** EAKV: European Waste Catalogue Directive EC: Effective Concentration EC: European Community EN: European Standard IATA-DGR: International Air Transport Association - Dangerous Goods Regulations IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization LC: Lethal Concentration LD: Lethal Dose MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OECD: Organisation for Economic Cooperation and Development PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.