according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

WEBAC 4270 Comp. B Special Epoxy Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

hardener/amine component for epoxy resin

1.3 Details of the supplier of the safety data sheet

supplier

WEBAC-Chemie GmbH

Fahrenberg 22 Telephone: +49 40 670570 22885 Barsbüttel Telefax: +49 40 6703227 Deutschland

Department responsible for information

E-mail (competent person) msds@webac.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40

available 24h/365days; Information will be provided in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 oral; Acute toxicity; H302 Harmful if swallowed.

Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage.

Skin Corr. 1A; Skin corrosion/irritation; H314 Causes severe skin burns and eye damage.

Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

Aquatic Chronic 2; Hazardous to the aquatic environment; H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS05 GHS07 Signal word

Danger

Hazard statements

H302 Harmful if swallowed.

GHS09

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

Page 1/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER.

P391 Collect spillage.

Hazard components for labelling

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine 3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-methylenebis(cyclohexylamine)

Amines, polyethylenepoly-, triethylenetetramine fraction

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Hydrocarbons, C9-unsaturated, polymerized

Methyleneoxide, polymer with benzenamine, hydrogenated

3-aminopropyldimethylamine Phenol, methylstyrenated Phenol, styrenated

m-phenylenebis(methylamine)

Supplemental hazard information

not applicable

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

hardener/amine component for epoxy resin

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
25513-64-8 247-063-2 -	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine 01-2119560598-25-xxxx Acute Tox. 4 H302 / Skin Corr. 1A H314 / Skin Sens. 1A H317 ATE (oral): 910 mg/kg	25,0 < 50,0
90640-67-8 292-588-2 -	Amines, polyethylenepoly-, triethylenetetramine fraction 01-2119487919-13-xxxx Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412 ATE (oral): = 5.500 mg/kg ATE (dermal): = 1.465 mg/kg ATE (oral): = 1.600 mg/kg ATE (oral): = 1.716 mg/kg	10,0 < 25,0
2579-20-6 219-941-5 -	1,3-Cyclohexanedimethanamine 01-2119543741-41-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1C H314 / Aquatic Chronic 3 H412 ATE (dermal): = 1.700 mg/kg ATE (oral): = 700 mg/kg	10,0 < 25,0
71302-83-5 701-299-7 -	Hydrocarbons, C9-unsaturated, polymerized 01-2119555292-40-xxxx Asp. Tox. 1 H304 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412	10,0 < 25,0
9046-10-0 618-561-0 -	Poly(oxypropylene)diamine 01-2119557899-12-xxxx Skin Corr. 1C H314 / Aquatic Chronic 3 H412 ATE (dermal): = 2.980 mg/kg ATE (oral): = 2.885 mg/kg	2,50 < 10,0
100-51-6 202-859-9 603-057-00-5	benzyl alcohol 01-2119492630-38-xxxx Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 ATE (dermal): = 2.000 mg/kg ATE (oral): = 1.230 mg/kg ATE (inhalative): > 4,178 mg/L (4 h)	2,50 < 10,0
61788-44-1 262-975-0 -	Phenol, styrenated 01-2119980970-27-xxxx Skin Irrit. 2 H315 / Skin Sens. 1A H317 / Aquatic Chronic 2 H411 ATE (oral): > 2.000 mg/kg ATE (dermal): > 2.000 mg/kg	2,50 < 10,0
135108-88-2 603-894-6	Methyleneoxide, polymer with benzenamine, hydrogenated 01-2119983522-33-xxxx	2,50 < 10,0

Page 2/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

ion 1.0	Revision date 15-May-2023 P	rint date 16-May-202
-	Acute Tox. 4 H302 / Skin Corr. 1C H314 / Skin Sens. 1 H317 / STOT RE 2 H373 / Aquatic Chronic 3 H412 ATE (dermal): > 2.000 mg/kg ATE (oral): = 367 mg/kg	
68082-29-1 500-191-5 -	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 01-2119972320-44-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Aquatic Chronic 2 H411 ATE (dermal): > 2.000 mg/kg ATE (oral): > 2.000 mg/kg	2,50 < 10,0
1477-55-0 216-032-5 -	m-phenylenebis(methylamine) 01-2119480150-50-xxxx Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Acute Tox. 4 H332 / Aquatic Chronic 3 H412 ATE (dermal): > 3.100 mg/kg ATE (oral): = 930 mg/kg	1,00 < 2,50
1761-71-3 217-168-8 -	4,4'-methylenebis(cyclohexylamine) 01-2119541673-38-xxxx Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1B H317 / STOT RE 2 H373 ATE (dermal): = 2.110 mg/kg ATE (oral): = 625 mg/kg	0,50 < 1,00
2855-13-2 220-666-8 612-067-00-9	3-aminomethyl-3,5,5-trimethylcyclohexylamine 01-2119514687-32-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412 Specific concentration limit (SCL) Skin Sens. 1A H317: >= 0,001 ATE (dermal): = 1.840 mg/kg ATE (oral): = 1.030 mg/kg	0,50 < 1,00
109-55-7 203-680-9 612-061-00-6	3-aminopropyldimethylamine 01-2119486842-27-xxxx Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 ATE (dermal): = 2.139 mg/kg ATE (oral): = 1.600 mg/kg	0,50 < 1,00
61788-46-3 262-977-1 612-285-00-4	amines, coco alkyl 01-2119473798-17-xxxx Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Skin Corr. 1B H314 / STOT SE 3 H335 / STOT RE 2 H373 / Aquatic Acute 1 H400 (M = 10,00) / Aquatic Chronic 1 H410 (M = 10,00) ATE (oral): = 1.300 mg/kg	0,50 < 1,00
69-72-7 200-712-3 607-732-00-5	salicylic acid 01-2119486984-17-xxxx Acute Tox. 4 H302 / Eye Dam. 1 H318 / Repr. 2 H361d ATE (oral): = 891 mg/kg ATE (dermal): > 2.000 mg/kg	0,50 < 1,00
68512-30-1 270-966-8 -	Phenol, methylstyrenated 01-2119555274-38-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412 ATE (oral): = 3.600 mg/kg ATE (dermal): > 2.000 mg/kg ATE (oral): > 2.000 mg/kg > 2.000 mg/kg	0,100 < 0,50
38640-62-9 254-052-6 -	Bis(isopropyl)naphthalene 01-2119565150-48-xxxx Asp. Tox. 1 H304 / Aquatic Chronic 1 H410 (M = 1,00)	0,100 < 0,50

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Page 3/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8 Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Page 4/16 IE (en_GB)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023

Print date 16-May-2023

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Do not store together with: Food and feedingstuffs

Storage class

LGK8A - Combustible corrosive substances

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
1477-55-0	m-phenylenebis(methylamine)	-	0,1 / - (-) mg/m³

Additional information

Long-term: Long-term occupational exposure limit value short-term: short-term occupational exposure limit value

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL long-term dermal (systemic)	0,2 mg/kg bw/day
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL long-term inhalative (systemic)	0,71 mg/m³
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL acute inhalative (systemic)	21,2 mg/m³
2579-20-6	1,3-Cyclohexanedimethanamine	DNEL acute dermal, short-term (systemic)	6 mg/kg
109-55-7	3-aminopropyldimethylamine	DNEL acute inhalative (systemic)	9,8 mg/m³
109-55-7	3-aminopropyldimethylamine	DNEL long-term inhalative (local)	4,9 mg/m³
109-55-7	3-aminopropyldimethylamine	DNEL long-term inhalative (systemic)	4,9 mg/m³
109-55-7	3-aminopropyldimethylamine	DNEL acute inhalative (local)	9,8 mg/m³
1761-71-3	4,4'-methylenebis(cyclohexylamine)	DNEL long-term dermal (systemic)	0,1 mg/kg bw/day
1761-71-3	4,4'-methylenebis(cyclohexylamine)	DNEL long-term inhalative (systemic)	1 mg/m³
38640-62-9	Bis(isopropyl)naphthalene	DNEL long-term dermal (systemic)	4,3 mg/kg bw/day
38640-62-9	Bis(isopropyl)naphthalene	DNEL long-term inhalative (systemic)	30 mg/m³
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	DNEL long-term inhalative (systemic)	3,9 mg/m³
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	DNEL long-term dermal (systemic)	1,1 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term inhalative (systemic)	3,3 mg/m³

Page 5/16 IE (en_GB)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Versi	on 1.0	Revision date 15-May-2023		Print date 16-May-2023
-	71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term dermal (systemic)	4,7 mg/kg
-				7

71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	DNEL long-term dermal (systemic)	4,7 mg/kg
68512-30-1	Phenol, methylstyrenated	DNEL long-term dermal (systemic)	16,4 mg/kg bw/day
68512-30-1	Phenol, methylstyrenated	DNEL long-term inhalative (systemic)	57 mg/m³
61788-44-1	Phenol, styrenated	DNEL long-term dermal (systemic)	2,92 mg/kg bw/day
61788-44-1	Phenol, styrenated	DNEL long-term inhalative (systemic)	4,11 mg/m³
9046-10-0	Poly(oxypropylene)diamine	DNEL long-term dermal (local)	62,3 mg/dm ²
9046-10-0	Poly(oxypropylene)diamine	DNEL long-term dermal (systemic)	2,5 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL acute dermal, short-term (systemic)	47 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL long-term dermal (systemic)	9,5 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL acute inhalative (systemic)	450 mg/m³
100-51-6	benzyl alcohol	DNEL long-term inhalative (systemic)	90 mg/m³
1477-55-0	m-phenylenebis(methylamine)	DNEL long-term inhalative (local)	0,2 mg/m³
1477-55-0	m-phenylenebis(methylamine)	DNEL long-term inhalative (systemic)	1,2 mg/m³
1477-55-0	m-phenylenebis(methylamine)	DNEL long-term dermal (systemic)	0,33 mg/kg
69-72-7	salicylic acid	DNEL long-term dermal (systemic)	2 mg/kg bw/day
69-72-7	salicylic acid	DNEL long-term inhalative (systemic)	16 mg/m³

DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL long-term oral (repeated)	0,526 mg/kg

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, intermittent release	0,331 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC sewage treatment plant (STP)	10 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, marine water	0,033 mg/L
2579-20-6	1,3-Cyclohexanedimethanamine	PNEC aquatic, freshwater	0,033 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC aquatic, intermittent release	0,295 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC aquatic, marine water	0,003 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC aquatic, freshwater	0,029 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC sewage treatment plant (STP)	72 mg/L
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC sediment, marine water	0,018 mg/kg
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC sediment, freshwater	0,18 mg/kg
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	PNEC soil, freshwater	0,019 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, intermittent release	0,23 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sewage treatment plant (STP)	3,18 mg/L

Page 6/16 IE (en_GB)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

Print date 16-May-2023

April 2 aminomethyl 2 5 5 trimethylogolophyylomina PNEC agustia marina water 10 006 mg/l

2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, marine water	0,006 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, freshwater	0,06 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sediment, marine water	0,578 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sediment, freshwater	5,784 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC soil, freshwater	1,121 mg/kg
109-55-7	3-aminopropyldimethylamine	PNEC aquatic, intermittent release	0,535 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC sewage treatment plant (STP)	69,5 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC aquatic, marine water	0,053 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC aquatic, freshwater	0,053 mg/L
109-55-7	3-aminopropyldimethylamine	PNEC sediment, marine water	0,059 mg/kg
109-55-7	3-aminopropyldimethylamine	PNEC sediment, freshwater	0,585 mg/kg
109-55-7	3-aminopropyldimethylamine	PNEC soil, freshwater	0,085 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, intermittent release	0,08 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, marine water	0,001 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, freshwater	0,008 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sewage treatment plant (STP)	80 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sediment, marine water	0,039 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sediment, freshwater	0,39 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC soil, freshwater	0,072 mg/kg
38640-62-9	Bis(isopropyl)naphthalene	PNEC Secondary Poisoning	25 mg/kg
38640-62-9	Bis(isopropyl)naphthalene	PNEC aquatic, marine water	0,026 mg/L
38640-62-9	Bis(isopropyl)naphthalene	PNEC aquatic, freshwater	0,26 mg/L
38640-62-9	Bis(isopropyl)naphthalene	PNEC sewage treatment plant (STP)	0,15 mg/L
38640-62-9	Bis(isopropyl)naphthalene	PNEC sediment, marine water	0,094 mg/kg
38640-62-9	Bis(isopropyl)naphthalene	PNEC sediment, freshwater	0,94 mg/kg
38640-62-9	Bis(isopropyl)naphthalene	PNEC soil, freshwater	0,187 mg/kg
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC aquatic, marine water	0 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC aquatic, freshwater	0,004 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC aquatic, intermittent release	0,043 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC sewage treatment plant (STP)	3,84 mg/L
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC sediment, marine water	43,4 mg/kg
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	PNEC sediment, freshwater	434,02 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, freshwater	0,026 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, intermittent release	0,54 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC aquatic, marine water	0,003 mg/L
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sewage treatment plant	0,26 mg/L
		(STP)	<u></u>

Page 7/16 IE (en_GB)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B Ver

71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sediment, marine water	196 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC sediment, freshwater	1.960 mg/kg
71302-83-5	Hydrocarbons, C9-unsaturated, polymerized	PNEC soil, freshwater	391 mg/kg
68512-30-1	Phenol, methylstyrenated	PNEC aquatic, intermittent release	140 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC aquatic, marine water	1,4 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC aquatic, freshwater	14 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC sewage treatment plant (STP)	2,4 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC sediment, marine water	5,3 mg/kg
68512-30-1	Phenol, methylstyrenated	PNEC sediment, freshwater	52,9 mg/kg
68512-30-1	Phenol, methylstyrenated	PNEC soil, freshwater	10,5 mg/kg
61788-44-1	Phenol, styrenated	PNEC aquatic, freshwater	11,5 mg/L
61788-44-1	Phenol, styrenated	PNEC aquatic, marine water	1,15 mg/L
61788-44-1	Phenol, styrenated	PNEC aquatic, intermittent release	13,5 mg/L
61788-44-1	Phenol, styrenated	PNEC sewage treatment plant (STP)	10 mg/L
61788-44-1	Phenol, styrenated	PNEC sediment, marine water	0,156 mg/kg
61788-44-1	Phenol, styrenated	PNEC sediment, freshwater	1,564 mg/kg
61788-44-1	Phenol, styrenated	PNEC soil, freshwater	0,305 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC aquatic, marine water	0,014 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC aquatic, freshwater	0,015 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC aquatic, intermittent release	0,15 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC Secondary Poisoning	6,93 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC sewage treatment plant (STP)	7,5 mg/L
9046-10-0	Poly(oxypropylene)diamine	PNEC sediment, marine water	0,125 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC sediment, freshwater	0,132 mg/kg
9046-10-0	Poly(oxypropylene)diamine	PNEC soil, freshwater	0,018 mg/kg
100-51-6	benzyl alcohol	PNEC aquatic, intermittent release	2,3 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, marine water	0,1 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, freshwater	1 mg/L
100-51-6	benzyl alcohol	PNEC sewage treatment plant (STP)	39 mg/L
100-51-6	benzyl alcohol	PNEC sediment, marine water	0,527 mg/kg
100-51-6	benzyl alcohol	PNEC sediment, freshwater	5,27 mg/kg
100-51-6	benzyl alcohol	PNEC soil, freshwater	0,456 mg/kg
1477-55-0	m-phenylenebis(methylamine)	PNEC aquatic, intermittent release	0,152 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC aquatic, marine water	0,009 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC aquatic, freshwater	0,094 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC sewage treatment plant (STP)	10 mg/L
1477-55-0	m-phenylenebis(methylamine)	PNEC sediment, marine water	0,043 mg/kg
1477-55-0	m-phenylenebis(methylamine)	PNEC sediment, freshwater	0,43 mg/kg
1477-55-0	m-phenylenebis(methylamine)	PNEC soil, freshwater	0,045 mg/kg
69-72-7	salicylic acid	PNEC aquatic, marine water	0,02 mg/L
69-72-7	salicylic acid	PNEC aquatic, freshwater	0,2 mg/L

Page 8/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



Print date 16-May-2023

WEBAC 4270 Comp. B

Version 1.0

release salicylic acid PNEC sewage treatment plant 162 mg/L 69-72-7 (STP) 69-72-7 salicylic acid PNEC sediment, marine water 0,142 mg/kg

69-72-7 salicylic acid PNEC sediment, freshwater 1,42 mg/kg 69-72-7 PNEC soil, freshwater 0,166 mg/kg salicylic acid

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Revision date 15-May-2023

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0,4 mm

Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Liquid

Eye/face protection

Eye glasses with side protection: EN 166

Wear closely fitting protective glasses in case of splashes.

Body protection

Physical state

Wear suitable protective clothing. Change contaminated, saturated clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Colour vellow Odour characteristic Hq not applicable Melting point/freezing point not determined Initial boiling point and boiling range not determined > 101 °C Flash point flammability not applicable Lower explosion limit at 20°C not determined Upper explosion limit at 20°C not determined Vapour pressure at 20°C 0,93 mbar Relative vapour density not applicable Density at 20 °C 0,949 kg/l

Water solubility at 20°C practically insoluble Partition coefficient: n-octanol/water see section 12 Ignition temperature in °C not determined Decomposition temperature not determined Viscosity at 20 °C: $> 20,5 \text{ mm}^2/\text{s}$ not applicable particle characteristics

Page 9/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2 Chemical stability

Stable under recommended storage and handling conditions.

Please note the expiry date.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

ATEmix: (oral) 1.480,32 mg/kg

1,3-Cyclohexanedimethanamine

LD50: dermal (Rabbit): = 1.700 mg/kg

LD50: oral (Rat): = 700 mg/kg

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

LD50: oral (Rat): 910 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine

LD50: dermal (Rabbit): = 1.840 mg/kg

LD50: oral (Rat): = 1.030 mg/kg

3-aminopropyldimethylamine

LD50: dermal (Rabbit): = 2.139 mg/kg

LD50: oral (Rat): = 1.600 mg/kg

4,4'-methylenebis(cyclohexylamine)

LD50: dermal (Rabbit): = 2.110 mg/kg

LD50: oral (Rat): = 625 mg/kg

Amines, polyethylenepoly-, triethylenetetramine fraction

LD50: oral (Rabbit): = 5.500 mg/kg

LD50: dermal (Rabbit): = 1.465 mg/kg

LD50: oral (Mouse): = 1.600 mg/kg

LD50: oral (Rat): = 1.716 mg/kg

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

LD50: dermal (Rat): > 2.000 mg/kg

LD50: oral (Rat): > 2.000 mg/kg

Methyleneoxide, polymer with benzenamine, hydrogenated

LD50: dermal (Rabbit): > 2.000 mg/kg

LD50: oral (Rat): = 367 mg/kg

Page 10/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

Phenol, methylstyrenated

LD50: oral (Rabbit): = 3.600 mg/kg

LD50: dermal (Rabbit): > 2.000 mg/kg

LD50: oral (Rat): > 2.000 mg/kg

LD50: dermal (Rat): > 2.000 mg/kg

Phenol, styrenated

LD50: oral (Rat): > 2.000 mg/kg LD50: dermal (Rat): > 2.000 mg/kg

Poly(oxypropylene)diamine

LD50: dermal (Rabbit): = 2.980 mg/kg

LD50: oral (Rat): = 2.885 mg/kg

amines, coco alkyl

LD50: oral (Rat): = 1.300 mg/kg

benzyl alcohol

LD50: dermal (Rabbit): = 2.000 mg/kg

LD50: oral (Rat): = 1.230 mg/kg

LC50: inhalative (Rat): > 4,178 mg/L (4 h)

m-phenylenebis(methylamine)

LD50: dermal (Rabbit): > 3.100 mg/kg

LD50: oral (Rat): = 930 mg/kg

salicylic acid

LD50: oral (Rat): = 891 mg/kg

LD50: dermal (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Indications for this are:

Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Algae toxicity

Page 11/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

1,3-Cyclohexanedimethanamine

ErC50: (Pseudokirchneriella subcapitata): > 100 mg/L (72 h)

Method: OECD 201

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

ErC50: (Scenedesmus subspicatus): = 43,5 mg/L (72 h)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

ErC50: (Scenedesmus subspicatus): > 50 mg/L (72 h)

3-aminopropyldimethylamine

EC50 = 56.2 mg/L (72 h)

Amines, polyethylenepoly-, triethylenetetramine fraction

EC50 (Scenedesmus subspicatus): = 2,5 (16 h)

ErC50: (Selenastrum capricornutum): = 20 mg/L (72 h)

Phenol, methylstyrenated

ErC50: (Scenedesmus subspicatus): = 15 mg/L (72 h)

Phenol, styrenated

ErC50: (Scenedesmus subspicatus): = 3,14 mg/L (72 h)

Poly(oxypropylene)diamine

ErC50: (Pseudokirchneriella subcapitata): = 15 mg/L (72 h)

amines, coco alkyl

ErC50: (Selenastrum capricornutum): = 0,17 mg/L (72 h)

benzyl alcohol

ErC50: (Pseudokirchneriella subcapitata): = 770 mg/L (72 h)

NOEC (Pseudokirchneriella subcapitata): = 310 mg/L (72 h)

m-phenylenebis(methylamine)

ErC50: (Scenedesmus subspicatus): = 12 mg/L (72 h)

ErC50: (Scenedesmus subspicatus): = 12 mg/L (72 h)

Daphnia toxicity

1,3-Cyclohexanedimethanamine

EC50 (Daphnia magna (Big water flea)): = 65,4 mg/L (48 h)

Method: OECD 202

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

EC50 = 31,5 (24 h)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC50 (Daphnia magna (Big water flea)): = 23 mg/L (48 h)

Method: OECD 202

EC50 = 3 mg/L (504 h)

Method: OECD 202

3-aminopropyldimethylamine

EC50 = 59.5 mg/L (48 h)

EC50 (Daphnia magna (Big water flea)): = 44,5 mg/L (24 h)

Amines, polyethylenepoly-, triethylenetetramine fraction

EC50 (Daphnia magna (Big water flea)): = 31 mg/L (48 h)

Poly(oxypropylene)diamine

EC50 (Daphnia magna (Big water flea)): = 80 mg/L (48 h)

amines, coco alkyl

EC50 (Daphnia magna (Big water flea)): = 0,045 mg/L (48 h)

benzyl alcohol

EC50 (Daphnia magna (Big water flea)): = 230 mg/L (48 h)

m-phenylenebis(methylamine)

EC50 (Daphnia magna (Big water flea)): = 15,2 mg/L (48 h)

salicylic acid

EC50 = 870 mg/L (48 h)

Fish toxicity

Page 12/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

1,3-Cyclohexanedimethanamine

LC50: (Leuciscus idus (golden orfe)): = 130 mg/L (96 h)

Method: OECD 203

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

EC50 (Pseudomonas putida): = 89 (17 h)

LC50: (Leuciscus idus (golden orfe)): = 174 (48 h)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC10: (Pseudomonas putida): = 1.120 mg/L (18 h)

Method: literature value

LC50: (Danio rerio (zebrafish)): = 110 mg/L (96 h)

3-aminopropyldimethylamine

EC50 > 1.000 mg/L

EC50 (Pseudomonas putida): = 95 mg/L (17 h)

LC50: (Leuciscus idus (golden orfe)): = 122 mg/L (96 h)

Amines, polyethylenepoly-, triethylenetetramine fraction

= 0,003 mg/L

= 0.135 mg/L

= 800 mg/L

EC50 (Pseudomonas putida): = 137 mg/L

LC50: = 330 mg/L (96 h)

LC50: (Poecilia reticulata (Guppy)): = 570 (96 h)

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

LC50: = 7,07 mg/L (96 h)

Phenol, methylstyrenated

LC50: = 25.8 mg/L (96 h)

Phenol, styrenated

LC50: = 14.8 mg/L (96 h)

Poly(oxypropylene)diamine

NOEC (Oncorhynchus mykiss (Rainbow trout)): = 15 mg/L (96 h)

LC50: (Leuciscus idus (golden orfe)): > 15 mg/L (96 h)

benzyl alcohol

LC50: = 460 mg/L (96 h)

m-phenylenebis(methylamine)

LC50: (Oncorhynchus mykiss (Rainbow trout)): > 100 mg/L (96 h)

LC50: (Danio rerio (zebrafish)): > 100 mg/L (96 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

1,3-Cyclohexanedimethanamine

Partition coefficient: n-octanol/water = 0,73

Method: OECD 107

Bis(isopropyl)naphthalene

Partition coefficient: n-octanol/water = 4

12.4 Mobility in soil

Hydrocarbons, C9-unsaturated, polymerized

=5,5

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

Page 13/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

UN 2735

14.2 UN proper shipping name

Land transport (ADR/RID)

AMINE, FLÜSSIG, ÄTZEND, N.A.G (enthält TRIETHYLENTETRAMIN, 1,3-CYCLOHEXANDIMETHANAMIN)

Sea transport (IMDG)

Amines, liquid, corrosive, n.o.s. (contain TRIETHYLENETETRAMINE, 1,3-CYCLOHEXANEDIMETHANAMINE, AMINES OR POLYAMINES, LIQUID, CORROSIVE)

Air transport (ICAO-TI / IATA-DGR)

Amines, liquid, corrosive, n.o.s. (contain TRIETHYLENETETRAMINE, 1,3-CYCLOHEXANEDIMETHANAMINE)

14.3 Transport hazard class(es)

Land transport (ADR/RID) 8
Sea transport (IMDG) 8
Air transport (ICAO-TI / IATA-DGR) 8

14.4 Packing group

Land transport (ADR/RID) II
Sea transport (IMDG) II
Air transport (ICAO-TI / IATA-DGR) II

14.5 Environmental hazards

Land transport (ADR/RID) ENVIRONMENTALLY HAZARDOUS

Sea transport (IMDG) Marine pollutant / AMINE ODER POLYAMINE, FLÜSSIG, ÄTZEND

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Tunnel restriction code: E Limited quantity (LQ): 1 ltr

Hazard identification number (Kemler No.): 80

Sea transport (IMDG)

Segregation group: IMDG-Code segregation group 18 - Alkalis

EmS-No.: F-A, S-B Limited quantity (LQ): 1 ltr


Air transport (ICAO-TI / IATA-DGR)

not applicable


Page 14/16 IE (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878







15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 43 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200t; Quantity 2: 500t

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated

exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause

the hazard).

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 oral
Eye Dam. 1
Skin Corr. 1A
Skin Sens. 1
Aquatic Chronic 2
Calculation method.
Calculation method.
Calculation method.
Calculation method.
Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration EC: European Community

Page 15/16 IE (en_GB)



according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



WEBAC 4270 Comp. B

Version 1.0 Revision date 15-May-2023 Print date 16-May-2023

EN: European Standard

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

ᄓ

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.

Page 16/16 IE (en_GB)