

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

**WEBAC®**

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 1 / 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name/designation WEBAC 4430 Comp. A, RAL 7030  
Epoxy Floor Coating

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

epoxy resin component  
Restricted to professional users.

**1.3. Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

WEBAC-Chemie GmbH

Fahrenberg 22  
22885 Barsbüttel / Hamburg  
GERMANY

Telephone: +49 40 67057-0

Telefax: +49 40 6703227

**Department responsible for information:**

laboratory

E-mail

sdb@webac.de

**1.4. Emergency telephone number**

Giftinformationszentrum-Nord +49 551 19240

24 hr. emergency phone number

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Aquatic Chronic 2 / H411

Hazardous to the aquatic environment

Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Warning**

**Hazard statements**

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H317

May cause an allergic skin reaction.

H411

Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P260

Do not breathe vapour.

P273

Avoid release to the environment.

P280

Wear protective gloves and eye/face protection.

P391

Collect spillage.

**Hazard components for labelling**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and

2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

Alcohols C13-15 (branched and linear, odd numbered), reaction product with

1-chloro-2,3-epoxypropane

**Supplemental hazard information**

EUH205

Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards**

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 2 / 9

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

**Description** epoxy resin component

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
216-823-5 1675-54-3	01-2119456619-26-xxxx 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411 Specific concentration limit (SCL): Skin Irrit. 2 H315 >= 5 / Eye Irrit. 2 H319 >= 5	25 - 50
701-263-0	01-2119454392-40-xxxx Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	10 - 25
701-328-3	01-2119962192-39-xxxx Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane Skin Sens. 1 H317 / Aquatic Chronic 2 H411	2,5 - 10

#### Additional information

Full text of classification: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

##### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

##### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

##### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

##### Unsuitable extinguishing media

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 3 / 9

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Follow the legal protection and safety regulations. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel!

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

**Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limit values:**

not applicable

**DNEL:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC No. 216-823-5 / CAS No. 1675-54-3

DNEL long-term dermal (systemic), Workers: 0,75 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 4,93 mg/m<sup>3</sup>

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

EC No. 701-263-0

DNEL long-term dermal (systemic), Workers: 104,15 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 29,39 mg/m<sup>3</sup>

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane

EC No. 701-328-3

DNEL long-term dermal (systemic), Workers: 4 mg/kg

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 4 / 9

**PNEC:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC No. 216-823-5 / CAS No. 1675-54-3

PNEC aquatic, freshwater: 0,006 mg/L

PNEC aquatic, marine water: 0,001 mg/L

PNEC sediment, freshwater: 0,341 mg/kg

PNEC sediment, marine water: 0,034 mg/kg

PNEC, soil: 0,065 mg/kg

PNEC sewage treatment plant (STP): 10 mg/L

PNEC Secondary Poisoning: 11 mg/kg

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

EC No. 701-263-0

PNEC aquatic, freshwater: 0,003 mg/L

PNEC aquatic, marine water: 0,0003 mg/L

PNEC aquatic, intermittent release: 0,025 mg/L

PNEC sediment, freshwater: 0,294 mg/kg

PNEC sediment, marine water: 0,0294 mg/kg

PNEC, soil: 0,237 mg/kg

PNEC sewage treatment plant (STP): 10 mg/L

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane

EC No. 701-328-3

PNEC aquatic, freshwater: 0,007 mg/L

PNEC aquatic, marine water: 0,001 mg/L

PNEC aquatic, intermittent release: 0,072 mg/L

PNEC sediment, freshwater: 6,677 mg/kg

PNEC sediment, marine water: 0,677 mg/kg

PNEC, soil: 8,012 mg/kg

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Personal protection equipment**

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number.

Suitable respiratory protection apparatus: Usually no personal respirative protection necessary.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear eye glasses with side protection according to EN 166. Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear suitable protective clothing. Wear work clothes with long sleeves. Remove contaminated, saturated clothing immediately.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Physical state:**

**Liquid**

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 5 / 9

<b>Colour:</b>	<b>grey</b>
<b>Odour:</b>	<b>poor</b>
<b>Odour threshold:</b>	<b>not determined</b>
<b>Melting point/freezing point:</b>	<b>not determined</b>
<b>Initial boiling point and boiling range:</b>	<b>not determined</b>
<b>Flammability</b>	<b>not applicable</b>
<b>Lower and upper explosion limit:</b>	
<b>Lower explosion limit:</b>	<b>not determined</b>
<b>Upper explosion limit:</b>	<b>not determined</b>
<b>Flash point:</b>	<b>&gt; 101 °C</b> Method: DIN 53213
<b>Auto-ignition temperature:</b>	<b>not determined</b>
<b>Decomposition temperature:</b>	<b>not applicable</b>
<b>pH at 20 °C:</b>	<b>not applicable</b>
<b>Cinematic viscosity (40°C):</b>	<b>&gt; 20,5 mm²/s</b>
<b>Solubility(ies):</b>	
<b>Water solubility at 20 °C:</b>	<b>insoluble</b>
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>
<b>Vapour pressure at 20 °C:</b>	<b>0,2072 mbar</b>
<b>Density and/or relative density:</b>	
<b>Density at 20 °C:</b>	<b>1,67 g/cm³</b> Method: calculated
<b>Relative vapour density:</b>	<b>not applicable</b>
<b>particle characteristics:</b>	<b>not applicable</b>

9.2. **Other information**

**solvent content:**  
**Organic solvents:** **0 weight-%**

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No further relevant information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

10.4. **Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

No further relevant information available.

10.6. **Hazardous decomposition products**

No further relevant information available.

**SECTION 11: Toxicological information**

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane  
oral, LD50, Rat: 15000 mg/kg  
dermal, LD50, Rabbit: 23000 mg/kg

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 6 / 9

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane  
oral, LD50, Rat: > 5000 mg/kg  
dermal, LD50, Rat: > 2000 mg/kg

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane  
oral, LD50, Rat: 26800 mg/kg  
dermal, LD50, Rat: > 2000 mg/kg

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Causes skin irritation.

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

No further relevant information available.

**Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 1,8 mg/L (48 h)

Algae toxicity, ErC50: 11 mg/L (72 h)

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and

2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

Fish toxicity, LC50, fish: 2,54 mg/L (96 h)

Alcohols C13-15 (branched and linear, odd numbered), reaction product with 1-chloro-2,3-epoxypropane

Fish toxicity, LC50: 7 mg/L (96 h)

Daphnia toxicity, EC50: 7,2 mg/L (48 h)

**Long-term Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

Toxicological data are not available.

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**Bioconcentration factor (BCF)**

Toxicological data are not available.

**12.4. Mobility in soil**

Toxicological data are not available.

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 7 / 9

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Liquid product may not be disposed of with household waste or landfilled. Do not allow to enter into drains/waters or in the soil. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number or ID number**

UN 3082

**14.2. UN proper shipping name**

Land transport (ADR/RID):

Environmentally hazardous substance, liquid, n.o.s.  
(EPOXIDE RESIN)

Sea transport (IMDG):

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(EPOXIDE RESIN)

Air transport (ICAO-TI / IATA-DGR):

Environmentally hazardous substance, liquid, n.o.s.  
(EPOXIDE RESIN)

**14.3. Transport hazard class(es)**

Land transport (ADR/RID):

9

Sea transport (IMDG)

Air transport (ICAO-TI / IATA-DGR)

9

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID)

UMWELTGEFÄHRDEND

Marine pollutant

p / EPOXIDE RESIN

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

Tunnel restriction code

-

**Sea transport (IMDG)**

EmS-No.

F-A, S-F

**14.7. Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.



Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 8 / 9

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 15,000

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/j) ; VOC limit value: 500 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 112,000

#### National regulations

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

#### Full text of classification in section 3:

Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

#### Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

#### Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

**WEBAC®**

Print date: 10.11.2022  
Version: 7

WEBAC 4430 Comp. A, RAL 7030  
Revision date: 20.10.2022  
Issue date: 19.10.2022

EN  
Page 9 / 9

---

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.