

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

#### Trade name/designation

WEBAC 4430 Comp. B  
Epoxy Floor Coating

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

#### Relevant identified uses

hardener/amine component for epoxy resin

### 1.3 Details of the supplier of the safety data sheet

#### supplier

WEBAC-Chemie GmbH

Fahrenberg 22  
22885 Barsbüttel  
Deutschland

Telephone: +49 40 670570  
Telefax: +49 40 6703227

#### Department responsible for information

E-mail (competent person) msds@webac.de

### 1.4 Emergency telephone number

#### Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40  
available 24h/365days; Information will be provided in German and English

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 oral; Acute toxicity; H302 Harmful if swallowed.

Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage.

Skin Corr. 1B; Skin corrosion/irritation; H314 Causes severe skin burns and eye damage.

Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

Aquatic Chronic 3; Hazardous to the aquatic environment; H412 Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



GHS05 GHS07

#### Signal word

Danger

#### Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P260	Do not breathe vapours.
P280	Wear protective gloves and eye/face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER.

**Hazard components for labelling**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-methylenebis(cyclohexylamine)

benzyl alcohol

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

Methyleneoxide, polymer with benzenamine, hydrogenated

Phenol, methylstyrenated

**Supplemental hazard information**

not applicable

**2.3 Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients.**

**3.2 Mixtures**

**Description**

hardener/amine component for epoxy resin

**Hazardous ingredients**

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
100-51-6 202-859-9 603-057-00-5	<b>benzyl alcohol</b> 01-2119492630-38-xxxx Acute Tox. 4 H302 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 ATE (dermal): = 2.000 mg/kg ATE (oral): = 1.230 mg/kg ATE (inhalative): > 4,178 mg/L (4 h)	25,0 < 50,0
68609-08-5 614-657-1 -	<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer</b> Skin Corr. 1B H314 / Eye Dam. 1 H318	25,0 < 50,0
2855-13-2 220-666-8 612-067-00-9	<b>3-aminomethyl-3,5,5-trimethylcyclohexylamine</b> 01-2119514687-32-xxxx Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412 Specific concentration limit (SCL) Skin Sens. 1A H317: >= 0,001 ATE (dermal): = 1.840 mg/kg ATE (oral): = 1.030 mg/kg	10,0 < 25,0
135108-88-2 603-894-6 -	<b>Methyleneoxide, polymer with benzenamine, hydrogenated</b> 01-2119983522-33-xxxx Acute Tox. 4 H302 / Skin Corr. 1C H314 / Skin Sens. 1 H317 / STOT RE 2 H373 / Aquatic Chronic 3 H412 ATE (dermal): > 2.000 mg/kg ATE (oral): = 367 mg/kg	2,50 < 10,0
69-72-7 200-712-3 607-732-00-5	<b>salicylic acid</b> 01-2119486984-17-xxxx Acute Tox. 4 H302 / Eye Dam. 1 H318 / Repr. 2 H361d ATE (oral): = 891 mg/kg ATE (dermal): > 2.000 mg/kg	1,00 < 2,50
1761-71-3 217-168-8 -	<b>4,4'-methylenebis(cyclohexylamine)</b> 01-2119541673-38-xxxx Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1B H317 / STOT RE 2 H373 ATE (dermal): = 2.110 mg/kg ATE (oral): = 625 mg/kg	1,00 < 2,50
68512-30-1 270-966-8 -	<b>Phenol, methylstyrenated</b> 01-2119555274-38-xxxx Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412 ATE (oral): = 3.600 mg/kg ATE (dermal): > 2.000 mg/kg ATE (oral): > 2.000 mg/kg ATE (dermal): > 2.000 mg/kg	1,00 < 2,50

**Remark**

Full text of H- and EUH-statements: see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**Following inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

**Symptoms**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3 Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Powder, spray mist, (water)

**Unsuitable extinguishing media**

Strong water jet

**5.2 Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3 Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Ventilate affected area. Do not breathe vapours.

**6.2 Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3 Methods and material for containment and cleaning up**

**For containment**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

**For cleaning up**

Clean using cleansing agents. Do not use solvents.

**6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid breathing spray. Personal protection equipment: see section 8  
Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons.  
Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.  
Do not store together with: Food and feedingstuffs

**Storage class** LGK8A - Combustible corrosive substances

### 7.3 Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No data available

#### Biological limit values

No data available

#### DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
1761-71-3	4,4'-methylenebis(cyclohexylamine)	DNEL long-term dermal (systemic)	0,1 mg/kg bw/day
1761-71-3	4,4'-methylenebis(cyclohexylamine)	DNEL long-term inhalative (systemic)	1 mg/m³
68512-30-1	Phenol, methylstyrenated	DNEL long-term dermal (systemic)	16,4 mg/kg bw/day
68512-30-1	Phenol, methylstyrenated	DNEL long-term inhalative (systemic)	57 mg/m³
100-51-6	benzyl alcohol	DNEL acute dermal, short-term (systemic)	47 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL long-term dermal (systemic)	9,5 mg/kg bw/day
100-51-6	benzyl alcohol	DNEL acute inhalative (systemic)	450 mg/m³
100-51-6	benzyl alcohol	DNEL long-term inhalative (systemic)	90 mg/m³
69-72-7	salicylic acid	DNEL long-term dermal (systemic)	2 mg/kg bw/day
69-72-7	salicylic acid	DNEL long-term inhalative (systemic)	16 mg/m³

#### DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL long-term oral (repeated)	0,526 mg/kg

#### PNEC

CAS No.	Substance name	PNEC type	PNEC Value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, intermittent release	0,23 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sewage treatment plant (STP)	3,18 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, marine water	0,006 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC aquatic, freshwater	0,06 mg/L
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sediment, marine water	0,578 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC sediment, freshwater	5,784 mg/kg

2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	PNEC soil, freshwater	1,121 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, intermittent release	0,08 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, marine water	0,001 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC aquatic, freshwater	0,008 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sewage treatment plant (STP)	80 mg/L
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sediment, marine water	0,039 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC sediment, freshwater	0,39 mg/kg
1761-71-3	4,4'-methylenebis(cyclohexylamine)	PNEC soil, freshwater	0,072 mg/kg
68512-30-1	Phenol, methylstyrenated	PNEC aquatic, intermittent release	140 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC aquatic, marine water	1,4 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC aquatic, freshwater	14 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC sewage treatment plant (STP)	2,4 mg/L
68512-30-1	Phenol, methylstyrenated	PNEC sediment, marine water	5,3 mg/kg
68512-30-1	Phenol, methylstyrenated	PNEC sediment, freshwater	52,9 mg/kg
68512-30-1	Phenol, methylstyrenated	PNEC soil, freshwater	10,5 mg/kg
100-51-6	benzyl alcohol	PNEC aquatic, intermittent release	2,3 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, marine water	0,1 mg/L
100-51-6	benzyl alcohol	PNEC aquatic, freshwater	1 mg/L
100-51-6	benzyl alcohol	PNEC sewage treatment plant (STP)	39 mg/L
100-51-6	benzyl alcohol	PNEC sediment, marine water	0,527 mg/kg
100-51-6	benzyl alcohol	PNEC sediment, freshwater	5,27 mg/kg
100-51-6	benzyl alcohol	PNEC soil, freshwater	0,456 mg/kg
69-72-7	salicylic acid	PNEC aquatic, marine water	0,02 mg/L
69-72-7	salicylic acid	PNEC aquatic, freshwater	0,2 mg/L
69-72-7	salicylic acid	PNEC aquatic, intermittent release	1 mg/L
69-72-7	salicylic acid	PNEC sewage treatment plant (STP)	162 mg/L
69-72-7	salicylic acid	PNEC sediment, marine water	0,142 mg/kg
69-72-7	salicylic acid	PNEC sediment, freshwater	1,42 mg/kg
69-72-7	salicylic acid	PNEC soil, freshwater	0,166 mg/kg

## 8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

### Personal protection equipment

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Hand protection

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material  $\geq$  0,4 mm

Breakthrough time  $\geq$  480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

#### Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Eye glasses with side protection: EN 166

Wear closely fitting protective glasses in case of splashes.

#### Body protection

Wear suitable protective clothing. Change contaminated, saturated clothing.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	yellow
Odour	characteristic
pH	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	> 101 °C
flammability	not applicable
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	0,196 mbar
Relative vapour density	not applicable
Density at 20 °C	1,033 kg/l
Water solubility at 20°C	practically insoluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined
Viscosity at 20 °C:	> 20,5 mm²/s
particle characteristics	not applicable

### 9.2 Other information

not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions.  
Please note the expiry date.

### 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

### 10.5 Incompatible materials

No further relevant information available.

### 10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, smoke.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if swallowed.  
ATEmix: (oral) 1.243,489 mg/kg

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine

LD50: dermal (Rabbit): = 1.840 mg/kg

LD50: oral (Rat): = 1.030 mg/kg

**4,4'-methylenebis(cyclohexylamine)**

LD50: dermal (Rabbit): = 2.110 mg/kg

LD50: oral (Rat): = 625 mg/kg

**Methyleneoxide, polymer with benzenamine, hydrogenated**

LD50: dermal (Rabbit): > 2.000 mg/kg

LD50: oral (Rat): = 367 mg/kg

**Phenol, methylstyrenated**

LD50: oral (Rabbit): = 3.600 mg/kg

LD50: dermal (Rabbit): > 2.000 mg/kg

LD50: oral (Rat): > 2.000 mg/kg

LD50: dermal (Rat): > 2.000 mg/kg

**benzyl alcohol**

LD50: dermal (Rabbit): = 2.000 mg/kg

LD50: oral (Rat): = 1.230 mg/kg

LC50: inhalative (Rat): > 4,178 mg/L (4 h)

**salicylic acid**

LD50: oral (Rat): = 891 mg/kg

LD50: dermal (Rat): > 2.000 mg/kg

**Skin corrosion/irritation**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Overall assessment on CMR properties**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Indications for this are:

Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Harmful to aquatic life with long lasting effects.

**Algae toxicity**

**3-aminomethyl-3,5,5-trimethylcyclohexylamine**

ErC50: (Scenedesmus subspicatus): > 50 mg/L (72 h)

**Phenol, methylstyrenated**

ErC50: (Scenedesmus subspicatus): = 15 mg/L (72 h)



**benzyl alcohol**

ErC50: (Pseudokirchneriella subcapitata): = 770 mg/L (72 h)

NOEC (Pseudokirchneriella subcapitata): = 310 mg/L (72 h)

***Daphnia toxicity***

**3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EC50 (Daphnia magna (Big water flea)): = 23 mg/L (48 h)

Method: OECD 202

EC50 = 3 mg/L (504 h)

Method: OECD 202

**benzyl alcohol**

EC50 (Daphnia magna (Big water flea)): = 230 mg/L (48 h)

**salicylic acid**

EC50 = 870 mg/L (48 h)

***Fish toxicity***

**3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EC10: (Pseudomonas putida): = 1.120 mg/L (18 h)

Method: literature value

LC50: (Danio rerio (zebrafish)): = 110 mg/L (96 h)

**Phenol, methylstyrenated**

LC50: = 25,8 mg/L (96 h)

**benzyl alcohol**

LC50: = 460 mg/L (96 h)

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

No information available.

**12.4 Mobility in soil**

No information available.

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6 Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Product/Packaging disposal**

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Waste codes/waste designations according to EWC/AVV**

080409\* - Waste adhesives and sealants containing organic solvents or other dangerous substances  
Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Other disposal recommendations**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1 UN number or ID number**

UN 2735

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**



AMINE, FLÜSSIG, ÄTZEND, N.A.G (enthält METHYLENOXID, POLYMER MIT BENZENAMIN, HYDRIERT, 4,4'-METHYLENBIS(CYCLOHEXYLAMIN))

**Sea transport (IMDG)**

Amines, liquid, corrosive, n.o.s. (contain METHYLENEOXIDE, POLYMER WITH BENZENAMINE, HYDROGENATED, 4,4'-METHYLENEBIS(CYCLOHEXYLAMINE))

**Air transport (ICAO-TI / IATA-DGR)**

Amines, liquid, corrosive, n.o.s. (contain METHYLENEOXIDE, POLYMER WITH BENZENAMINE, HYDROGENATED, 4,4'-METHYLENEBIS(CYCLOHEXYLAMINE))

**14.3 Transport hazard class(es)**

Land transport (ADR/RID)	8
Sea transport (IMDG)	8
Air transport (ICAO-TI / IATA-DGR)	8

**14.4 Packing group**

Land transport (ADR/RID)	II
Sea transport (IMDG)	II
Air transport (ICAO-TI / IATA-DGR)	II

**14.5 Environmental hazards**

Land transport (ADR/RID)	not applicable
Sea transport (IMDG)	not applicable

**14.6 Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**14.7 Maritime transport in bulk according to IMO instruments**

No transport as bulk according to IBC Code.

**14.8 Additional information**

**Land transport (ADR/RID)**

Tunnel restriction code: E  
Limited quantity (LQ): 1 ltr  
Hazard identification number (Kemler No.): 80

**Sea transport (IMDG)**

Segregation group: IMDG-Code segregation group 18 - Alkalies  
EmS-No.: F-A, S-B  
Limited quantity (LQ): 1 ltr

**Air transport (ICAO-TI / IATA-DGR)**

not applicable

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.  
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

VOC value: 408 g/l

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

VOC limit value: 2004/42/IIA(j): 500 g/l (2010)  
Maximum VOC content of the product in a ready to use condition: 743

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**

**Hazard categories / Named dangerous substances**

This product is not classified according to Directive 2012/18/EU.

**National regulations**

Observe in addition any national regulations!

**15.2 Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**List of relevant hazard statements and/or precautionary statements from sections 2 to 15**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H412	Harmful to aquatic life with long lasting effects.

**Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

Acute Tox. 4 oral	Calculation method.
Eye Dam. 1	Calculation method.
Skin Corr. 1B	Calculation method.
Skin Sens. 1	Calculation method.
Aquatic Chronic 3	Calculation method.

**Abbreviations and acronyms**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
OEL: Occupational Exposure Limit Value  
BLV: Biological limit values  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging  
CMR: Carcinogenic, Mutagenic and Reprotoxic  
DIN: German Institute for Standardization / German industrial standard  
DNEL: Derived No-Effect Level  
EAKV: European Waste Catalogue Directive  
EC: Effective Concentration  
EC: European Community  
EN: European Standard  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG Code: International Maritime Code for Dangerous Goods  
ISO: International Organization for Standardization  
LC: Lethal Concentration  
LD: Lethal Dose  
:  
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
OECD: Organisation for Economic Cooperation and Development  
PBT: persistent, bioaccumulative, toxic  
PNEC: Predicted No Effect Concentration  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
UN: United Nations  
VOC: Volatile Organic Compounds  
vPvB: very persistent and very bioaccumulative

**Indication of changes**

\* Data changed compared with the previous version.